

(2)

NAVAL POSTGRADUATE SCHOOL

Monterey, California

THESIS

LOWER CONFIDENCE INTERVAL BOUNDS FOR COHERENT SYSTEMS WITH CYCLIC COMPONENTS

by

Valerie A. Covington

September, 1990

Thesis Advisor: W. Max Woods

Approved for public release; distribution is unlimited.



Unclassified

security classification of this page

REPORT DOCUMENTATION PAGE

1a Report Security Classification: Unclassified		1b Restrictive Markings	
2a Security Classification Authority		3 Distribution/Availability of Report: Approved for public release; distribution is unlimited.	
2b Declassification/Downgrading Schedule			
4 Performing Organization Report Number(s)		5 Monitoring Organization Report Number(s)	
6a Name of Performing Organization: Naval Postgraduate School	6b Office Symbol (*if applicable*): OR	7a Name of Monitoring Organization: Naval Postgraduate School	
6c Address (*city, state, and ZIP code*): Monterey, CA 93943-5000		7b Address (*city, state, and ZIP code*): Monterey, CA 93943-5000	
8a Name of Funding Sponsoring Organization	8b Office Symbol (*if applicable*)	9 Procurement Instrument Identification Number	
8c Address (*city, state, and ZIP code*)		10 Source of Funding Numbers	
		Program Element No	Project No / Task No / Work Unit Accession No

11 Title (*Include security classification*): LOWER CONFIDENCE INTERVAL BOUNDS FOR COHERENT SYSTEMS WITH CYCLIC COMPONENTS

12 Personal Author(s): Valerie A. Covington

13a Type of Report	13b Time Covered	14 Date of Report (*year, month, day*)	15 Page Count
Master's Thesis	From To	September 1990	132

16 Supplementary Notation: The views expressed in this thesis are those of the author and do not reflect the official policy or position of the Department of Defense or the U.S. Government.

17 Cosati Codes			18 Subject Terms (*continue on reverse if necessary and identify by block number*)
Field	Group	Subgroup	reliability, lower confidence limit, coherent systems, cyclic components.

19 Abstract (*continue on reverse if necessary and identify by block number*)

Three lower confidence interval estimation procedures for system reliability of coherent systems with cyclic components are developed and their accuracy measured using Monte Carlo techniques. The procedures use either the Poisson approximation to the Binomial distribution, the lower Binomial confidence limit procedure, or a modified procedure using the Poisson approximation to the Binomial distribution to obtain an equation for the lower confidence limit. The accuracy of the interval estimators were evaluated using standard computer simulation methods for series, parallel, series-parallel, and Wheatstone Bridge systems. The method determined to be most accurate can be combined with similar procedures for components that have continuous failure times and applied to yield a lower confidence interval procedure for the reliability of coherent systems with cyclic and continuously operating components.

20 Distribution/Availability of Abstract	21 Abstract Security Classification	
☒ unclassified unlimited ☐ same as report ☐ DTIC users	Unclassified	
22a Name of Responsible Individual: W. Max Woods	22b Telephone (*include Area code*): (408) 646-2768	22c Office Symbol: OR-Wo

DD FORM 1473,84 MAR — 83 APR edition may be used until exhausted. All other editions are obsolete

security classification of this page

Unclassified

Approved for public release; distribution is unlimited.

Lower Confidence Interval
Bounds for Coherent Systems
With Cyclic Components

by

Valerie A. Covington
Lieutenant, United States Navy
B.A., University of South Florida, 1975
M.Ed., West Georgia College, 1979

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN OPERATIONS RESEARCH

from the

NAVAL POSTGRADUATE SCHOOL
September 1990

Author: Valerie A. Covington
Valerie A. Covington

Approved by: W. Max Woods
W. Max Woods, Thesis Advisor

Lyn R. Whitaker
Lyn R. Whitaker, Second Reader

P. Purdue
Peter Purdue, Chairman,
Department of Operations Research

ABSTRACT

Three lower confidence interval estimation procedures for system reliability of coherent systems with cyclic components are developed and their accuracy measured using Monte Carlo techniques. The procedures use either the Poisson approximation to the Binomial distribution, the lower Binomial confidence limit procedure, or a modified procedure using the Poisson approximation to the Binomial distribution to obtain an equation for the lower confidence limit. The accuracy of the interval estimators were evaluated using standard computer simulation methods for series, parallel, series-parallel, and Wheatstone Bridge systems. The method determined to be most accurate can be combined with similar procedures for components that have continuous failure times and applied to yield a lower confidence interval procedure for the reliability of coherent systems with cyclic and continuously operating components.

THESIS DISCLAIMER

The reader is cautioned that computer programs developed in this research may not have been exercised for all cases of interest. While every effort has been made, within the time available, to ensure that the programs are free of computational and logic errors, they cannot be considered validated. Any application of these programs without additional verification is at the risk of the user.

TABLE OF CONTENTS

LIST OF TABLES

LIST OF FIGURES

I. INTRODUCTION

Coherent systems are those systems for which the system performs if all components function, the system fails if all the components fail, replacing a failed component with a working component does not cause the system to fail and similarly replacing a working component with a failed component does not cause the system to work [Ref. 1: p. 343]. The reliability of a coherent system is not reduced when the reliability of its components is increased. Cyclic components are those whose function is measured on a pass-fail basis and whose reliability is computed from a discrete probability distribution, usually the Geometric distribution.

The problem of obtaining confidence limits on the reliability of a coherent system based on data gathered on its individual components has attracted considerable interest. Confidence bounds for the reliability of series systems have been obtained asymptotically, based on methods such as Likelihood Ratio, Maximum Likelihood, or Modified Maximum Likelihood. Asymptotic methods are inaccurate at higher percentiles unless the component sample sizes are large. Bayesian methods have been developed for this problem, but they are extremely sensitive to the selection of the prior distribution. [Ref. 2: p. 21]

Exact confidence limits have been obtained for simple systems. This solution requires that the reliability of at least one of the components has to be greater than that of the system. However, identifying such a component becomes quite complex for all but simple systems composed of no more than two or three components [Ref. 3: p. 220]. Exact methods have also been developed for series systems using asymptotic approaches and the unbiased minimum variance estimators of the probability of success, p, based on Binomial data [Ref. 4: p. 782].

Unfortunately, none of the above referenced interval estimation procedures based on discrete data can be readily used in conjunction with the data of components that have continuous failure times. Therefore it is difficult to obtain interval estimates for the reliability of complex systems that have mixtures of cyclic components and components that operate continuously. The methods developed in this thesis can be combined with similiar methods that use continuous data, namely those developed by Lee [Ref. 5]. The combination of these methods may provide interval estimation for the reliability of systems with cyclic and continuously operating components.

In this thesis, three procedures that provide lower confidence limits for the reliability of coherent systems with cyclic components were analyzed. These procedures use only discrete data. There is a problem with using component data to establish system reliability, especially for a system that has quite a bit of redundancy. Even though the tested components fail individually and their estimated reliabilities are moderate, had these components been assembled into a system, the system could very well have worked. In such a case, the system has a very high degree of reliability and methods that work well in estimating the more moderate component reliability will not work well in estimating the system reliability. Thus, each procedure that we study has modifications to accommodate component test data which when assembled into systems would exhibit zero system failures, one system failure, or more than one system failure, i.e.

- no component failures occur or only components fail that are redundant in the system, so that no system failure could occur if all the components were combined to form systems,
- exactly one component fails that would result in a system failure or redundant components in the system fail in a quantity, so that no more than one system failure could occur if the components were combined to form systems (this modification is explained in more detail in the following chapters),
- for any component, i, more than one component fails out of n_i tested which would lead to more than one system failure.

The systems analyzed in this thesis are as follows:

- all components arranged in series (see Figure 1)



Figure 1. Series System

- all components arranged in series with at least one component consisting of two parallel subcomponents (see Figure 2)



Figure 2. Series-Parallel System

- all components arranged in series with at least one component consisting of two parallel subcomponents and at least one component in a two out of three subcomponent parallel arrangement (see Figure 3)



Figure 3. Series Parallel With Two Out of Three Subcomponent System

- a system with all components in a parallel arrangement (see Figure 4)



Figure 4. Parallel System

- a five component redundant system commonly referred to as a Wheatstone Bridge (see Figure 5)



Figure 5. Wheatstone Bridge

II. PREFERRED LOWER CONFIDENCE LIMIT FOR SYSTEM RELIABILITY

A. METHODOLOGY

The procedure selected to determine the lower confidence limit of relatively simple complex systems uses a method employed by Lomnicki [Ref. 6: p. 109] and extended by Myhre and others [Ref. 2: p. 213]. It uses the Poisson approximation to the Binomial distribution when numerous component failures occur that would result in multiple system failures if the tested components were assembled into systems. In cases where zero system failures occur or only one system failure could result from the failed components, the Poisson approximation appears to be conservative and the lower confidence limit is computed using the Binomial distribution directly.

Suppose a coherent system has k different types of components that are statistically independent. Test data is available on each type of component. The n_i tests for component i are assumed to be independent Bernoulli trials with probability of failure, q_i, for each test. Therefore the number of failures, F_i, in these n_i tests has a Binomial distribution.

Any of the k components, say component m, can be chosen as a base component and q_i expressed as a fraction or multiple, a_i, of q_m. That is

$$q_i = a_i q_m. \tag{2.1}$$

Suppose it is appropriate to assume that the probability distribution of the number of failures of each component, F_i, can be approximated by the Poisson distribution with mean $n_i q_i$. If $F = \sum_{i=1}^{k} F_i$, then from Equation (2.1), the distribution of F is approximately Poisson with parameter $q_m \sum_{i=1}^{k} n_i a_i$. Consequently the mean of F, $E(F)$, is given by

$$E(F) = q_m \sum_{i=1}^{k} n_i a_i \tag{2.2}$$

The system reliability, R_s, can be defined as a function of the unreliability, q_m and the associated values $a_i = \frac{q_i}{q_m}$. That is,

$$R_s = h(q_m, a_1, a_2, \ldots, a_k) \tag{2.3}$$

By definition, h is non-increasing in q_m, because the system is coherent. If $a_1, a_2,..., a_k$ are known, an approximate lower confidence limit, $R_{s,L(\alpha)}$, may be obtained from an upper confidence limit, $\hat{q}_{m,U(\alpha)}$, for q_m by the equation

$$\hat{R}_{s,L(\alpha)} = h(\hat{q}_{m,U(\alpha)}, a_1, a_2,..., a_k) \tag{2.4}$$

When appropriate, the upper confidence limit, $\hat{q}_{m,U(\alpha)}$, may be obtained from the well known upper confidence limit for the mean, λ, of a Poisson distribution, namely, if F is distributed POISSON(λ) then

$$\lambda_{U(\alpha)} = \frac{X^2_{\alpha,\,2(1+F)}}{2} \tag{2.5}$$

where $X^2_{\alpha,2(1-F)}$ is the $(1-\alpha)$ quantile of a Chi-square probability distribution with degrees of freedom equivalent to $2(1+F)$, where F is the number of system failures. From Equation (2.2), substitution of $q_m \sum_{i=1}^{k} n_i a_i$ for λ into Equation (2.5) gives

$$q_{m,U(\alpha)} = \frac{X^2_{\alpha,\,2(1+F)}}{2\sum_{i=1}^{k} n_i a_i} \tag{2.6}$$

If the a_i are unknown then an approximate upper confidence limit, $\hat{q}_{m,U(\alpha)}$ is given by

$$\hat{q}_{m,U(\alpha)} = \frac{X^2_{\alpha,\,2(1+F)}}{2\sum_{i=1}^{k} n_i \hat{a}_i} \tag{2.7}$$

where $\hat{a}_i$ is an estimator for a_i, $i = 1,2,...,k$.

The Poisson approximation to the Binomial distribution is conservative when all F_i equal zero or redundant components of the system fail in such a way that results in zero system failures. In this case, let n^* represent the number of system tests equivalent to testing each component n_i times, $i = 1,...,k$. Then the distribution of s, the number of system tests that would have been successful, is approximately Binomial(n^*,R_s). If s is distributed BINOMIAL(n^*,R_s) then we can use the binomial lower confidence limit

$$\hat{R}_{s,L(\alpha)} = \sqrt[n^*]{\alpha} \tag{2.8}$$

to compute the lower confidence limit for system reliability. The following two methods for the calculation of the number of equivalent system tests, n^*, were selected and each applied separately using Equation (2.8).

$$n_1^* = \min(n_1, n_2, \ldots, n_k) \tag{2.9}$$

$$n_2^* = \frac{\sum_{i=1}^{k} n_i}{k} \tag{2.10}$$

where n_i is the number of tests of component i.

Some instances of component failures could only result in one equivalent system failure if all of the tested components were combined into complete systems. In this case, we again define n^* and treat n^* system trials with one failure. The resulting lower confidence limit, $\hat{R}_{s,L(\alpha)}$, for system reliability is the solution for $p = (1 - q)$ in the equation

$$\alpha = \sum_{j=n^*-1}^{n^*} \binom{n^*}{j} (1-q)^j q^{n^*-j} \tag{2.11}$$

In the Wheatstone Bridge case, two or more component failures among the tested components could result in one system failure if the components are assembled into Wheatstone systems. In this case we set $n^* = n_1^*$ for one interval procedure and $n^* = n_2^*$ for the second interval procedure.

In a series system, n^* is equal to the number of tests performed on the failed single component, because the reliability of the system is determined largely by the reliability of the least reliable component. Since it is difficult to solve for p in Equation (2.11), an equivalent equation using the Snedecor F distribution is used. Thus,

$$\hat{R}_{s,\,L(\alpha)} = \frac{s}{s + (f+1)\mathrm{F}_{(1-\alpha),2(f+1),2s}} \tag{2.12}$$

where s is the number of system successes, f is the number of system failures, and $\mathrm{F}_{(1-\alpha),2(f-1),2s}$ is the α quantile of the Snedecor F distribution with $2(f+1)$ and $2s$ degrees of freedom [Ref. 7: p. 43].

B. RESULTS

The accuracy of this procedure was evaluated using computer simulations for each of the following systems described in Section A:

- series systems
- series sytems where the second component is composed of two parallel subcomponents
- series systems where the second component is composed of two parallel subcomponents and the fourth component consists of a two of three subcomponent parallel arrangement
- parallel systems
- Wheatstone Bridge

Groups of test data were generated where the parameters, q_i and n_i were chosen to control the expected number of failures, $E[f] = \sum_{i=1}^{k} n_i q_i$. Confidence levels of 0.20 and 0.05 were used in each case. A total of 1000 replications were generated for each set of parameter values. Each replication produced one value of $\hat{R}_{s,L(\alpha)}$. These 1000 values, $\hat{R}_{s,L(\alpha)}$, were ordered and used to get the simulated probability distribution of $\hat{R}_{s,L(\alpha)}$. The simulation procedures are described in Chapter IV. The 80^{th} and 95^{th} percentile point of the simulated probability distribution of $\hat{R}_{s,L(\alpha)}$ was compared to R_s for determining the accuracy of the procedure. This comparison is made because $\hat{R}_{s,L(\alpha)}$ is the lower $100(1-\alpha)$ percentile confidence limit for R_s if $1-\alpha = P(\hat{R}_{s,L(\alpha)} \leq R_s)$. This equation states that R_s is the $100(1-\alpha)$ percentile point of the probability distribution of $\hat{R}_{s,L(\alpha)}$. The "true confidence level" is the percentile point of the simulated distribution corresponding to the true value of R_s.

The parameter values $n_1q_1, n_2q_2, \ldots, n_kq_k$ determine a case number and are labeled as such in the tables that describe the simulation results. A summary table that provides the parameter values, q_i and n_i , is given in Appendix B.

All tables report the 80^{th} and 95^{th} percentile points of the simulated distribution of $\hat{R}_{s,L(\alpha)}$ and appear in the tables under the column labeled $\hat{R}'_{s,L(\alpha)}$.

1. Series System

By definition, the reliability, R_s, for a series system of k independent components is

$$R_s = \prod_{i=1}^{k}(1-q_i) = \prod_{i=1}^{k}(1-a_i q_m) \tag{2.13}$$

The corresponding lower confidence limit is given by

$$\hat{R}_{s,L(\alpha)} = \prod_{i=1}^{k} (1 - \hat{a}_i \hat{q}_{m_i,U(\alpha)}) \tag{2.14}$$

These formulae are used to calculate the reliability when at least two components fail. If zero components fail Equation (2.8) is used and if one component fails Equation (2.12) is used. The results are presented in Table 1. In Table 1, column 1 of $\hat{R}'_{s,L(\alpha)}$ is calculated using Equation (2.10) and column 2 is calculated using Equation (2.9) for n^* when the component failures equate to zero system failures.

Table 1. SERIES SYSTEM

Case	# Compts	$E[F]$	R_s	α Level	$\hat{R}'_{s,L(\alpha)}$		True Confidence Level	
1	5	1.03	.95572	.20	.91447	.90345	75	75
				.05	.85140	.85140	100	100
2	10	1.2	.93206	.20	.88491	.88491	100	100
				.05	.85140	.85140	100	100
3	5	4.9	.95084	.20	.95361	.95361	76	76
				.05	.95969	.95969	90	90
4	10	4.9	.85951	.20	.85369	.85369	85.2	85.2
				.05	.86718	.86089	94.5	94.5
5	5	5.74	.95084	.20	.95036	.95036	76.3	76.3
				.05	.95779	.95779	91.1	91.1
6	10	5.75	85951	.20	.85910	.85910	80.1	80.1
				.05	.88114	.88072	92.5	92.6
7	5	10.5	.85828	.20	.87174	.87174	72.4	72.4
				.05	.88366	.88366	86.6	86.6
8	10	10.5	.85951	.20	.87137	.87137	73.3	73.3
				.05	.89049	.89049	86.4	86.4

In some cases the true confidence level equals 100. This is not uncommon for confidence intervals based on discrete data and is further explained in Appendix A.

2. Series-Parallel Systems

A modification was made to the series systems to form the series-parallel system. The second component in the series was modified to consist of two parallel subcomponents of equal unrelibility, q_{2_i}. For the second component to fail both subcomponents must fail. The unreliability of component two is $q_{2_i}^2$. Since component two is in series with the other components the corresponding lower confidence limit is calculated using Equation (2.8) when the equivalent number of system failures is zero, Equation (2.12) when the number of system failures is one, and Equation (2.14) is used in all other cases. The results are presented in Table 2. In Table 2, column 1 of $\hat{R}'_{s,L(\alpha)}$ is calculated using Equation (2.10) and column 2 is calculated using Equation (2.9) for n^* when the component failures equate to zero system failures.

Table 2. SERIES-PARALLEL SYSTEM

Case	# Compts	$E[F]$	R_s	α Level	$\hat{R}'_{s,L(\alpha)}$		True Confidence Level	
9	5	1.03	.95572	.20	.91447	.90345	75	75
				.05	.85140	.85140	100	100
10	10	2.72	.93206	.20	.95770	.95770	64.5	64.5
				.05	.95344	.95344	74.4	64.5
11	5	4.9	.85828	.20	.85369	.85369	83.5	83.5
				.05	.86685	.86089	94.2	94.3
12	10	4.9	.85951	.20	.85546	.85546	83.1	83.1
				.05	.86685	.86685	94.1	94.1
13	5	9.79	.95084	.20	.95321	.95321	76.8	76.8
				.05	.95779	.96029	88.6	88.6
14	10	10.5	85951	.20	.85943	.86943	75.2	75.2
				.05	.88606	.88606	87.6	87.6

Note the accuracy of the lower confidence interval is somewhat reasonable when the expected number of failures exceeds 4.9 in both the series and series-parallel systems.

3. Series-Parallel Systems with a 2 of 3 Parallel Component

Another modification was made to the five and ten component series systems. The third component in the series was modified and now consists of three parallel subcomponents of equal unreliability, q_{3_i}. For this component to fail, two or three parallel components must fail. The unreliability, q_3, of component three is $\binom{3}{2}(1-q_{3_i})q_{3_i}^2 + q_{3_i}^3$.

The fourth component of each system is composed of two parallel subcomponents as defined in the series-parallel system. Since these components are in series with the other components, the corresponding lower-confidence limit is calculated using the same series of equations as the series-parallel system. The results are presented in Table 3. The term n^* is computed from Equation (2.10) when the equivalent number of system failures is zero.

Table 3. SERIES-PARALLEL WITH A 2 OUT OF 3 COMPONENT SYSTEM

Case	# Compts	$E[F]$	R_s	α Level	$\hat{R}'_{s,L(\alpha)}$	True Confidence Level
15	5	.88	.96525	.20	.91447	100
				.05	.85140	100
16	10	2.6	.94136	.20	.95770	63.7
				.05	.95344	85.7
17	5	3.21	.96035	.20	.95937	80.4
				.05	.96877	88.5
18	10	4.6	.88945	.20	.88582	80.9
				.05	.91735	89.5
19	5	6.17	.96035	.20	.96126	78.8
				.05	.96886	90.5
20	10	8.37	.88917	.20	.89734	76.7
				.05	.91817	87.8

Another series of simulations were conducted on these systems. For each case previously run, new cases were defined by decreasing the unreliability of selected components without changing the number of component tests. These changes result in a decrease in the number of expected failures and an increase in the reliability of the system. The results are presented in Table 4. The term n^* is computed from Equation (2.10) when the equivalent number of system failures is zero.

Table 4. SERIES-PARALLEL WITH A 2 OUT OF 3 COMPONENT SYSTEM (CONSTANT NUMBER OF MISSION TESTS, DECREASING RELIABILITY)

Case	# Compts	$E[F]$	R_s	% Level	$\hat{R}'_{s,L(\alpha)}$	True Confidence Level
21	10	.51	.99136	.20	.97661	100
				.05	.95690	100
22	10	1.68	.96836	.20	.97661	72.3
				.05	.95690	96.3
23	10	6.57	.95430	.20	.95497	77.2
				.05	.96169	91.3
24	10	9.90	.90249	.20	.90515	78.9
				.05	.91486	91.6

Tables 3 and 4 indicate that for $E(F) > 5$ the lower confidence limits are reasonably accurate.

4. Parallel System

The accuracy of the lower confidence procedure was evaluated when it was applied to a five component system with each component, i, in parallel with the others. The unreliabilities, q, of each component are equal and the unreliability of the system is defined as q^5. For the system to fail all five components must fail. The results of the computer simulations are presented in Table 5. The term n^* is computed from Equation (2.10) when the equivalent number of system failures is zero. If n of these components are tested and four or fewer failures occur, then no system failures would have occured had these components been assembled into systems. The lower confidence limit is calculated using Equation (2.8) when the equivalent number of system failures is zero, Equation (2.12) when the number of system failures is one, and Equation (2.14), with $k = 1$, in all other cases.

Table 5. PARALLEL SYSTEM

Case	# Compts	$E[F]$	R_s	α Level	$\hat{R}'_{s,L(\alpha)}$	True Confidence Level
25	5	1	.99000	.20	.98403	100
				.05	.97049	100
26	5	4	.96000	.20	.95770	91.1
				.05	.95344	98.3
27	5	6	.94000	.20	.93370	83.9
				.05	.93838	98.2
28	5	9	.94000	.20	.94012	77.6
				.05	.94002	93.6

5. Wheatstone Bridge

By definition, the reliability, R_s, for the Wheatstone Bridge, in Figure 5, with five independent components is

$$\begin{aligned} R_s = {} & p_1p_4 + p_2p_5 + p_1p_2p_5 + p_2p_3p_4 - p_1p_2p_3p_4 \\ & - p_1p_2p_4p_5 - p_1p_3p_4p_5 - p_2p_3p_4p_5 + 2p_1p_2p_3p_4p_5 \end{aligned} \tag{2.16}$$

where $p_i = (1 - q_i)$. In terms of q_i Equation (2.16) becomes

$$\begin{aligned} R_s &= h(q_m, a_1, \ldots, a_5) \\ &= 1 - q_m^2(a_1a_2 + a_4a_5) - q_m^3(a_1a_3a_5 + a_2a_3a_4) \\ &+ q_m^4(a_1a_2a_3a_4 + a_1a_2a_3a_5 + a_1a_2a_4a_5 + a_1a_3a_4a_5 + a_2a_3a_4a_5) \\ &- 2q_m^5(a_1a_2a_3a_4a_5) \end{aligned} \tag{2.17}$$

[Ref. 2: p. 215]. By substituting $\hat{a}_i\hat{q}_{m,U(\alpha)}$ for q_i, the corresponding lower confidence limit is obtained.

$$\hat{R}_{s,L(\alpha)} = h(\hat{q}_{m,U(\alpha)}, \hat{a}_1, \ldots, \hat{a}_5) \tag{2.18}$$

The reliability of the Wheatstone Bridge system is normally high due to the redundancy of the system. This system experiences zero system failures in the following five different failure patterns.

- $F_1 = F_2 = F_3 = F_4 = F_5 = 0$
- $F_1 = F_3 = F_5 = 0$
- $F_1 = F_4 = 0$
- $F_2 = F_5 = 0$
- $F_2 = F_3 = F_4 = 0$

where F_i is the number of failures of component i, among its n_i tests. Any other failure patterns will produce one or more system failures. The lower confidence limit is calculated using Equation (2.8) when the equivalent number of system failures is zero, Equation (2.12) when the number of system failures is one, and Equation (2.18) in all other cases. The results of the computer simulations are presented in Table 6. In Table 6, column 1 of $\hat{R}'_{s,L(\alpha)}$ is calculated using Equation (2.10) and column 2 is calculated using Equation (2.9) for n^* when the component failures equate to zero system failures.

Table 6. WHEATSTONE BRIDGE SYSTEM

Case	# Compts	$E[F]$	R_s	α Level	$\hat{R}'_{s,L(\alpha)}$		True Confidence Level	
29	5	5.75	.99776	.20	.99658	.99658	88.6	88.6
				.05	.99766	.99766	95.4	95.4
30	5	6	.99976	.20	.99960	.99960	91.4	91
				.05	.99966	.99966	98.3	98.3
31	5	.5	.99977	.20	.91447	.72478	100	100
				.05	.98678	.98678	100	100
32	5	.5	.99977	.20	.92622	.72478	100	100
				.05	.99339	.99339	100	100

The system reliability values in cases 31 and 32 are too large for these interval estimation procedures to be accurate using the sample sizes given in Table 15 in Appendix B. Also, more than 1000 replications would be needed to assess the accuracy of any lower confidence limit procedure for system reliability when the true system reliability is as large as it is in these cases.

III. ALTERNATE PROCEDURE A FOR THE LOWER CONFIDENCE LIMIT FOR SYSTEM RELIABILITY

A. METHODOLOGY

This procedure determines the lower confidence limit for simple and complex systems using only the Poisson approximation to the Binomial distribuiton. It is used extensively by Bellini [Ref. 8: p.4-6].

This procedure uses the principles outlined in Chapter II of this thesis except in the cases where there are zero or one system failure. In the case where there are zero system failures (no components fail) the estimated unreliabilty, $\hat{q}_i$, becomes zero because $\hat{q}_i = \frac{F_i}{N_i}$ where F_i is the number of failures in n_i mission tests of component i. Therefore, the value of $\hat{a}_i$, the estimated value of a_i, becomes zero and Equation (2.7) becomes undefined. When this occurs the estimated lower confidence limit of the system reliability, $\hat{R}_{s,L(\alpha)}$, is defined as

$$\hat{R}_{s,L(\alpha)} = 1 - \frac{X^2_{\alpha,2}}{2n^*} \tag{3.1}$$

where n^* is defined as in Equation (2.10).

If only component, m, fails the value of $\hat{a}_m$ is equal to 1. The $\hat{a}_i$ for all other components are zero, and the lower confidence limit, $\hat{R}_{s,L(\alpha)}$ is defined as

$$\hat{R}_{s,L(\alpha)} = 1 - \frac{X^2_{\alpha,2(1+F)}}{2n_m} \tag{3.2}$$

where n_m is the number of mission tests of the failed component.

B. RESULTS

The accuracy of this procedure was evaluated only for series and Wheatstone Bridge systems. Testing was limited because a comparision of results of the three procedures, discussed in this thesis, indicated this procedure to be less accurate in determining the lower confidence limit for the reliability of simple systems. This observation is noted in those systems experiencing zero system failures or one system failure. Selected results illustrating the accuracy of this procedure compared to the accuracy of the preferred

procedure" (Chapter II) are indicated in Tables 7 and 8. The term n^* is computed from Equation (2.10) when the equivalent number of system failures is zero.

Table 7. COMPARISON OF PREFERRED PROCEDURE AND ALTERNATE PROCEDURE A (SERIES SYSTEM)

			Preferred Procedure		Alternate Procedure	
Case	R_s	α Level	$\hat{R}'_{s,L(z)}$	True Confidence Level	$\hat{R}'_{s,L(z)}$	True Confidence Level
1	.95572	.20	.91447	75	.83140	100
		.05	.85140	100	.92356	100
2	.93206	.20	.88491	100	.83140	100
		.05	.85140	100	.92356	100
3	.95084	.20	.95361	76	.95361	76
		.05	.95969	90	.95969	90
4	.85951	.20	.85369	85.2	.85119	85.5
		..05	.86718	94.5	.85083	95.2
5	.95084	.20	.95036	76.3	.95036	80.3
		.05	.95779	91.1	.96359	89.6
6	.85951	.20	.85910	80.1	.86910	80
		.05	.88114	92.5	.88072	92.9
7	.85828	.20	.87174	72.4	.87174	72.4
		.05	.88366	86.6	.88366	86.6
8	.85951	.20	.87137	73.3	.87137	73.3
		.05	.89049	86.4	.89049	86.4

Table 8. COMPARISION OF PREFERRED PROCEDURE AND ALTERNATE PROCEDURE A (WHEATSTONE BRIDGE)

			Preferred Procedure		Alternate Procedure	
Case	R_s	α Level	$\hat{R}'_{s,L(z)}$	True Confidence Level	$\hat{R}'_{s,L(z)}$	True Confidence Level
29	.99776	.20	.99658	88.6	1.000	63.6
		.05	.99766	95.4	1.000	70.4
30	.99976	.20	.99960	91.4	1.000	66.2
		.05	.99966	98.3	1.000	73.1
31	.99977	.20	.91447	100	.72478	91.8
		.05	.98678	100	1.000	91.8
32	.99977	.20	.92622	100	.99549	93.7
		.05	.99339	100	1.000	93.7

This alternate procedure produced lower confidence limits that were more conservative than those produced by the "preferred procedure".

IV. ALTERNATE PROCEDURE B FOR THE LOWER CONFIDENCE LIMIT FOR SYSTEM RELIABILITY

A. METHODOLOGY

The purpose of this alternate procedure was to construct a procedure that accommodates zero component failures in a different manner than that employed in other procedures. This procedure redefines the estimated value, $\hat{a}_i$, of a_i, and in so doing uses the Poisson approximation to the Binomial distribution.

Suppose a component, i, undergoes n_i tests where there is a probability of success, p_i, on each component test. Let F_i be the number of failures in these n_i tests. We define $F = \sum_{i=1}^{k} F_i$.

The 50 percent lower binomial confidence limit for the reliability of component i, $\hat{p}_{i,L}$, can be determined by using its number of failures, F_i, and number of tests, n_i. The upper Biniomial confidence limit, $\hat{q}_{i,U}$, is equal to $1 - \hat{p}_{i,L}$. In this alternate procedure we define $\hat{a}_i$ by

$$\hat{a}_i = \frac{\hat{q}_{i,U}}{\hat{q}_{m,U}} \tag{4.1}$$

where $\hat{q}_{m,U} = \max(\hat{q}_{1,U}, \hat{q}_{2,U}, \ldots, \hat{q}_{k,U})$. Note that the index will be determined by the data and $\hat{a}_i$ is well defined even if no components fail. The probability distribution of F_i is approximated by the Poisson distribution. The estimated upper confidence limit, $\hat{q}_{m,U(s)}$, can be calculated using Equation (2.7) and the system reliability lower confidence limit, $\hat{R}_{s,L(s)}$, can be obtained from Equation (2.4) where $\hat{a}_i$ is defined by Equation (4.1).

This procedure is used without exception, regardless of the number of system failures.

B. RESULTS

This procedure was evaluated only on series and Wheatstone Bridge systems. Evaluations were limited because a comparision of the results with other procedures discussed in this thesis, indicated this procedure to be less accurate. Selected results illustrating the accuracy of this procedure compared to the accuracy of the "preferred procedure" (Chapter II) are indicated in Tables 9 and 10. The term n^* is computed for Equation (2.10) when the equivalent number of system failures is zero.

Table 9. COMPARISON OF PREFERRED PROCEDURE AND ALTERNATE PROCEDURE B (SERIES SYSTEM)

			Preferred Procedure		Alternate Procedure	
Case	R_s	α Level	$\hat{R}'_{s,L(\alpha)}$	True Confidence Level	$\hat{R}'_{s,L(\alpha)}$	True Confidence Level
1	.95572	.20	.91447	75	.97788	37.1
		.05	.85140	100	.99489	7.4
2	.93206	.20	.88491	100	.97197	70.3
		.05	.85140	100	.99350	33.2
3	.95084	.20	.95361	76	.97294	25.7
		.05	.95969	90	.98732	9.7
4	.85951	.20	.85369	85.2	.93224	26.7
		..05	.86718	94.5	.97896	8.3
5	.95084	.20	.95036	76.3	.97497	30.1
		.05	.95779	91.1	.99155	9.2
6	.85951	.20	.85910	80.1	.91470	39
		.05	.88114	92.5	.97405	7.1
7	.85828	.20	.87174	72.4	.89848	44.5
		.05	.88366	86.6	.94607	19.4
8	.85951	.20	.87137	73.3	.88412	56.3
		.05	.89049	86.4	.93886	24.9

Cases 4, 5, and 6 in Table 9 clearly illustrate a more accurate "preferred procedure" for a series system.

Table 10. COMPARISION OF PREFERRED PROCEDURE AND ALTERNATE PROCEDURE B (WHEATSTONE BRIDGE)

			Preferred Procedure		Alternate Procedure	
Case	R_s	α Level	$\hat{R}'_{s,L(\alpha)}$	True Confidence Level	$\hat{R}'_{s,L(\alpha)}$	True Confidence Level
29	.99776	.20	.99658	88.6	98123	90.1
		.05	.99766	95.4	98235	97.6
30	.99976	.20	.99960	91.4	99810	92.0
		.05	.99966	98.3	99856	99.1
31	.99977	.20	.91447	100	.90478	91.8
		.05	.98678	100	.99900	91.8.
32	.99977	.20	.92622	100	90932	100
		.05	.99339	100	99221	100

In the case of the Wheatstone Bridge, Table 10 illustrates that the "preferred procedure" is more accurate than the "alternate procedure".

V. SIMULATION

Standard simulation techniques are used to determine the accuracy of the lower confidence limit procedures. Some of the basic simulation programs were developed by Bellini [Ref. 8: Appendix A]. Each program was modified to incorporate the necessary mathematical formulae that are needed to define the lower confidence limit for a particular procedure.

Input parameters needed to run the computer programs are

- k - number of components in the system
- $\overline{n}$ - vector of component tests $(n_1, n_2, ..., n_k)$
- $\overline{q}$ - vector of component unreliabilites $(q_1, q_2, ... q_k)$
- α - level of confidence

Note that the value of system reliability, R_s, is determined by the vector $\overline{q}$.

The NON-IMSL random number generator, SRND, was used to simulate the success or failure of each test of the k components. From this data, the values of $\hat{q}_i$, $\hat{a}_i$, $\hat{q}_{m,U(\alpha)}$, and $\hat{R}_{s,L(\alpha)}$ are calculated. Each scenario was replicated 1000 times to generate 1000 ordered values of $\hat{R}_{s,L(\alpha)}$. The $1000(1-\alpha)^{th}$ ordered value, $\hat{R}_{s,L(\alpha),1000(1-\alpha)}$ from smallest to largest denotes the $100(1-\alpha)^{th}$ percentile point of the probability distribution of $\hat{R}_{s,L(\alpha)}$. If the lower confidence limit procedure is exact, $\hat{R}_{s,L(\alpha),1000(1-\alpha)}$ should equal R_s. The percentiles in all of the tables are the values of $\hat{R}_{s,L(\alpha),1000(1-\alpha)}$. A true confidence limit is then determined by finding the element of the vector of replications which is closest to R_s and noting its index number, j. The true confidence level is then calculated to be $\frac{j}{1000} \times 100$.

A system report is generated and reports to the analyst the following information.

- q_i - unreliability of each component, i
- a_i - fraction of unreliability of base component, m
- n_i - number of mission tests for each component, i
- R_s - true system reliability
- $\hat{R}_{s,L(\alpha)}$ - estimated lower confidence limit for the $100(1-\alpha)$ percentile
- difference between R_s and $\hat{R}_{s,L(\alpha)}$
- true confidence level

VI. CONCLUSIONS AND RECOMMENDATIONS

The accuracies of three approximate interval estimation procedures, based on discrete component data, for the reliability of coherent systems were analyzed in this thesis. Computer simulations were used to perform this analysis. Each interval estimation method employs ratios of component failure rate estimates when two or more different component types have at least one failure. This specific ratio feature is needed to extend this work to more complex systems with mixtures of cyclic components and componenets whose failure times have a continuous probability distribution.

The simulations reveal that the method labeled the "preferred method" in this thesis appears to be reasonably accurate if four or more failures are expected to occur among all components tested. However, any general interpretation of this type is not warranted at this time. The potential for error can be significant if several components have relatively small samples (less than 15) and zero failures. Zero failures joined with small sample sizes will always be the bane of classical interval estimation procedures.

The ratio procedure does allow the possible use of information extraneous to the data. Previous test programs on similar hardware operating under similar environments, as that present for the current test data, might be used to modify the component failure rate estimates or prehaps only the ratios of the failure rate estimates. So called "off the shelf" hardware purchased in accordance with existing DOD specifications would be prime candidates for this type of failure rate modification. Supplementing current test data with other existing "similar" data has become more common as resources for reliability demonstration testing has been reduced.

APPENDIX A. DISCRETE CONFIDENCE LIMIT PROPERTIES

Equations for confidence limits on parameters of discrete probability distributions are not exact. If $\hat{p}_{L(\alpha)}$ is the lower $100(1-\alpha)$ percent confidence limit for the parameter p in the Binomial distribution, then $\hat{p}_{L(\alpha)}$ is defined so that

$$P(\hat{p}_{L(\alpha)} < p) \geq 1 - \alpha \qquad (A1)$$

If the parameter p, is the probability of success on each trial in a sample of size n and s is the observed number of successes then $\hat{p}_{L(\alpha)}$ is the solution for p in the equation

$$\sum_{j=s}^{n} \binom{n}{j} p^j (1-p)^{n-j} = \alpha \qquad (A2)$$

if $s > 0$, and $\hat{p}_{L(\alpha)} = 0$ if $s = 0$. Specifically, suppose $s = n$ then in Equation (A2), $\hat{p}_{L(\alpha)} = \sqrt[n]{\alpha}$. This is the largest value of $\hat{p}_{L(\alpha)}$. Consequently if the true value of p is greater than $\sqrt[n]{\alpha}$ then $P(\hat{p}_{L(\alpha)} \leq p) = 1$. This has important implications when analyzing computer simulations of confidence limit procedures based on discrete data to assess their accuracy. If the value of p used to generate the data on the computer is greater than $\sqrt[n]{\alpha}$, then all of the $\hat{p}_{L(\alpha)}$ values will be smaller than p and the analysis will show the procedure has confidence level 100 . This is to be expected when evaluating these confidence interval procedures for some choices of sample sizes and parameter values.

The exact value of $P(\hat{p}_{L(\alpha)} \leq p)$ depends on the sample size, n, and the true value of p. For fixed n, the possible values of s are 0,1,2,...,n. Each value of s yields a specific value of $\hat{p}_{L(\alpha)}$, say $p(s)$. Consequently,

$$P(\hat{p}_{L(\alpha)} = p(s) \mid p) = P(S = s \mid p) \qquad (A3)$$

and

$$P(\hat{p}_{L(\alpha)} < p(s) \mid p) = P(S < s \mid p) \qquad (A4)$$

If the true value of p equals $\hat{p}_{L(\alpha)}(s)$ for some s then, the probability in Equation (A4) has the value $1 - \alpha$ because this value of p satisfies Equation (A2). Consequently if the true value of p equals any of the values $p(n), p(n-1), \ldots, p(1)$, then $P(\hat{p}_{L(\alpha)} < p) = 1 - \alpha$.

For all other values of p, $P(\hat{p}_{L(\alpha)} < p) > 1 - \alpha$. Figure 6 is a sketch of the behavior of this phenomena for $\alpha = .10$ and $n = 5$.



Figure 6. Behavior of $P(\hat{p}_{L(\alpha)} < p)$

APPENDIX B. INPUT PARAMETERS

Table 11. SERIES SYSTEM INPUT PARAMETERS

Case		Components									
		1	2	3	4	5	6	7	8	9	10
1	q_i	.02	.01	.005	.005	.005					
	n_i	30	25	20	10	5					
2	q_i	.02	.01	.005	.005	.005	.005	.005	.005	.005	.005
	n_i	30	25	20	15	10	5	5	5	5	5
3	q_i	.01	.005	.003	.008	.025					
	n_i	200	400	720	265	80					
4	q_i	.005	.01	.015	.02	.025	.005	.01	.015	.02	.025
	n_i	100	50	30	25	20	100	50	30	25	20
5	q_i	.01	.005	.003	.008	.025					
	n_i	150	80	240	265	50					
6	q_i	.005	.01	.015	.02	.025	.005	.01	.015	.02	.025
	n_i	150	20	20	50	25	150	20	20	50	25
7	q_i	.01	.02	.03	.04	.05					
	n_i	300	20	20	100	50					
8	q_i	.005	.01	.015	.02	.025	.005	.01	.015	.02	.025
	n_i	300	20	20	100	50	300	20	20	100	50

Table 12. SERIES-PARALLEL SYSTEM INPUT PARAMETERS

Case		Components									
		1	2	3	4	5	6	7	8	9	10
9	q_i	.02	.01	.005	.005	.005					
	n_i	30	25	20	10	5					
10	q_i	.02	.01	.005	.005	.005	.005	.005	.005	.005	.005
	n_i	100	30	15	10	10	10	10	10	10	10
11	q_i	.01	.02	.03	.04	.05					
	n_i	100	50	30	25	20					
12	q_i	.005	.01	.015	.02	.025	.005	.01	.015	.02	.025
	n_i	100	50	30	25	20	100	50	30	25	20
13	q_i	.01	.005	.003	.008	.025					
	n_i	200	400	720	265	80					
14	q_i	.005	.01	.015	.02	.025	.005	.01	.015	.02	.025
	n_i	300	20	20	100	50	300	20	20	100	50

Table 13. SERIES-PARALLEL WITH A 2 OUT OF 3 COMPONENT SYSTEM INPUT PARAMETERS

Case		Components									
		1	2	3	4	5	6	7	8	9	10
15	q_i	.02	.01	7E-5	2E-5	.005					
	n_i	30	25	20	10	5					
16	q_i	.02	.01	7E-5	2E-5	.005	.005	.005	.005	.005	.005
	n_i	100	30	15	10	10	10	10	10	10	10
17	q_i	.01	.005	2E-5	6E-5	.025					
	n_i	150	80	240	265	50					
18	q_i	.005	.01	7E-5	4E-5	.025	.005	.01	.015	.02	.025
	n_i	150	20	20	50	25	150	20	20	50	25
19	q_i	.01	.005	2E-5	6E-5	.025					
	n_i	200	400	720	265	80					
20	q_i	.005	.01	7E-5	4E-5	.025	.005	.01	.015	.02	.025
	n_i	300	20	20	100	50	300	20	20	100	50
21	q_i	1E-4	.002	7E-5	1E-4	.001	.001	.001	.001	.002	4E-4
	n_i	200	100	60	50	40	40	40	40	50	60
22	q_i	.001	.002	7E-5	.000	.005	.005	.005	.005	.006	.003
	n_i	200	100	60	50	40	40	40	40	50	60
23	q_i	.025	.02	2E-4	2E-4	.001	.001	.001	.001	.002	.005
	n_i	200	100	60	50	40	40	40	40	50	60
24	q_i	.025	.015	7E-5	4E-4	.005	.005	.005	.005	.006	.035
	n_i	200	100	60	50	40	40	40	40	50	60

Table 14. PARALLEL SYSTEM INPUT PARAMETERS

Case		Components									
		1	2	3	4	5	6	7	8	9	10
25	q_i	.01									
	n_i	100									
26	q_i	.04									
	n_i	30									
27	q_i	.06									
	n_i	100									
28	q_i	.06									
	n_i	150									

Table 15. WHEATSTONE BRIDGE INPUT PARAMETERS

Case		Components									
		1	2	3	4	5	6	7	8	9	10
29	q_i	.01	.02	.03	.04	.05					
	n_i	150	20	20	50	25					
30	q_i	.01	.005	.003	.008	.025					
	n_i	150	80	240	265	50					
31	q_i	.02	.01	.005	.005	.005					
	n_i	30	25	20	10	5					
32	q_i	.02	.01	.005	.005	.005					
	n_i	50	30	10	10	5					

APPENDIX C. FORTRAN CODE FOR THE PREFERRED LOWER CONFIDENCE LIMIT FOR SYSTEM RELIABILITY (SERIES SYSTEM AND WHEATSTONE BRIDGE SYSTEM)

```
      PROGRAM ZFYSCN
C*****************************************************************************
C*                                                                           *
C*      TITLE: BINOMIAL INTERVAL ESTIMATION PROCEDURE                        *
C*             ZERO FAILURES ALLOWED; NO SCALING                             *
C*     AUTHOR: E. F. BELLINI, LT, USN                                        *
C*     MODIFIED BY:  LT VALERIE A. COVINGTON,USN    (MAR 90)
C*       DATE: NOV 89                                                        *
C*                                                                           *
C*     THIS PROGRAM COMPUTES THE TRUE CONFIDENCE LEVEL FOR THE ESTIMATE      *
C*     RELIABILITY OF A SERIES AND BRIDGE SYSTEM GIVEN THE RELIABILITY       *
C*     OF THEIR COMPONENTS                                                   *
C*                                                                           *
C*     IN ITS PRESENT CONFIGURATION THIS PROGRAM IS SET UP TO RUN 12          *
C*     TIMES EACH TIME PRODUCING 1000 REPLICATIONS USING A DIFFERENT         *
C*     SET OF INPUT DATA.  RUN THE PROGRAM FROM CMS BY TYPING 'B1 EXEC'.     *
C*     THE REXX EXEC PROGRAM                                                 *
C*     'B1' CALLS THE INPUT FILES TO BE READ AND NAMES THE 12 OUTPUT         *
C*     FILES RESULTING FROM THE 12 CONSECUTIVE RUNS.  BY EDITING THE         *
C*     INDEX COUNTERS I, J, K OF THE 'B1' EXEC ONE CAN RUN ANY USER-         *
C*     SPECIFIC RUN FROM JUST ONE RUN TO ALL 12.                             *
C*                                                                           *
C*     VARIABLES USED                                                        *
C*                                                                           *
C*          AHATI  : WEIGHT ESTIMATES FOR EACH COMPONENT                     *
C*          AI     : INPUT WEIGHTS FOR EACH COMPONENT                        *
C*          ALFA   : LEVELS OF SIGNIFICANCE                                  *
C*          BIGF   : TOTAL NO. OF FAILURES FOR EACH REPLICATION              *
C*          CHISQ  : CHI-SQUARE RANDOM VARIABLE VALUE                        *
C*          C1C15  : FORMAT LABEL                                            *
C*          DEGFR  : DEGREES OF FREEDOM                                      *
C*          DELBRG : DIFFERENCE FOR BRIDGE SYSTEM                            *
C*          DELSTR : DIFFERENCE FOR SERIES SYSTEM- CLOSED FORM               *
C*          DELTAR : DIFFERENCE FOR SERIES SYSTEM                            *
C*          DIFF   : DIFFERENCE (TRUE REL. - ESTIMATED REL.)                 *
C*          EPS    : SMALL QUANTITY(CONSTANT)                                *
C*          ERROR  : PARAMETER FOR IMSL ROUTINE                              *
C*          FAILS  : COUNTS NO. OF REPLICATIONS WITH AT LST. 1 FAILURE       *
C*          FI     : NO. OF FAILURES FOR EACH COMPONENT(ALL MISSION TST)     *
C*          FLAG   : 1 IF ALL COMP. HAVE SAME NO. OF MISSION TESTS           *
C*          INC    : INCREMENT STEP SIZE FOR ROUTINE USMNMX                  *
C*          KEY1   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
C*          KEY2   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
C*          KEY3   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
C*          KEY4   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
C*          KK     : ARRAY SIZING PARAMETER FOR THE MAX NO OF COMPONENTS     *
C*          LOOP   : COUNTS NO. OF REPLICATION PERFORMED                     *
C*          MAXALF : MAX NO. OF SIGNIFICANT LEVELS DESIRED(ARRAY SIZING)     *
```

```
*          MAXREP : MAX NO. OF REPLICATIONS                                  *
*          MAXRUN : MAX NO. OF PROGRAM ITERATIONS ALLOWED                    *
*          MSTRQ  : MASTER UNRELIABILITY(USED WITH AI'S TO CALC. QI'S)       *
*          MULT   : MULTIPLIER FOR RANDOM NO. GENERATOR SRND                 *
*          N      : NO. OF MISSION TEST FOR EACH COMPONENT                   *
*          NIMAX  : MAX NO. OF MISSION TESTS                                 *
*          NIMIM  : MIN NO. OF MISSION TESTS                                 *
*          NINDX  : INDEX NO. OF MAX NO. OF MISSION TESTS                    *
*          NIREAL : NO. OF MISSION TESTS TRANSFORMED TO REAL                 *
*          NMAX   : MAX NO. OF MISSION TESTS FOR OUTPUT CONTROL              *
*          NPRNT  : FLAG FOR DETAILED REPORT OUTPUT                          *
*          PRNT   : SAME AS ABOVE(PARAMETER)                                 *
*          QHATI  : UNRELIABILITY ESTIMATES FOR EACH COMPONENT               *
*          QHTMAX : LARGEST QHATI                                            *
*          QHTUPR : UPPER LIMIT ON SYSTEM UNRELIABILITY                      *
*          QI     : INPUT UNRELIABILIY FOR EACH COMPONENT                    *
*          QINDX  : INDEX                                                    *
*          QUANTL : QUANTILE                                                 *
*          REPSHD : REPLICATIONS HEADING FORMAT NUMBER                       *
*          RHTSTR : SERIES SYSTEM RELIABILITY ESTIMATE(CLOSED FORM)          *
*          RS     : TRUE SERIES SYSTEM RELIABILITY                           *
*          RSBRDG : TRUE BRIDGE SYSTEM RELIABILITY                           *
*          RSHAT  : SERIES SYSTEM RELIABILITY ESTIMATE                       *
*          RSHTBR : BRIDGE SYSTEM RELIABILITY ESTIMATE                       *
*          SEED   : PARAMETER                                                *
*          SELCTA : SIGNIFICANCE LEVEL SELECTION                             *
*          SELCTB : SIGNIFICANCE LEVEL SELECTION                             *
*          SORT   : PARAMETER FOR ROUTINE SRND                               *
*          SUMNAI : SUM OF THE PRODUCT OF NI'S AND AI'S                      *
*          TEMP   : TEMPORARY ARRAY                                          *
*          TOTREP : TOTAL NUMBER OF PROGRAM ITERATIONS                       *
*          TRANBR : TEMPORARY ARRAY                                          *
*          TRANSQ : TEMPORARY ARRAY                                          *
*          TRANSR : TEMPORARY ARRAY                                          *
*          TRIALS : BERNOULLI TRIALS ARRAY (2-DIM)                           *
*          TRNSTR : TEMPORARY ARRAY                                          *
*          TRUQNT : TRUE QUANTILE                                            *
*          UNIRV  : UNIFORM RANDOM DEVIATES (2-DIM)                          *
*          ZFAILS : TOTAL NUMBER OF REPLICATIONS WITH ZERO FAILURES          *
*          ZFPREP : NO. OF COMPNTS. WITH ZERO FAILURES PER REPLICATION       *
*                                                                            *
******************************************************************************

      PARAMETER (KK=10,MAXALF=2,NPRNT=0)
      PARAMETER (MAXREP=1000, MAXRUN=2000, EPS=.000001)
      REAL*4 UNIRV(15,1000),TEMP(1000),QI(KK),AI(KK),AHATI(KK)
      REAL*4 QHATI(KK), NMAX, NNMAX, QHTMAX, CHISQR(5,5), ALFA(MAXALF)
      REAL*4 DF(5),AALFA(5),SUMNAI,RSHAT(MAXALF,MAXREP),RS
      REAL*4 KEY1(MAXREP),KEY2(MAXREP),KEY3(MAXREP),TRNSTR(MAXREP)
      REAL*4 DEGFR(MAXREP), QHTUPR(MAXALF,MAXREP),CHISQ(MAXALF,MAXREP)
      REAL*4 QUPA1(MAXREP), QUPA2(MAXREP),RHTSTR(MAXALF,MAXREP)
      REAL*4 DELTAR(MAXALF), TRANSQ(MAXREP),TRANSR(MAXREP),DIFF(MAXREP)
      REAL*4 DELSTR(MAXALF),NIMIN,NIMAX,NIREAL(KK)
      REAL*4 RSHTBR(MAXALF,MAXREP),DELBRG(MAXALF),KEY4(MAXREP)
      REAL*4 TRANBR(MAXREP), RSBRDG ,MSTRQ
      REAL*4 ZFPREP
```

```
      REAL*4 AVGN,SUC,STUD

      INTEGER SEED, MULT, SORT, TRIALS(15,1000), BIGF, FI(KK), N(KK)
      INTEGER NINDX, QINDX, ERROR, REPS, SELCTA, SELCTK, TOTREP
      INTEGER C1C15, REPSHD, SELCTB, ALF, FLAG, LOOP,PRNT
      INTEGER QUANTL(MAXALF), TRUQNT(MAXALF),ZFAILS,FAILS,INC
      INTEGER NTEST,FCT,BFLAG

      CHARACTER*8 LOOPS0(MAXREP)

      DATA SEED/123457/, MULT/1/, INC/1/
      DATA AALFA/.01,.05,.9,.95,.99/, DF/1,5,10,30,40/
      DATA ALFA/.20,.050/
      DATA SORT/0/

      ASSIGN 8 TO C1C15
      ASSIGN 9 TO REPSHD

*     CALL COMPRS
      PRNT = NPRNT

      DO 12 I=1,KK
           AI(I) = 9999.
           N(I) = 99999999
   12 CONTINUE

      READ(03,*)K,MSTRQ

      DO 11 I=1,K
      READ(03,*) AI(I),N(I)
   11 CONTINUE


      IF(K.NE.5) THEN
           WRITE(1,'(''WARNING: BRIDGE STRUCTURE '',
     +''ONLY USES THE FIRST 5 COMPONENTS'')')
      ELSE
      END IF

***INITIALIZE THE QHTUPR ARRAY OF UNRELIABILITY REPLICATIONS,    ***
*  RSHAT ARRAY OF ESTIMATE SYSTEM RELIABILITY REPLICATIONS        *
*  AND RHTSTR ARRAY OF EST. SYST. REL. FOR A SERIES SYST WHEN     *
***ALL THE COMPONENT MISSION TESTS ARE EQUAL IN NUMBER           ***

      DO 172 ALF=1,MAXALF
           DO 173 REPS=1,MAXREP
                QHTUPR(ALF,REPS) = 0.
                RSHAT(ALF,REPS) = 0.
                RHTSTR(ALF,REPS) = 0.
                RSHTBR(ALF,REPS) = 0.
                LOOPS0(REPS)=' ****** '
  173       CONTINUE
  172 CONTINUE

***SET FLAG TO 1 IF ALL COMPONENTS HAVE SAME NO. OF MISSION TESTS****
```

```
      FLAG=1
      DO 50 I=1,K -1
           IF((N(I) - N(I+1)).NE.0) THEN
                FLAG=0
           ELSE
           END IF
   50 CONTINUE
      PRINT *, 'FLAG IS:', FLAG

***MAIN PROGRAM OUTER LOOP START(EVERY LOOP IS ONE REPLICATION)***

      ZFPREP = 0.
      ZFAILS = 0
      FAILS = 0
      TOTREP = 0
      LOOP = 0
   10 IF(LOOP.LT.MAXREP) THEN
           LOOP = LOOP + 1
           IF(TOTREP.LT.MAXRUN) THEN
                TOTREP = TOTREP + 1
      SELCTA = 1
      SELCTB = 2

***FILL ARRAY KEY(REPS) WITH INTEGERS 1 TO K TO BE USED AS OUTPUT***
***OF THE SUBROUTINE SHSORT                                      ***

      DO 95 REPS=1, MAXREP
           KEY1(REPS) = REPS
           KEY2(REPS) = REPS
           KEY3(REPS) = REPS
           KEY4(REPS) = REPS
   95 CONTINUE

***CALCULATE NMAX NOT TO PRINT LONGER THAN THE MAX SAMPLE SIZE***

***CALCULATE THE MAXIMUM NO. OF TRIALS AND ITS INDEX NO.***

      CALL IMAX(N,K,NMAX,NINDX)


***CALCULATE THE QI'S FROM THE GIVEN MASTER Q AND THE AI'S***

      DO 115 I=1, K
           QI(I) = MSTRQ * AI(I)
  115 CONTINUE

      DO 120 I=1,15
           DO 125 J=1,500
                UNIRV(I,J) = 999.
                TRIALS(I,J) = 99999
  125      CONTINUE
  120 CONTINUE

*** DRAW UNIFORM (0,1) RV'S AND CONVERT TO BERNOULLI TRIALS***

      DO 130 I=1, K
```

```
            CALL SRND(SEED, TEMP, N(I), MULT, SORT)
            DO 135 J=1, N(I)
                 UNIRV(I,J) = TEMP(J)
                 IF (UNIRV(I,J).LE. 1 - QI(I)) THEN
                      TRIALS(I,J) = 0
                 ELSE
                      TRIALS(I,J) = 1
                 END IF
 135   CONTINUE
 130   CONTINUE


***CALCULATE THE NO. OF FAILURES FOR EACH COMPONENT***

       DO 150 I=1, K
            FI(I) = 0
 150   CONTINUE
       IONECT = 0

***CALCULATE THE F SUB I'S AND THE GRAND TOTAL NO. OF FAILURES***
       BIGF = 0
       DO 155 I=1, K
            DO 160 J=1, N(I)
                 FI(I) = FI(I) + TRIALS(I,J)
 160           CONTINUE
            IF(FI(I).EQ.0) THEN
                 ZFPREP = ZFPREP + 1
            ELSE
            END IF

***CALCULATE THE QHAT SUB I'S: F SUB I'S DIVIDED BY N SUB I'S***
                 QHATI(I) = REAL(FI(I)) / N(I)
            BIGF = BIGF + FI(I)
 155   CONTINUE

***COUNTS NUMBER OF COMPONENTS THAT HAVE FAILED***

       DO 156 I=1,K
          IF (FI(I) .NE. 0) IONECT=IONECT+1
 156   CONTINUE

       CALL CPARE(FI,K,BFLAG)


***CASE WHERE NO COMPONENTS HAVE ANY FAILURES***

            AVGN=0.0
            DO 200 I=1,K
                 AVGN=AVGN+REAL(N(I))
 200        CONTINUE
            AVGN=AVGN/REAL(K)
       IF(BIGF.EQ.0) THEN
            LOOPSO(LOOP)=' *ZERO* '
            ZFAILS = ZFAILS + 1
            DO 205 ALF=1, MAXALF
                 RSHAT(ALF,LOOP)= ALFA(ALF)**(1./AVGN)
```

```
                IF(FLAG.EQ.1) THEN
                    RHTSTR(ALF,LOOP)=ALFA(ALF)**(1./N(1))
                ELSE
                END IF
                IF (BFLAG .EQ. 0) THEN
                    RSHTBR(ALF,LOOP)=ALFA(ALF)**(1./AVGN)
                ENDIF
 205        CONTINUE
                DEGFR(LOOP) = 2.
                GO TO 10
      ELSE
           FAILS = FAILS + 1
      END IF

***COUNTS NUMBER OF COMPONENTS THAT FAIL RECORDS NO. COMPT TESTS***
      FCT=0
      DO 202 I=1,K
           IF (FI(I) .NE. 0) THEN
              FCT=FCT+1
              NTEST=N(I)
       ENDIF
 202  CONTINUE

***FIND THE MAX OF THE INDIVIDUAL COMPONENT UNRELIABILITIES***

      CALL RMAX(QHATI, K, QHTMAX, QINDX)

***CALCULATE THE AHAT SUB I'S (WEIGHT ESTIMATES)***
***IF COMPONENT HAS NO FAILURES AHAT SUB I IS ZERO***

      SUMNAI = 0.
      DO 165 I=1, K
           AHATI(I) = QHATI(I) / QHTMAX
           SUMNAI = SUMNAI + N(I) * AHATI(I)
 165  CONTINUE

***1 COMPONENT FAILURE SERIES SYSTEM***

      IF (FCT .EQ. 1) THEN
         LOOPS0(LOOP)=' *ONECF*  '
         DO 305 ALF=1,MAXALF
            SUC=REAL(NTEST-BIGF)
            STUD=FIN(1.-ALFA(ALF),2.*(REAL(BIGF)+1.),2.*SUC)
            RSHAT(ALF,LOOP)=SUC/(SUC+(REAL(BIGF)+1.)*STUD)
            IF (FLAG .EQ. 1) THEN
                 RHTSTR(ALF,LOOP)=RSHAT(ALF,LOOP)
            ELSE
            ENDIF
 305     CONTINUE
      ENDIF

***CALCULATE 1 REPLICATION OF UPPR ALFA C.L. ON SYSTEM RELIABILITY***

      DEGFR(LOOP) = 2 * (1 + BIGF)

      DO 170 ALF=1, MAXALF
```

```
            CALL MDCHI(1 - ALFA(ALF),DEGFR(LOOP),CHISQ(ALF,LOOP), ERROR)
            QHTUPR(ALF,LOOP) = CHISQ(ALF,LOOP) / (2 * SUMNAI)
            IF(FLAG.EQ.1) THEN
                 RHTSTR(ALF,LOOP) = 1 -(CHISQ(ALF,LOOP) / REAL(2*N(1)))
            ELSE
            END IF

***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR COMPNTS. IN SERIES***

            IF (FCT .NE. 1) THEN
            CALL RHTSRS(QHTUPR(ALF,LOOP), AHATI,K, RSHAT(ALF,LOOP))
            ENDIF

***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR BRIDGE STRUCTURE***

***IF NO SYSTEM FAILURE AND BRIDGE SYSTEM***

                 IF (BFLAG .EQ. 0) THEN
                     RSHTBR(ALF,LOOP)=ALFA(ALF)**(1./AVGN)
                 ENDIF
***IF MORE THAN 1 SYSTEM FAILURE AND BRIDGE SYSTEM***

            IF (BFLAG .EQ. 2) THEN
               CALL RHTBRG(QHTUPR(ALF,LOOP),AHATI,K,RSHTBR(ALF,LOOP))
            ENDIF

***EXACTLY 1 SYSTEM FAILURE AND BRIDGE SYSTEM***

      IF (BFLAG .EQ. 1) THEN
            SUC=REAL(AVGN-1)
            STUD=FIN(1.-ALFA(ALF),2.*2.,2.*SUC)
            RSHTBR(ALF,LOOP)=SUC/(SUC+2.*STUD)
      ENDIF
 170  CONTINUE

***THIS ELSE AND ENDIF ARE FOR THE TEST AGAINST MAXRUN***

      ELSE
           WRITE(1,'('' '',/''PROGRAM EXCEEDED THE MAX NO. OF RUNS'',
     +'' ALLOWED OF:'',I6)') TOTREP
      GOTO 9999

      END IF
      GOTO 10
      END IF

C     WRITE(2,'(''UNSORTED RSHAT 1  IS:'',/10(F8.5))')
C    +(RSHAT(1,LOOP), LOOP=1, MAXREP)
C     WRITE(2,'(''UNSORTED RSHAT 2  IS:'',/10(F8.5))')
C    +(RSHAT(2,LOOP), LOOP=1, MAXREP)
C     IF(FLAG.EQ.1) THEN
C          WRITE(2,'(''UNSORTED RHTSTR 1  IS:'',/10(F8.5))')
C    +(RHTSTR(1,LOOP), LOOP=1, MAXREP)
C          WRITE(2,'(''UNSORTED RHTSTR 2  IS:'',/10(F8.5))')
C    +(RHTSTR(2,LOOP), LOOP=1, MAXREP)
C     ELSE
```

```
C     END IF
C     IF(K.EQ.5) THEN
C          WRITE(2,'(''UNSORTED RSHTBR 1  IS:'',/10(F8.5))')
C    +(RSHTBR(1,LOOP), LOOP=1, MAXREP)
C          WRITE(2,'(''UNSORTED RSHTBR 2  IS:'',/10(F8.5))')
C    +(RSHTBR(2,LOOP), LOOP=1, MAXREP)
C     ELSE
C     END IF
C     WRITE (2,'(''ZERO AND ONE FAILURE REPS:'',/10(A8))')
C    +  (LOOPS0(LOOP),LOOP=1,MAXREP)

***SORT THE ARRAYS OF SYSTEM UNRELIABILITIES(1 FOR EACH CONF. LEVEL)***

      DO 700 ALF=1, MAXALF
           DO 800 REPS=1, MAXREP
                TRANSQ(REPS) = QHTUPR(ALF,REPS)
                TRANSR(REPS) = RSHAT(ALF,REPS)
                TRNSTR(REPS) = RHTSTR(ALF,REPS)
                TRANBR(REPS) = RSHTBR(ALF,REPS)
 800        CONTINUE
           CALL SHSORT(TRANSQ,KEY1,MAXREP)
           CALL SHSORT(TRANSR,KEY2,MAXREP)
           CALL SHSORT(TRNSTR,KEY3,MAXREP)
           CALL SHSORT(TRANBR,KEY4,MAXREP)
           DO 900 REPS=1, MAXREP
                QHTUPR(ALF,REPS) = TRANSQ(REPS)
                RSHAT(ALF,REPS) = TRANSR(REPS)
                RHTSTR(ALF,REPS) = TRNSTR(REPS)
                RSHTBR(ALF,REPS) = TRANBR(REPS)
 900        CONTINUE
 700  CONTINUE

***PRINT OUTPUT REPORT HEADINGS***

      WRITE(1,6666)
      WRITE(1,6667) MAXREP
      WRITE(1,6668) K
      WRITE(1,6669)
      IF(K.EQ.5) THEN
           WRITE(1,6699)
      ELSE
      END IF
      WRITE(1,6670) MSTRQ
      WRITE(1,6671)
      WRITE(1,C1C15)
      WRITE(1,3334) AI
      WRITE(1,0007)
      WRITE(1,C1C15)
      WRITE(1,3334) QI
      WRITE(1,0005)
      WRITE(1,C1C15)
      WRITE(1,3335) N
      WRITE(1,6674)

***COMPUTE THE VALUE RS OF THE TRUE SYSTEM REL. FNCTN.(SERIES SYSTEM)***
***  AND FOR THE 5-COMPONENT BRIDGE STRUCTURE***
```

```
      CALL RSRS(QI,K,RS)
      WRITE(1,'('' '',////''THE TRUE SERIES SYSTEM '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RS
      CALL RBRIDG(QI,K,RSBRDG)
      IF(K.EQ.5) THEN
      WRITE(1,'('' '',////''THE TRUE BRIDGE STRUCTURE '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RSBRDG
      ELSE
      END IF
      WRITE(1,6675)

***COMPUTE THE DIFFERENCE 'DELTAR' BTWN. RS AND RSHAT OF THE THEO***
***RETICAL QUANTILE GIVEN BY ALFA(MUST USE SORTED RSHAT ARRAY)***

      IF(FLAG.EQ.1) THEN
      WRITE(1,5755)
      ELSE
      END IF
      DO 450 ALF=1, MAXALF
           QUANTL(ALF) = MAXREP * (1 - ALFA(ALF))
           DELTAR(ALF) = RS - RSHAT(ALF,QUANTL(ALF))
           DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
           IF(FLAG.EQ.1) THEN
                DELSTR(ALF) = RS - RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5656) RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5657) DELSTR(ALF)
           ELSE
           END IF
           IF(K.EQ.5) THEN
                DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5666) RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5667) DELBRG(ALF)
           ELSE
           END IF
           WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
           WRITE(1,5556) RSHAT(ALF,QUANTL(ALF))
           WRITE(1,5557) DELTAR(ALF)
 450  CONTINUE
      PRINT *, 'QUANTL(1) IS:', QUANTL(1)
      PRINT *, 'QUANTL(2) IS:', QUANTL(2)

***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***              ********* RSHAT ********                    ***

      WRITE(1,6676)
      DO 400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 500 REPS=1, MAXREP
                DIFF(REPS) = RS - RSHAT(ALF,REPS)
 500       CONTINUE
           DO 600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
```

```
                    WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +              F8.4)')
     +              (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                    GO TO 620
               ELSEIF(DIFF(REPS).LT.0.) THEN
                    TRUQNT(ALF) = REPS
                    GO TO 610
               ELSE
               END IF
 600       CONTINUE
 610       IF(TRUQNT(ALF).EQ.0.) THEN
               WRITE(1,4443) ALFA(ALF)
               WRITE(1,'('' '',/''THE SMALLEST'',
     +         '' DIFFERENCE BETWEEN RS AND RSHAT IS:'',F10.5)') DIFF(
     +         MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
               WRITE(1,4442) ALFA(ALF)
               WRITE(1,'('' '',/''ALL RSHAT'',
     +          '' ARE GREATER THAN RS'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
               WRITE(1,4444) ALFA(ALF),
     +         (TRUQNT(ALF) / REAL(MAXREP)) * 100.
               WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF))
               WRITE(1,4446)
           ELSE
               WRITE(1,4444) ALFA(ALF),
     +         ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
               WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF)-1)
               WRITE(1,4447)
 620       END IF
 400   CONTINUE


***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***         ********* RSHTBR (BRIDGE) ********                  ***

      IF(K.EQ.5) THEN
      DO 401 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 501 REPS=1, MAXREP
                DIFF(REPS) = RSBRDG - RSHTBR(ALF,REPS)
 501       CONTINUE
           DO 601 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                    TRUQNT(ALF) = REPS
                    WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +              F8.4)')
     +              (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                    GO TO 621
               ELSEIF(DIFF(REPS).LT.0.) THEN
                    TRUQNT(ALF) = REPS
                    GO TO 611
               ELSE
               END IF
 601       CONTINUE
```

```
611         IF(TRUQNT(ALF).EQ.0.) THEN
                 WRITE(1,4443) ALFA(ALF)
                 WRITE(1,'('' '',/''THE SMALLEST'',
     +           '' DIFFERENCE BETWEEN RSBRDG AND RSHTBR IS:'',
     +           F10.5)') DIFF(MAXREP)
            ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                 WRITE(1,4442) ALFA(ALF)
                 WRITE(1,'('' '',/''ALL RSHTBR'',
     +            '' ARE GREATER THAN RSBRDG'')')
            ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +      THEN
                 WRITE(1,4444) ALFA(ALF),
     +           (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                 WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF))
                 WRITE(1,4446)
            ELSE
                 WRITE(1,4444) ALFA(ALF),
     +           ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                 WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF)-1)
                 WRITE(1,4447)
621         END IF
401   CONTINUE
      ELSE
      END IF


***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***                 ********* RHTSTR *********                 ***

      IF(FLAG.EQ.1) THEN
      DO 4400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 5500 REPS=1, MAXREP
                DIFF(REPS) = RS - RHTSTR(ALF,REPS)
5500       CONTINUE
           DO 6600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                     GO TO 6620
                ELSEIF(DIFF(REPS).LT.0.) THEN
                     TRUQNT(ALF) = REPS
                     GO TO 6610
                ELSE
                END IF
6600       CONTINUE
6610       IF(TRUQNT(ALF).EQ.0.) THEN
                 WRITE(1,4443) ALFA(ALF)
                 WRITE(1,'('' '',/''THE SMALLEST'',
     +           '' DIFFERENCE BETWEEN RS AND RHTSTR IS:'',
     +           F9.5)') DIFF(MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                 WRITE(1,4442) ALFA(ALF)
                 WRITE(1,'('' '',/''ALL RHTSTR'',
```

```
     +          '' ARE GREATER THAN RS'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 6620      END IF
 4400 CONTINUE
      ELSE
      END IF

***PRINT THE ARRAYS PERTINENT TO THE OUPUT OF EACH REPLICATION***

      IF(PRNT.EQ.1) THEN
      I = 1
 185  WRITE(1,REPSHD) ALFA(SELCTA), ALFA(SELCTA),
     +ALFA(SELCTB),ALFA(SELCTB),ALFA(SELCTA),ALFA(SELCTA),ALFA(SELCTB),
     +ALFA(SELCTB)
 175  IF(I.GE.(MAXREP + 1)) THEN
           GOTO 180
      ELSE
           IF( (I.EQ.71).OR.(I.EQ.211).OR.(I.EQ.351).OR.(I.EQ.491).OR.
     +     (I.EQ.631).OR.(I.EQ.771).OR.(I.EQ.911).OR.(I.EQ.1051) ) THEN
                I = I + 70
                WRITE(1,'(''+'')')
                GOTO 185
           ELSE

           WRITE(1,3336) I, INT(DEGFR(I)), CHISQ(1,I), QHTUPR(1,I),
     +     CHISQ(2,I), QHTUPR(2,I)
           END IF
           IF(I + 70.LE.MAXREP) THEN
                WRITE(1,3337) I+70,INT(DEGFR(I+70)),CHISQ(1,I+70),
     +          QHTUPR(1,I+70),CHISQ(2,I+70),QHTUPR(2,I+70)
           ELSE
           END IF
      I = I + 1
      GOTO 175
 180  END IF
      ELSE
      ENDIF
 9999 WRITE(1,'(''THE TOTAL NO OF REPS WAS:'',I8)') TOTREP
      WRITE(1,'(''THE TOTAL NO OF EFFECTIVE REPS WAS:'',I8)') LOOP
      WRITE(1,'(''THE TOTAL NO OF NO FAILURE RUNS WAS:'',I8)') ZFAILS
      WRITE(1,'(''AVERAGE  NO. OF COMPONENTS PER REPLICATION WITH '',
     +''NO FAILURES:'',F5.2)') ZFPREP / MAXREP
      WRITE(1,'(''THE TOTAL NO OF RUNS WITH FAILURES WAS:'',I8)') FAILS
 0008 FORMAT (/ 3X,'C 1',5X,'C 2',
     +5X,'C 3',5X,'C 4',5X,'C 5',5X,'C 6',5X,'C 7',5X,
     +'C 8',5X,'C 9',5X,'C 10',4X,'C 11',4X,
```

```
     +'C 12',4X,'C 13',4X,'C 14',4X,'C 15')
0009 FORMAT(/1X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
     +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')',
     +2X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
     +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')'/)
0001 FORMAT (///'UNIFORM RANDOM DEVIATES ARE:')
0002 FORMAT (///'BERNOULLI TRIALS ARE:')
0003 FORMAT (///'TOTAL NO. OF FAILURES FOR EACH COMPONENT:')
0004 FORMAT (///'ESTIMATED UNRELIABILITY FOR EACH COMPONENT:')
0005 FORMAT (///'TOTAL NUMBER OF MISSION TESTS:')
0006 FORMAT (///'ESTIMATED WEIGHTS FOR EACH COMPONENT:')
0007 FORMAT (///'Q I FOR EACH COMPONENT:')
1111 FORMAT (15F8.5)

2222 FORMAT (/1X,15(I4,4X))
3333 FORMAT (/1X,15(I4,4X))
3334 FORMAT (/15F8.5)
3335 FORMAT (/1X,15(I4,4X))
3336 FORMAT (T3,I4,T9,I3,T13,F11.5,T27,F8.5,T39,F11.5,T53,F8.5)
3337 FORMAT ('+',T67,I4,T73,I3,T77,F11.5,T91,F8.5,T103,F11.5,T117,F8.5)
4442 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
     +'LIMIT IS:',T50,' 00.000 ')
4443 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
     +'LIMIT IS:',T50,'100.0000')
4444 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
     +'LIMIT IS:',T50,F8.4)
4445 FORMAT (' ',/'THE RSHAT VALUE CLOSEST TO RS IS: ',T51,F8.5)
4446 FORMAT (' ',/'(FIRST NEGATIVE DIFFERENCE)')
4447 FORMAT (' ',/'(ELEMENT PRECEEDING FIRST NEGATIVE DIFFERENCE)')
4448 FORMAT (' ',/'THE RHTSTR VALUE CLOSEST TO RS IS: ',T51,F8.5)
4449 FORMAT (' ',/'THE RSHTBR VALUE CLOSEST TO RSBRDG IS: ',T51,F8.5)
5555 FORMAT (' ',///'THE ',I4,'(1-',F4.3,') QUANTILE IS:',T49,F8.3)
5556 FORMAT (' ',/'THE VALUE OF RSHAT FOR THAT QUANTILE IS:',T51,F8.5)
5557 FORMAT (' ',/'THE DIFFERENCE(RS - RSHAT) IS:',T51,F8.5)
5656 FORMAT (' ',/'THE VALUE OF RHTSTR FOR THAT QUANTILE IS:',T51,F8.5)
5666 FORMAT (' ',/'THE VALUE OF RSHTBR FOR THAT QUANTILE IS:',T51,F8.5)
5657 FORMAT (' ',/'THE DIFFERENCE(RS - RHTSTR) IS:',T51,F8.5)
5667 FORMAT (' ',/'THE DIFFERENCE(RS - RSHTBR) IS:',T51,F8.5)
5755 FORMAT (' ',///'SINCE THE NO. OF MISSION TESTS IS THE SAME FOR',
     +' ALL COMPONENTS THE CLOSED FORM SERIES SYSTEM RELIABILITY ',
     +'''RHTSTR'' IS COMPUTED')
6666 FORMAT ('+','*************************************************',
     +'********** RUN INPUT SETTINGS **********************************',
     +'**********')
6667 FORMAT (' ',//'NUMBER OF REPLICATIONS:',T50,I4)
6668 FORMAT (' ',//'NUMBER OF COMPONENTS:',T50,I4)
6669 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'SERIES')
6699 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'BRIDGE')
6670 FORMAT (' ',//'MASTER UNRELIABILITY USED:',T50,F8.5)
6671 FORMAT (' ',//'INPUT WEIGHTS(A SUB I''S):')
6674 FORMAT ('+',///'*************************************************',
     +'**R U N  R E S U L T S**********************************************',
     +'**********')
6675 FORMAT ('+',///'*************************************************',
     +' ESTIMATE ERRORS ***********************************************',
     +'**********')
```

```
 6676 FORMAT ('+',//'**********************************************************'
     +' TRUE CONFIDENCE LIMITS **********************************************',
     +'**********')
      END
```

APPENDIX D. FORTRAN CODE FOR THE PREFERRED LOWER CONFIDENCE LIMIT FOR SYSTEM RELIABILITY (SERIES PARALLEL SYSTEM)

```
      PROGRAM ZFYSCN
*************************************************************************
*                                                                       *
*      TITLE: BINOMIAL INTERVAL ESTIMATION PROCEDURE                    *
*             ZERO FAILURES ALLOWED; NO SCALING                         *
*     AUTHOR: E. F. BELLINI, LT, USN                                    *
*     MODIFIED BY:  LT VALERIE A. COVINGTON,USN   (MAR 90)
*       DATE: NOV 89                                                    *
*                                                                       *
*     THIS PROGRAM COMPUTES THE TRUE CONFIDENCE LEVEL FOR THE ESTIMATE  *
*     RELIABILITY OF A SERIES AND BRIDGE SYSTEM GIVEN THE RELIABILITY   *
*     OF THEIR COMPONENTS                                               *
*                                                                       *
*     IN ITS PRESENT CONFIGURATION THIS PROGRAM IS SET UP TO RUN 12      *
*     TIMES EACH TIME PRODUCING 1000 REPLICATIONS USING A DIFFERENT     *
*     SET OF INPUT DATA.  RUN THE PROGRAM FROM CMS BY TYPING 'B1 EXEC'. *
*     THE REXX EXEC PROGRAM                                             *
*     'B1' CALLS THE INPUT FILES TO BE READ AND NAMES THE 12 OUTPUT     *
*     FILES RESULTING FROM THE 12 CONSECUTIVE RUNS.  BY EDITING THE     *
*     INDEX COUNTERS I, J, K OF THE 'B1' EXEC ONE CAN RUN ANY USER-     *
*     SPECIFIC RUN FROM JUST ONE RUN TO ALL 12.                         *
*                                                                       *
*     VARIABLES USED                                                    *
*                                                                       *
*          AHATI  : WEIGHT ESTIMATES FOR EACH COMPONENT                 *
*          AI     : INPUT WEIGHTS FOR EACH COMPONENT                    *
*          ALFA   : LEVELS OF SIGNIFICANCE                              *
*          BIGF   : TOTAL NO. OF FAILURES FOR EACH REPLICATION          *
*          CHISQ  : CHI-SQUARE RANDOM VARIABLE VALUE                    *
*          C1C15  : FORMAT LABEL                                        *
*          DEGFR  : DEGREES OF FREEDOM                                  *
*          DELBRG : DIFFERENCE FOR BRIDGE SYSTEM                        *
*          DELSTR : DIFFERENCE FOR SERIES SYSTEM- CLOSED FORM           *
*          DELTAR : DIFFERENCE FOR SERIES SYSTEM                        *
*          DIFF   : DIFFERENCE (TRUE REL. - ESTIMATED REL.)             *
*          EPS    : SMALL QUANTITY(CONSTANT)                            *
*          ERROR  : PARAMETER FOR IMSL ROUTINE                          *
*          FAILS  : COUNTS NO. OF REPLICATIONS WITH AT LST. 1 FAILURE   *
*          FI     : NO. OF FAILURES FOR EACH COMPONENT(ALL MISSION TST)*
*          FLAG   : 1 IF ALL COMP. HAVE SAME NO. OF MISSION TESTS       *
*          INC    : INCREMENT STEP SIZE FOR ROUTINE USMNMX              *
*          KEY1   : ARRAY OF INDECES FOR ROUTINE SHSORT                 *
*          KEY2   : ARRAY OF INDECES FOR ROUTINE SHSORT                 *
*          KEY3   : ARRAY OF INDECES FOR ROUTINE SHSORT                 *
*          KEY4   : ARRAY OF INDECES FOR ROUTINE SHSORT                 *
*          KK     : ARRAY SIZING PARAMETER FOR THE MAX NO OF COMPONENTS*
*          LOOP   : COUNTS NO. OF REPLICATION PERFORMED                 *
*          MAXALF : MAX NO. OF SIGNIFICANT LEVELS DESIRED(ARRAY SIZING)*
```

```
*          MAXREP : MAX NO. OF REPLICATIONS                                  *
*          MAXRUN : MAX NO. OF PROGRAM ITERATIONS ALLOWED                    *
*          MSTRQ  : MASTER UNRELIABILITY USED WITH AI'S TO CALC. QI'S)       *
*          MULT   : MULTIPLIER FOR RANDOM NO. GENERATOR SRND                 *
*          N      : NO. OF MISSION TEST FOR EACH COMPONENT                   *
*          NIMAX  : MAX NO. OF MISSION TESTS                                 *
*          NIMIM  : MIN NO. OF MISSION TESTS                                 *
*          NINDX  : INDEX NO. OF MAX NO. OF MISSION TESTS                    *
*          NIREAL : NO. OF MISSION TESTS TRANSFORMED TO REAL                 *
*          NMAX   : MAX NO. OF MISSION TESTS FOR OUTPUT CONTROL              *
*          NPRNT  : FLAG FOR DETAILED REPORT OUTPUT                          *
*          PRNT   : SAME AS ABOVE(PARAMETER)                                 *
*          QHATI  : UNRELIABILITY ESTIMATES FOR EACH COMPONENT               *
*          QHTMAX : LARGEST QHATI                                            *
*          QHTUPR : UPPER LIMIT ON SYSTEM UNRELIABILITY                      *
*          QI     : INPUT UNRELIABILIY FOR EACH COMPONENT                    *
*          QINDX  : INDEX                                                    *
*          QUANTL : QUANTILE                                                 *
*          REPSHD : REPLICATIONS HEADING FORMAT NUMBER                       *
*          RHTSTR : SERIES SYSTEM RELIABILITY ESTIMATE(CLOSED FORM)          *
*          RS     : TRUE SERIES SYSTEM RELIABILITY                           *
*          RSBRDG : TRUE BRIDGE SYSTEM RELIABILITY                           *
*          RSHAT  : SERIES SYSTEM RELIABILITY ESTIMATE                       *
*          RSHTBR : BRIDGE SYSTEM RELIABILITY ESTIMATE                       *
*          SEED   : PARAMETER                                                *
*          SELCTA : SIGNIFICANCE LEVEL SELECTION                             *
*          SELCTB : SIGNIFICANCE LEVEL SELECTION                             *
*          SORT   : PARAMETER FOR ROUTINE SRND                               *
*          SUMNAI : SUM OF THE PRODUCT OF NI'S AND AI'S                      *
*          TEMP   : TEMPORARY ARRAY                                          *
*          TOTREP : TOTAL NUMBER OF PROGRAM ITERATIONS                       *
*          TRANBR : TEMPORARY ARRAY                                          *
*          TRANSQ : TEMPORARY ARRAY                                          *
*          TRANSR : TEMPORARY ARRAY                                          *
*          TRIALS : BERNOULLI TRIALS ARRAY (2-DIM)                           *
*          TRNSTR : TEMPORARY ARRAY                                          *
*          TRUQNT : TRUE QUANTILE                                            *
*          UNIRV  : UNIFORM RANDOM DEVIATES (2-DIM)                          *
*          ZFAILS : TOTAL NUMBER OF REPLICATIONS WITH ZERO FAILURES          *
*          ZFPREP : NO. OF COMPNTS. WITH ZERO FAILURES PER REPLICATION       *
*                                                                            *
******************************************************************************

      PARAMETER (KK=10,MAXALF=2,NPRNT=0)
      PARAMETER (MAXREP=1000, MAXRUN=2000, EPS=.000001)
      REAL*4 UNIRV(15,1000),TEMP(1000),QI(KK),AI(KK),AHATI(KK)
      REAL*4 QHATI(KK), NMAX, NNMAX, QHTMAX, CHISQR(5,5), ALFA(MAXALF)
      REAL*4 DF(5),AALFA(5),SUMNAI,RSHAT(MAXALF,MAXREP),RS
      REAL*4 KEY1(MAXREP),KEY2(MAXREP),KEY3(MAXREP),TRNSTR(MAXREP)
      REAL*4 DEGFR(MAXREP), QHTUPR(MAXALF,MAXREP),CHISQ(MAXALF,MAXREP)
      REAL*4 QUPA1(MAXREP), QUPA2(MAXREP),RHTSTR(MAXALF,MAXREP)
      REAL*4 DELTAR(MAXALF), TRANSQ(MAXREP),TRANSR(MAXREP),DIFF(MAXREP)
      REAL*4 DELSTR(MAXALF),NIMIN,NIMAX,NIREAL(KK)
      REAL*4 RSHTBR(MAXALF,MAXREP),DELBRG(MAXALF),KEY4(MAXREP)
      REAL*4 TRANBR(MAXREP), RSBRDG ,MSTRQ
      REAL*4 ZFPREP
```

```
      REAL*4 AVGN,SUC,STUD,PTEMP(10),FDEG1,FDEG2,P3,S3,S4

      INTEGER SEED, MULT, SORT, TRIALS(15,1000), BIGF, FI(KK), N(KK)
      INTEGER NINDX, QINDX, ERROR, REPS, SELCTA, SELCTK, TOTREP
      INTEGER C1C15, REPSHD, SELCTB, ALF, FLAG, LOOP,PRNT
      INTEGER QUANTL(MAXALF), TRUQNT(MAXALF),ZFAILS,FAILS,INC
      INTEGER NTEST,FCT,HFI

      CHARACTER*8 LOOPSO(MAXREP)

      DATA SEED/123457/, MULT/1/, INC/1/
      DATA AALFA/.01,.05,.9,.95,.99/, DF/1,5,10,30,40/
      DATA ALFA/.20,.050/
      DATA SORT/0/

      ASSIGN 8 TO C1C15
      ASSIGN 9 TO REPSHD

*     CALL COMPRS
      PRNT = NPRNT

      DO 12 I=1,KK
           AI(I) = 9999.
           N(I) = 99999999
   12 CONTINUE

      READ(03,*)K,MSTRQ

      DO 11 I=1,K
      READ(03,*) AI(I),N(I)
   11 CONTINUE


      IF(K.NE.5) THEN
           WRITE(1,'(''WARNING: BRIDGE STRUCTURE '',
     +''ONLY USES THE FIRST 5 COMPONENTS'')')
       ELSE
       END IF

***INITIALIZE THE QHTUPR ARRAY OF UNRELIABILITY REPLICATIONS,   ***
*  RSHAT ARRAY OF ESTIMATE SYSTEM RELIABILITY REPLICATIONS       *
*  AND RHTSTR ARRAY OF EST. SYST. REL. FOR A SERIES SYST WHEN    *
***ALL THE COMPONENT MISSION TESTS ARE EQUAL IN NUMBER          ***

      DO 172 ALF=1,MAXALF
           DO 173 REPS=1,MAXREP
                QHTUPR(ALF,REPS) = 0.
                RSHAT(ALF,REPS) = 0.
                RHTSTR(ALF,REPS) = 0.
                RSHTBR(ALF,REPS) = 0.
                LOOPSO(REPS)=' ******* '
  173       CONTINUE
  172  CONTINUE

***SET FLAG TO 1 IF ALL COMPONENTS HAVE SAME NO. OF MISSION TESTS****
```

```
      FLAG=1
      DO 50 I=1,K -1
           IF((N(I) - N(I+1)).NE.0) THEN
                FLAG=0
           ELSE
           END IF
   50 CONTINUE
      PRINT *, 'FLAG IS:', FLAG

***MAIN PROGRAM OUTER LOOP START(EVERY LOOP IS ONE REPLICATION)***

      ZFPREP = 0.
      ZFAILS = 0
      FAILS = 0
      TOTRLP = 0
      LOOP = 0
   10 IF(LOOP.LT.MAXREP) THEN
           LOOP = LOOP + 1
           IF(TOTREP.LT.MAXRUN) THEN
                TOTREP = TOTREP + 1
      SELCTA = 1
      SELCTB = 2

***FILL ARRAY KEY(REPS) WITH INTEGERS 1 TO K TO BE USED AS OUTPUT****
***OF THE SUBROUTINE SHSORT                                        ****

      DO 95 REPS=1, MAXREP
           KEY1(REPS) = REPS
           KEY2(REPS) = REPS
           KEY3(REPS) = REPS
           KEY4(REPS) = REPS
   95 CONTINUE

***CALCULATE NMAX NOT TO PRINT LONGER THAN THE MAX SAMPLE SIZE***

***CALCULATE THE MAXIMUM NO. OF TRIALS AND ITS INDEX NO.***

      CALL IMAX(N,K,NMAX,NINDX)


***CALCULATE THE QI'S FROM THE GIVEN MASTER Q AND THE AI'S***

      DO 115 I=1, K
           QI(I) = MSTRQ * AI(I)
  115 CONTINUE
C          S3=QI(3)
           S4=QI(1)**.50
      DO 120 I=1,15
           DO 125 J=1,500
                UNIRV(I,J) = 999.
                TRIALS(I,J) = 99999
  125      CONTINUE
  120 CONTINUE

*** DRAW UNIFORM (0,1) RV'S AND CONVERT TO BERNOULLI TRIALS***
      DO 130 I=1, K
```

```
            CALL SRND(SEED, TEMP, N(I), MULT, SORT)
            DO 135 J=1, N(I)
                 UNIRV(I,J) = TEMP(J)
                 IF (UNIRV(I,J).LE. 1 - QI(I)) THEN
                      TRIALS(I,J) = 0
                 ELSE
                      TRIALS(I,J) = 1
                 END IF
 135   CONTINUE
 130   CONTINUE


***CALCULATE THE NO. OF FAILURES FOR EACH COMPONENT****

       DO 150 I=1, K
            FI(I) = 0
 150   CONTINUE
       IONECT = 0

***CALCULATE THE F SUB I'S AND THE GRAND TOTAL NO. OF FAILURES****
       BIGF = 0
       DO 155 I=1, K
            DO 160 J=1, N(I)
                 FI(I) = FI(I) + TRIALS(I,J)
 160        CONTINUE
       IF (FI(I) .EQ. 0) THEN
          ZFPREP=ZFPREP+1
       ELSE
       ENDIF
       BIGF = BIGF + FI(I)

       QHATI(I) = REAL(FI(I)) / N(I)
 155   CONTINUE

***CHANGES FOR SERIES PARALLEL SYSTEM (COMPONENT 2)****

       IF (FI(2) .EQ. 0) THEN
          ZFPREP=ZFPREP - 1
       ENDIF
       BIGF = BIGF - FI(2)
       FI(1) = 0
       DO 161 I=1,N(2)
         HFI=0
         DO 162 J=1,2
            CALL SRND(SEED, PTEMP(J), N(2), MULT, SORT)
            IF (PTEMP(J) .GT. 1-S4) THEN
                HFI = HFI + 1
            ENDIF
 162     CONTINUE
         IF (HFI .EQ. 2) THEN
            FI(2) = FI(2) + 1
         ENDIF
 161   CONTINUE
       BIGF = BIGF + FI(2)
       IF (FI(2) .EQ. 0) THEN
           ZFPREP = ZFPREP + 1
```

```
      ELSE
      ENDIF
C     IF (FI(3) .EQ. 0) THEN
C        ZFPREP=ZFPREP - 1
C     ENDIF
C     BIGF = BIGF - FI(3)
C     FI(3) = 0
C     DO 163 I=1,N(3)
C       HFI=0
C       DO 164 J=1,3
C          CALL SRND(SEED, PTEMP(J), N(3), MULT, SORT)
C          IF (PTEMP(J) .GT. 1-S3) THEN
C              HFI = HFI + 1
C          ENDIF
C164     CONTINUE
C        IF (HFI .GE. 2) THEN
C          FI(3) = FI(3) + 1
C        ENDIF
C163   CONTINUE
C     BIGF = BIGF + FI(3)
C     IF (FI(3) .EQ. 0) THEN
C         ZFPREP = ZFPREP + 1
C     ELSE
C     ENDIF
      DO 19 I=1,K
       QI(I) = MSTRQ * AI(I)
      QHATI(I) = REAL(FI(I)) / N(I)

   19 CONTINUE
C     QI(4) = QI(4)**2
C     P3 = 1.-QI(3)
C     QI(3) = 1.-((3.*P3**2*QI(3))+(P3**3))
***COUNTS NUMBER OF COMPONENTS THAT HAVE FAILED***

      DO 156 I=1,K
         IF (FI(I) .NE. 0) IONECT=IONECT+1
  156 CONTINUE

***CASE WHERE NO COMPONENTS HAVE ANY FAILURES***

      IF(BIGF.EQ.0) THEN
           LOOPS0(LOOP)=' *ZERO* '
           ZFAILS = ZFAILS + 1
           AVGN=0.0
           DO 200 I=1,K
                AVGN=AVGN+REAL(N(I))
  200      CONTINUE
           AVGN=AVGN/REAL(K)
           DO 205 ALF=1, MAXALF
                RSHAT(ALF,LOOP)= ALFA(ALF)**(1./AVGN)
           IF(FLAG.EQ.1) THEN
                RHTSTR(ALF,LOOP)=ALFA(ALF)**(1./N(1))
           ELSE
           END IF
*          PRINT *,LOOP',LOOP,'RSHAT',RSHAT(ALF,LOOP)
  205      CONTINUE
```

```
                DEGFR(LOOP) = 2.
                GO TO 10
        ELSE
             FAILS = FAILS + 1
        END IF

***COUNTS NUMBER OF COMPONENTS THAT FAIL RECORDS NO. COMPT TESTS***
        FCT=0
        DO 202 I=1,K
             IF (FI(I) .NE. 0) THEN
                FCT=FCT+1
                NTEST=N(I)
         ENDIF
 202    CONTINUE

***FIND THE MAX OF THE INDIVIDUAL COMPONENT UNRELIABILITIES***

        CALL RMAX(QHATI, K, QHTMAX, QINDX)
        IF (LOOP .EQ. 1) THEN
        ENDIF

***CALCULATE THE AHAT SUB I'S (WEIGHT ESTIMATES)***
***IF COMPONENT HAS NO FAILURES AHAT SUB I IS ZERO***

        SUMNAI = 0.
        DO 165 I=1, K
             AHATI(I) = QHATI(I) / QHTMAX
             SUMNAI = SUMNAI + N(I) * AHATI(I)
 165    CONTINUE

***1 COMPONENT FAILURE SERIES SYSTEM***

        IF (FCT .EQ. 1) THEN
           LOOPS0(LOOP)=' *ONECF*  '
           DO 305 ALF=1,MAXALF
              SUC=REAL(NTEST-BIGF)
              FDEG1=2.*(REAL(BIGF)+1.)
              FDEG2=2.*SUC
              STUD=FIN(1.-ALFA(ALF),FDEG1,FDEG2)
              RSHAT(ALF,LOOP)=SUC/(SUC+(REAL(BIGF)+1.)*STUD)
*             PRINT *,'SUC=',SUC,'FAIL=',BIGF,'NTEST=',NTEST
*             PRINT *,'FIN=',STUD
*             PRINT *,'ALFA=',ALFA(ALF),'RSHAT=',RSHAT(ALF,LOOP)
              IF (FLAG .EQ. 1) THEN
                   RHTSTR(ALF,LOOP)=RSHAT(ALF,LOOP)
              ELSE
              ENDIF
 305       CONTINUE
        ENDIF

***CALCULATE 1 REPLICATION OF UPPR ALFA C.L. ON SYSTEM RELIABILITY***

        DEGFR(LOOP) = 2 * (1 + BIGF)

        DO 170 ALF=1, MAXALF
             CALL MDCHI(1 - ALFA(ALF),DEGFR(LOOP),CHISQ(ALF,LOOP), ERROR)
```

```
            QHTUPR(ALF,LOOP) = CHISQ(ALF,LOOP) / (2 * SUMNAI)
            IF(FLAG.EQ.1) THEN
                 RHTSTR(ALF,LOOP) = 1 -(CHISQ(ALF,LOOP) / REAL(2*N(1)))
            ELSE
            END IF

***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR COMPNTS. IN SERIES***

            IF (FCT .NE. 1) THEN
            CALL RHTSRS(QHTUPR(ALF,LOOP), AHATI,K, RSHAT(ALF,LOOP))
            ENDIF

***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR BRIDGE STRUCTURE***

            IF (IONECT .NE. 1) THEN
               CALL RHTBRG(QHTUPR(ALF,LOOP),AHATI,K,RSHTBR(ALF,LOOP))
            ENDIF
 170  CONTINUE

***EXACTLY 1 COMPONENT FAILS AND REDUNDANT COMPONENT***

      IF ((IONECT .EQ. 1) .AND. (K .EQ.5)) THEN
           DO 207 I=1, K
                NIREAL(I) = REAL(N(I))
 207       CONTINUE
         CALL USMNMX(NIREAL,K,INC,NIMIN,NIMAX)
         DO 206 ALF=1,MAXALF
            RSHTBR(ALF,LOOP)=ALFA(ALF)**(1./NIMIN)
 206     CONTINUE
      ENDIF

***THIS ELSE AND ENDIF ARE FOR THE TEST AGAINST MAXRUN***

      ELSE
           WRITE(1,'('' '',/''PROGRAM EXCEEDED THE MAX NO. OF RUNS'',
     +'' ALLOWED OF:'',I6)') TOTREP
      GOTO 9999

      END IF
      GOTO 10
      END IF

C     WRITE(2,'(''UNSORTED RSHAT 1  IS:'',/10(F8.5))')
C    +(RSHAT(1,LOOP), LOOP=1, MAXREP)
C     WRITE(2,'(''UNSORTED RSHAT 2  IS:'',/10(F8.5))')
C    +(RSHAT(2,LOOP), LOOP=1, MAXREP)
C     IF(FLAG.EQ.1) THEN
C          WRITE(2,'(''UNSORTED RHTSTR 1  IS:'',/10(F8.5))')
C    +(RHTSTR(1,LOOP), LOOP=1, MAXREP)
C          WRITE(2,'(''UNSORTED RHTSTR 2  IS:'',/10(F8.5))')
C    +(RHTSTR(2,LOOP), LOOP=1, MAXREP)
C     ELSE
C     END IF
C     IF(K.EQ.5) THEN
C          WRITE(2,'(''UNSORTED RSHTBR 1  IS:'',/10(F8.5))')
C    +(RSHTBR(1,LOOP), LOOP=1, MAXREP)
```

```
C          WRITE(2,'(''UNSORTED RSHTBR 2  IS:'',/10(F8.5))')
C     +(RSHTBR(2,LOOP), LOOP=1, MAXREP)
C      ELSE
C      END IF
C      WRITE (2,'(''ZERO AND ONE FAILURE REPS:'',/10(A8))')
C     +  (LOOPS0(LOOP),LOOP=1,MAXREP)

***SORT THE ARRAYS OF SYSTEM UNRELIABILITIES(1 FOR EACH CONF. LEVEL)***

      DO 700 ALF=1, MAXALF
           DO 800 REPS=1, MAXREP
                TRANSQ(REPS) = QHTUPR(ALF,REPS)
                TRANSR(REPS) = RSHAT(ALF,REPS)
                TRNSTR(REPS) = RHTSTR(ALF,REPS)
                TRANBR(REPS) = RSHTBR(ALF,REPS)
 800       CONTINUE
           CALL SHSORT(TRANSQ,KEY1,MAXREP)
           CALL SHSORT(TRANSR,KEY2,MAXREP)
           CALL SHSORT(TRNSTR,KEY3,MAXREP)
           CALL SHSORT(TRANBR,KEY4,MAXREP)
           DO 900 REPS=1, MAXREP
                QHTUPR(ALF,REPS) = TRANSQ(REPS)
                RSHAT(ALF,REPS) = TRANSR(REPS)
                RHTSTR(ALF,REPS) = TRNSTR(REPS)
                RSHTBR(ALF,REPS) = TRANBR(REPS)
 900       CONTINUE
 700  CONTINUE

***PRINT OUTPUT REPORT HEADINGS***

      WRITE(1,6666)
      WRITE(1,6667) MAXREP
      WRITE(1,6668) K
      WRITE(1,6669)
      IF(K.EQ.5) THEN
           WRITE(1,6699)
      ELSE
      END IF
      WRITE(1,6670) MSTRQ
      WRITE(1,6671)
      WRITE(1,C1C15)
      WRITE(1,3334) AI
      WRITE(1,0007)
      WRITE(1,C1C15)
      WRITE(1,3334) QI
      WRITE(1,0005)
      WRITE(1,C1C15)
      WRITE(1,3335) N
      WRITE(1,6674)

***COMPUTE THE VALUE RS OF THE TRUE SYSTEM REL. FNCTN.(SERIES SYSTEM)***
***  AND FOR THE 5-COMPONENT BRIDGE STRUCTURE***


      CALL RSRS(QI,K,RS)
```

```
      WRITE(1,'('' '',////''THE TRUE SERIES SYSTEM '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RS
      CALL RBRIDG(QI,K,RSBRDG)
      IF(K.EQ.5) THEN
      WRITE(1,'('' '',////''THE TRUE BRIDGE STRUCTURE '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RSBRDG
      ELSE
      END IF
      WRITE(1,6675)

***COMPUTE THE DIFFERENCE 'DELTAR' BTWN. RS AND RSHAT OF THE THEO***
***RETICAL QUANTILE GIVEN BY ALFA(MUST USE SORTED RSHAT ARRAY)***

      IF(FLAG.EQ.1) THEN
      WRITE(1,5755)
      ELSE
      END IF
      DO 450 ALF=1, MAXALF
           QUANTL(ALF) = MAXREP * (1 - ALFA(ALF))
           DELTAR(ALF) = RS - RSHAT(ALF,QUANTL(ALF))
           DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
           IF(FLAG.EQ.1) THEN
                DELSTR(ALF) = RS - RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5656) RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5657) DELSTR(ALF)
           ELSE
           END IF
           IF(K.EQ.5) THEN
                DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5666) RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5667) DELBRG(ALF)
           ELSE
           END IF
           WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
           WRITE(1,5556) RSHAT(ALF,QUANTL(ALF))
           WRITE(1,5557) DELTAR(ALF)
 450  CONTINUE
      PRINT *, 'QUANTL(1) IS:', QUANTL(1)
      PRINT *, 'QUANTL(2) IS:', QUANTL(2)

***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***                ******** RSHAT *******                      ***

      WRITE(1,6676)
      DO 400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 500 REPS=1, MAXREP
                DIFF(REPS) = RS - RSHAT(ALF,REPS)
 500       CONTINUE
           DO 600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
```

```
     +                  (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                        GO TO 620
                   ELSEIF(DIFF(REPS).LT.0.) THEN
                        TRUQNT(ALF) = REPS
                        GO TO 610
                   ELSE
                   END IF
 600          CONTINUE
 610          IF(TRUQNT(ALF).EQ.0.) THEN
                   WRITE(1,4443) ALFA(ALF)
                   WRITE(1,'('' '',/''THE SMALLEST'',
     +             '' DIFFERENCE BETWEEN RS AND RSHAT IS:'',F10.5)') DIFF(
     +             MAXREP)
              ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                   WRITE(1,4442) ALFA(ALF)
                   WRITE(1,'('' '',/''ALL RSHAT'',
     +               '' ARE GREATER THAN RS'')')
              ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +        THEN
                   WRITE(1,4444) ALFA(ALF),
     +             (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                   WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF))
                   WRITE(1,4446)
              ELSE
                   WRITE(1,4444) ALFA(ALF),
     +             ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                   WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF)-1)
                   WRITE(1,4447)
 620          END IF
 400     CONTINUE


***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***          ********* RSHTBR (BRIDGE) ********                  ***

        IF(K.EQ.5) THEN
        DO 401 ALF=1,MAXALF
        TRUQNT(ALF) = 0
             DO 501 REPS=1, MAXREP
                  DIFF(REPS) = RSBRDG - RSHTBR(ALF,REPS)
 501         CONTINUE
             DO 601 REPS=1, MAXREP
                  IF(ABS(DIFF(REPS)).LE.EPS) THEN
                       TRUQNT(ALF) = REPS
                       WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +                 F8.4)')
     +                 (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                       GO TO 621
                  ELSEIF(DIFF(REPS).LT.0.) THEN
                       TRUQNT(ALF) = REPS
                       GO TO 611
                  ELSE
                  END IF
 601         CONTINUE
 611         IF(TRUQNT(ALF).EQ.0.) THEN
                  WRITE(1,4443) ALFA(ALF)
```

```
                WRITE(1,'('' '',/''THE SMALLEST'',
     +          '' DIFFERENCE BETWEEN RSBRDG AND RSHTBR IS:'',
     +          F10.5)') DIFF(MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RSHTBR'',
     +          '' ARE GREATER THAN RSBRDG'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 621       END IF
 401  CONTINUE
      ELSE
      END IF


***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***                ********* RHTSTR *********                 ***

      IF(FLAG.EQ.1) THEN
      DO 4400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 5500 REPS=1, MAXREP
                DIFF(REPS) = RS - RHTSTR(ALF,REPS)
 5500       CONTINUE
           DO 6600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                     GO TO 6620
                ELSEIF(DIFF(REPS).LT.0.) THEN
                     TRUQNT(ALF) = REPS
                     GO TO 6610
                ELSE
                END IF
 6600       CONTINUE
 6610       IF(TRUQNT(ALF).EQ.0.) THEN
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST'',
     +          '' DIFFERENCE BETWEEN RS AND RHTSTR IS:'',
     +          F9.5)') DIFF(MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RHTSTR'',
     +          '' ARE GREATER THAN RS'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
```

```
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 6620      END IF
 4400 CONTINUE
      ELSE
      END IF

***PRINT THE ARRAYS PERTINENT TO THE OUPUT OF EACH REPLICATION***

      IF(PRNT.EQ.1) THEN
      I = 1
 185  WRITE(1,REPSHD) ALFA(SELCTA), ALFA(SELCTA),
     +ALFA(SELCTB),ALFA(SELCTB),ALFA(SELCTA),ALFA(SELCTA),ALFA(SELCTB),
     +ALFA(SELCTB)
 175  IF(I.GE.(MAXREP + 1)) THEN
           GOTO 180
      ELSE
           IF( (I.EQ.71).OR.(I.EQ.211).OR.(I.EQ.351).OR.(I.EQ.491).OR.
     +     (I.EQ.631).OR.(I.EQ.771).OR.(I.EQ.911).OR.(I.EQ.1051) ) THEN
                I = I + 70
                WRITE(1,'(''+'')')
                GOTO 185
           ELSE

           WRITE(1,3336) I, INT(DEGFR(I)), CHISQ(1,I), QHTUPR(1,I),
     +     CHISQ(2,I), QHTUPR(2,I)
           END IF
           IF(I + 70.LE.MAXREP) THEN
                WRITE(1,3337) I+70,INT(DEGFR(I+70)),CHISQ(1,I+70),
     +          QHTUPR(1,I+70),CHISQ(2,I+70),QHTUPR(2,I+70)
           ELSE
           END IF
       I = I + 1
       GOTO 175
 180   END IF
       ELSE
       ENDIF
 9999  WRITE(1,'(''THE TOTAL NO OF REPS WAS:'',I8)') TOTREP
       WRITE(1,'(''THE TOTAL NO OF EFFECTIVE REPS WAS:'',I8)') LOOP
       WRITE(1,'(''THE TOTAL NO OF NO FAILURE RUNS WAS:'',I8)') ZFAILS
       WRITE(1,'(''AVERAGE  NO. OF COMPONENTS PER REPLICATION WITH '',
      +''NO FAILURES:'',F5.2)') ZFPREP / MAXREP
       WRITE(1,'(''THE TOTAL NO OF RUNS WITH FAILURES WAS:'',I8)') FAILS
 0008  FORMAT (/ 3X,'C 1',5X,'C 2',
      +5X,'C 3',5X,'C 4',5X,'C 5',5X,'C 6',5X,'C 7',5X,
      +'C 8',5X,'C 9',5X,'C 10',4X,'C 11',4X,
      +'C 12',4X,'C 13',4X,'C 14',4X,'C 15')
 0009  FORMAT(/1X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
```

```
    +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')',
    +2X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
    +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')'/)
0001 FORMAT (///'UNIFORM RANDOM DEVIATES ARE:')
0002 FORMAT (///'BERNOULLI TRIALS ARE:')
0003 FORMAT (///'TOTAL NO. OF FAILURES FOR EACH COMPONENT:')
0004 FORMAT (///'ESTIMATED UNRELIABILITY FOR EACH COMPONENT:')
0005 FORMAT (///'TOTAL NUMBER OF MISSION TESTS:')
0006 FORMAT (///'ESTIMATED WEIGHTS FOR EACH COMPONENT:')
0007 FORMAT (///'Q I FOR EACH COMPONENT:')
1111 FORMAT (15F8.5)

2222 FORMAT (/1X,15(I4,4X))
3333 FORMAT (/1X,15(I4,4X))
3334 FORMAT (/15F8.5)
3335 FORMAT (/1X,15(I4,4X))
3336 FORMAT (T3,I4,T9,I3,T13,F11.5,T27,F8.5,T39,F11.5,T53,F8.5)
3337 FORMAT ('+',T67,I4,T73,I3,T77,F11.5,T91,F8.5,T103,F11.5,T117,F8.5)
4442 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
    +'LIMIT IS: ',T50,' 00.000 ')
4443 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
    +'LIMIT IS: ',T50,'100.0000')
4444 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
    +'LIMIT IS: ',T50,F8.4)
4445 FORMAT (' ',/'THE RSHAT VALUE CLOSEST TO RS IS: ',T51,F8.5)
4446 FORMAT (':',/'(FIRST NEGATIVE DIFFERENCE)')
4447 FORMAT (' ',/'(ELEMENT PRECEEDING FIRST NEGATIVE DIFFERENCE)')
4448 FORMAT (' ',/'THE RHTSTR VALUE CLOSEST TO RS IS: ',T51,F8.5)
4449 FORMAT (' ',/'THE RSHTBR VALUE CLOSEST TO RSBRDG IS: ',T51,F8.5)
5555 FORMAT (' ',///'THE ',I4,'(1-',F4.3,') QUANTILE IS:',T49,F8.3)
5556 FORMAT (' ',/'THE VALUE OF RSHAT FOR THAT QUANTILE IS:',T51,F8.5)
5557 FORMAT (' ',/'THE DIFFERENCE(RS - RSHAT) IS:',T51,F8.5)
5656 FORMAT (' ',/'THE VALUE OF RHTSTR FOR THAT QUANTILE IS:',T51,F8.5)
5666 FORMAT (' ',/'THE VALUE OF RSHTBR FOR THAT QUANTILE IS:',T51,F8.5)
5657 FORMAT (' ',/'THE DIFFERENCE(RS - RHTSTR) IS:',T51,F8.5)
5667 FORMAT (' ',/'THE DIFFERENCE(RS - RSHTBR) IS:',T51,F8.5)
5755 FORMAT (' ',///'SINCE THE NO. OF MISSION TESTS IS THE SAME FOR',
    +' ALL COMPONENTS THE CLOSED FORM SERIES SYSTEM RELIABILITY ',
    +'''RHTSTR'' IS COMPUTED')
6666 FORMAT ('+','**************************************************',
    +'********** RUN INPUT SETTINGS **********************************',
    +'************************')
6667 FORMAT (' ',//'NUMBER OF REPLICATIONS:',T50,I4)
6668 FORMAT (' ',//'NUMBER OF COMPONENTS:',T50,I4)
6669 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'SERIES')
6699 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'BRIDGE')
6670 FORMAT (' ',//'MASTER UNRELIABILITY USED:',T50,F8.5)
6671 FORMAT (' ',//'INPUT WEIGHTS(A SUB I''S):')
6674 FORMAT ('+',///'**************************************************',
    +'**R U N  R E S U L T S**********************************************',
    +'***************')
6675 FORMAT ('+',///'**************************************************',
    +' ESTIMATE ERRORS ***********************************************',
    +'****************')
6676 FORMAT ('+',///'**************************************************',
    +' TRUE CONFIDENCE LIMITS ****************************************',
```

```
+'**********')
 END
```

APPENDIX E. FORTRAN CODE FOR THE PREFERRED LOWER CONFIDENCE LIMIT FOR SYSTEM RELIABILITY (SERIES-PARALLEL SYSTEM WITH A 2/3 COMPONENT

```
      PROGRAM ZFYSCN
*****************************************************************************
*                                                                           *
*      TITLE: BINOMIAL INTERVAL ESTIMATION PROCEDURE                        *
*             ZERO FAILURES ALLOWED; NO SCALING                             *
*     AUTHOR: E. F. BELLINI, LT, USN                                        *
*     MODIFIED BY:  LT VALERIE A. COVINGTON,USN   (MAR 90)
*       DATE: NOV 89                                                        *
*                                                                           *
*     THIS PROGRAM COMPUTES THE TRUE CONFIDENCE LEVEL FOR THE ESTIMATE      *
*     RELIABILITY OF A SERIES AND BRIDGE SYSTEM GIVEN THE RELIABILITY       *
*     OF THEIR COMPONENTS                                                   *
*                                                                           *
*     IN ITS PRESENT CONFIGURATION THIS PROGRAM IS SET UP TO RUN 12          *
*     TIMES EACH TIME PRODUCING 1000 REPLICATIONS USING A DIFFERENT         *
*     SET OF INPUT DATA.  RUN THE PROGRAM FROM CMS BY TYPING 'B1 EXEC'.     *
*     THE REXX EXEC PROGRAM                                                 *
*     'B1' CALLS THE INPUT FILES TO BE READ AND NAMES THE 12 OUTPUT         *
*     FILES RESULTING FROM THE 12 CONSECUTIVE RUNS.  BY EDITING THE         *
*     INDEX COUNTERS I, J, K OF THE 'B1' EXEC ONE CAN RUN ANY USER-         *
*     SPECIFIC RUN FROM JUST ONE RUN TO ALL 12.                             *
*                                                                           *
*     VARIABLES USED                                                        *
*                                                                           *
*          AHATI  : WEIGHT ESTIMATES FOR EACH COMPONENT                     *
*          AI     : INPUT WEIGHTS FOR EACH COMPONENT                        *
*          ALFA   : LEVELS OF SIGNIFICANCE                                  *
*          BIGF   : TOTAL NO. OF FAILURES FOR EACH REPLICATION              *
*          CHISQ  : CHI-SQUARE RANDOM VARIABLE VALUE                        *
*          C1C15  : FORMAT LABEL                                            *
*          DEGFR  : DEGREES OF FREEDOM                                      *
*          DELBRG : DIFFERENCE FOR BRIDGE SYSTEM                            *
*          DELSTR : DIFFERENCE FOR SERIES SYSTEM- CLOSED FORM               *
*          DELTAR : DIFFERENCE FOR SERIES SYSTEM                            *
*          DIFF   : DIFFERENCE (TRUE REL. - ESTIMATED REL.)                 *
*          EPS    : SMALL QUANTITY(CONSTANT)                                *
*          ERROR  : PARAMETER FOR IMSL ROUTINE                              *
*          FAILS  : COUNTS NO. OF REPLICATIONS WITH AT LST. 1 FAILURE       *
*          FI     : NO. OF FAILURES FOR EACH COMPONENT(ALL MISSION TST)     *
*          FLAG   : 1 IF ALL COMP. HAVE SAME NO. OF MISSION TESTS           *
*          INC    : INCREMENT STEP SIZE FOR ROUTINE USMNMX                  *
*          KEY1   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KEY2   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KEY3   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KEY4   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KK     : ARRAY SIZING PARAMETER FOR THE MAX NO OF COMPONENTS     *
*          LOOP   : COUNTS NO. OF REPLICATION PERFORMED                     *
*          MAXALF : MAX NO. OF SIGNIFICANT LEVELS DESIRED(ARRAY SIZING)     *
```

```
*          MAXREP : MAX NO. OF REPLICATIONS                                  *
*          MAXRUN : MAX NO. OF PROGRAM ITERATIONS ALLOWED                    *
*          MSTRQ  : MASTER UNRELIABILITY(USED WITH AI'S TO CALC. QI'S)       *
*          MULT   : MULTIPLIER FOR RANDOM NO. GENERATOR SRND                 *
*          N      : NO. OF MISSION TEST FOR EACH COMPONENT                   *
*          NIMAX  : MAX NO. OF MISSION TESTS                                 *
*          NIMIM  : MIN NO. OF MISSION TESTS                                 *
*          NINDX  : INDEX NO. OF MAX NO. OF MISSION TESTS                    *
*          NIREAL : NO. OF MISSION TESTS TRANSFORMED TO REAL                 *
*          NMAX   : MAX NO. OF MISSION TESTS FOR OUTPUT CONTROL              *
*          NPRNT  : FLAG FOR DETAILED REPORT OUTPUT                          *
*          PRNT   : SAME AS ABOVE(PARAMETER)                                 *
*          QHATI  : UNRELIABILITY ESTIMATES FOR EACH COMPONENT               *
*          QHTMAX : LARGEST QHATI                                            *
*          QHTUPR : UPPER LIMIT ON SYSTEM UNRELIABILITY                      *
*          QI     : INPUT UNRELIABILIY FOR EACH COMPONENT                    *
*          QINDX  : INDEX                                                    *
*          QUANTL : QUANTILE                                                 *
*          REPSHD : REPLICATIONS HEADING FORMAT NUMBER                       *
*          RHTSTR : SERIES SYSTEM RELIABILITY ESTIMATE(CLOSED FORM)          *
*          RS     : TRUE SERIES SYSTEM RELIABILITY                           *
*          RSBRDG : TRUE BRIDGE SYSTEM RELIABILITY                           *
*          RSHAT  : SERIES SYSTEM RELIABILITY ESTIMATE                       *
*          RSHTBR : BRIDGE SYSTEM RELIABILITY ESTIMATE                       *
*          SEED   : PARAMETER                                                *
*          SELCTA : SIGNIFICANCE LEVEL SELECTION                             *
*          SELCTB : SIGNIFICANCE LEVEL SELECTION                             *
*          SORT   : PARAMETER FOR ROUTINE SRND                               *
*          SUMNAI : SUM OF THE PRODUCT OF NI'S AND AI'S                      *
*          TEMP   : TEMPORARY ARRAY                                          *
*          TOTREP : TOTAL NUMBER OF PROGRAM ITERATIONS                       *
*          TRANBR : TEMPORARY ARRAY                                          *
*          TRANSQ : TEMPORARY ARRAY                                          *
*          TRANSR : TEMPORARY ARRAY                                          *
*          TRIALS : BERNOULLI TRIALS ARRAY (2-DIM)                           *
*          TRNSTR : TEMPORARY ARRAY                                          *
*          TRUQNT : TRUE QUANTILE                                            *
*          UNIRV  : UNIFORM RANDOM DEVIATES (2-DIM)                          *
*          ZFAILS : TOTAL NUMBER OF REPLICATIONS WITH ZERO FAILURES          *
*          ZFPREP : NO. OF COMPNTS. WITH ZERO FAILURES PER REPLICATION       *
*                                                                            *
******************************************************************************

      PARAMETER (KK=10,MAXALF=2,NPRNT=0)
      PARAMETER (MAXREP=1000, MAXRUN=2000, EPS=.000001)
      REAL*4 UNIRV(15,1000),TEMP(1000),QI(KK),AI(KK),AHATI(KK)
      REAL*4 QHATI(KK), NMAX, NNMAX, QHTMAX, CHISQR(5,5), ALFA(MAXALF)
      REAL*4 DF(5),AALFA(5),SUMNAI,RSHAT(MAXALF,MAXREP),RS
      REAL*4 KEY1(MAXREP),KEY2(MAXREP),KEY3(MAXREP),TRNSTR(MAXREP)
      REAL*4 DEGFR(MAXREP), QHTUPR(MAXALF,MAXREP),CHISQ(MAXALF,MAXREP)
      REAL*4 QUPA1(MAXREP), QUPA2(MAXREP),RHTSTR(MAXALF,MAXREP)
      REAL*4 DELTAR(MAXALF), TRANSQ(MAXREP),TRANSR(MAXREP),DIFF(MAXREP)
      REAL*4 DELSTR(MAXALF),NIMIN,NIMAX,NIREAL(KK)
      REAL*4 RSHTBR(MAXALF,MAXREP),DELBRG(MAXALF),KEY4(MAXREP)
      REAL*4 TRANBR(MAXREP), RSBRDG ,MSTRQ
      REAL*4 ZFPREP
```

```
      REAL*4 AVGN,SUC,STUD,PTEMP(10),FDEG1,FDEG2,P3,S3,S4

      INTEGER SEED, MULT, SORT, TRIALS(15,1000), BIGF, FI(KK), N(KK)
      INTEGER NINDX, QINDX, ERROR, REPS, SELCTA, SELCTK, TOTREP
      INTEGER C1C15, REPSHD, SELCTB, ALF, FLAG, LOOP,PRNT
      INTEGER QUANTL(MAXALF), TRUQNT(MAXALF),ZFAILS,FAILS,INC
      INTEGER NTEST,FCT,HFI

      CHARACTER*8 LOOPS0(MAXREP)

      DATA SEED/123457/, MULT/1/, INC/1/
      DATA AALFA/.01,.05,.9,.95,.99/, DF/1,5,10,30,40/
      DATA ALFA/.20,.050/
      DATA SORT/0/

      ASSIGN 8 TO C1C15
      ASSIGN 9 TO REPSHD

*     CALL COMPRS
      PRNT = NPRNT

      DO 12 I=1,KK
           AI(I) = 9999.
           N(I) = 99999999
   12 CONTINUE

      READ(03,*)K,MSTRQ

      DO 11 I=1,K
      READ(03,*) AI(I),N(I)
   11 CONTINUE


      IF(K.NE.5) THEN
           WRITE(1,'(''WARNING: BRIDGE STRUCTURE '',
     +''ONLY USES THE FIRST 5 COMPONENTS'')')
      ELSE
      END IF

***INITIALIZE THE QHTUPR ARRAY OF UNRELIABILITY REPLICATIONS,   ***
*  RSHAT ARRAY OF ESTIMATE SYSTEM RELIABILITY REPLICATIONS       *
*  AND RHTSTR ARRAY OF EST. SYST. REL. FOR A SERIES SYST WHEN    *
***ALL THE COMPONENT MISSION TESTS ARE EQUAL IN NUMBER          ***

      DO 172 ALF=1,MAXALF
           DO 173 REPS=1,MAXREP
                QHTUPR(ALF,REPS) = 0.
                RSHAT(ALF,REPS) = 0.
                RHTSTR(ALF,REPS) = 0.
                RSHTBR(ALF,REPS) = 0.
                LOOPS0(REPS)=' ****** '
  173       CONTINUE
  172  CONTINUE

***SET FLAG TO 1 IF ALL COMPONENTS HAVE SAME NO. OF MISSION TESTS****
```

```
      FLAG=1
      DO 50 I=1,K -1
           IF((N(I) - N(I+1)).NE.0) THEN
                FLAG=0
           ELSE
           END IF
   50 CONTINUE
      PRINT *, 'FLAG IS:', FLAG

***MAIN PROGRAM OUTER LOOP START(EVERY LOOP IS ONE REPLICATION)***

      ZFPREP = 0.
      ZFAILS = 0
      FAILS = 0
      TOTREP = 0
      LOOP = 0
   10 IF(LOOP.LT.MAXREP) THEN
           LOOP = LOOP + 1
           IF(TOTREP.LT.MAXRUN) THEN
                TOTREP = TOTREP + 1
      SELCTA = 1
      SELCTB = 2

***FILL ARRAY KEY(REPS) WITH INTEGERS 1 TO K TO BE USED AS OUTPUT***
***OF THE SUBROUTINE SHSORT                                      ***

      DO 95 REPS=1, MAXREP
           KEY1(REPS) = REPS
           KEY2(REPS) = REPS
           KEY3(REPS) = REPS
           KEY4(REPS) = REPS
   95 CONTINUE

***CALCULATE NMAX NOT TO PRINT LONGER THAN THE MAX SAMPLE SIZE***

***CALCULATE THE MAXIMUM NO. OF TRIALS AND ITS INDEX NO.***

      CALL IMAX(N,K,NMAX,NINDX)


***CALCULATE THE QI'S FROM THE GIVEN MASTER Q AND THE AI'S***

      DO 115 I=1, K
           QI(I) = MSTRQ * AI(I)
  115 CONTINUE
           S3=QI(3)
           S4=QI(4)
      DO 120 I=1,15
           DO 125 J=1,500
                UNIRV(I,J) = 999.
                TRIALS(I,J) = 99999
  125      CONTINUE
  120 CONTINUE

*** DRAW UNIFORM (0,1) RV'S AND CONVERT TO BERNOULLI TRIALS***
      DO 130 I=1, K
```

```
            CALL SRND(SEED, TEMP, N(I), MULT, SORT)
            DO 135 J=1, N(I)
                 UNIRV(I,J) = TEMP(J)
                 IF (UNIRV(I,J).LE. 1 - QI(I)) THEN
                      TRIALS(I,J) = 0
                 ELSE
                      TRIALS(I,J) = 1
                 END IF
 135   CONTINUE
 130   CONTINUE


***CALCULATE THE NO. OF FAILURES FOR EACH COMPONENT***

       DO 150 I=1, K
            FI(I) = 0
 150   CONTINUE
       IONECT = 0

***CALCULATE THE F SUB I'S AND THE GRAND TOTAL NO. OF FAILURES***
       BIGF = 0
       DO 155 I=1, K
            DO 160 J=1, N(I)
                 FI(I) = FI(I) + TRIALS(I,J)
 160        CONTINUE
       IF (FI(I) .EQ. 0) THEN
          ZFPREP=ZFPREP+1
       ELSE
       ENDIF
       BIGF = BIGF + FI(I)

       QHATI(I) = REAL(FI(I)) / N(I)
 155   CONTINUE

***Change for Series-Parallel System with 2 out of 3 component***


       IF (FI(4) .EQ. 0) THEN
          ZFPREP=ZFPREP - 1
       ENDIF
       BIGF = BIGF - FI(4)
       FI(4) = 0
       DO 161 I=1,N(4)
         HFI=0
         DO 162 J=1,2
            CALL SRND(SEED, PTEMP(J), N(4), MULT, SORT)
            IF (PTEMP(J) .GT. 1-S4) THEN
                HFI = HFI + 1
            ENDIF
 162     CONTINUE
         IF (HFI .EQ. 2) THEN
            FI(4) = FI(4) + 1
         ENDIF
 161   CONTINUE
       BIGF = BIGF + FI(4)
       IF (FI(4) .EQ. 0) THEN
```

```
            ZFPREP = ZFPREP + 1
          ELSE
          ENDIF
          IF (FI(3) .EQ. 0) THEN
             ZFPREP=ZFPREP - 1
          ENDIF
          BIGF = BIGF - FI(3)
          FI(3) = 0
          DO 163 I=1,N(3)
            HFI=0
            DO 164 J=1,3
               CALL SRND(SEED, PTEMP(J), N(3), MULT, SORT)
               IF (PTEMP(J) .GT. 1-S3) THEN
                   HFI = HFI + 1
               ENDIF
  164       CONTINUE
            IF (HFI .GE. 2) THEN
               FI(3) = FI(3) + 1
            ENDIF
  163     CONTINUE
          BIGF = BIGF + FI(3)
          IF (FI(3) .EQ. 0) THEN
            ZFPREP = ZFPREP + 1
          ELSE
          ENDIF
          DO 19 I=1,K
           QI(I) = MSTRQ * AI(I)
          QHATI(I) = REAL(FI(I)) / N(I)

    19    CONTINUE
          QI(4) = QI(4)**2
          P3 = 1.-QI(3)
          QI(3) = 1.-((3.*P3**2*QI(3))+(P3**3))
***COUNTS NUMBER OF COMPONENTS THAT HAVE FAILED***

          DO 156 I=1,K
             IF (FI(I) .NE. 0) IONECT=IONECT+1
    156   CONTINUE

***CASE WHERE NO COMPONENTS HAVE ANY FAILURES***

          IF(BIGF.EQ.0) THEN
               LOOPSO(LOOP)=' *ZERO* '
               ZFAILS = ZFAILS + 1
               AVGN=0.0
               DO 200 I=1,K
                    AVGN=AVGN+REAL(N(I))
    200        CONTINUE
               AVGN=AVGN/REAL(K)
               DO 205 ALF=1, MAXALF
                    RSHAT(ALF,LOOP)= ALFA(ALF)**(1./AVGN)
               IF(FLAG.EQ.1) THEN
                    RHTSTR(ALF,LOOP)=ALFA(ALF)**(1./N(1))
               ELSE
               END IF
*              PRINT *,LOOP',LOOP,'RSHAT',RSHAT(ALF,LOOP)
```

```
 205        CONTINUE
                 DEGFR(LOOP) = 2.
                 GO TO 10
      ELSE
           FAILS = FAILS + 1
      END IF

***COUNTS NUMBER OF COMPONENTS THAT FAIL RECORDS NO. COMPT TESTS***
      FCT=0
      DO 202 I=1,K
           IF (FI(I) .NE. 0) THEN
              FCT=FCT+1
              NTEST=N(I)
       ENDIF
 202  CONTINUE

***FIND THE MAX OF THE INDIVIDUAL COMPONENT UNRELIABILITIES***

      CALL RMAX(QHATI, K, QHTMAX, QINDX)

***CALCULATE THE AHAT SUB I'S (WEIGHT ESTIMATES)***
***IF COMPONENT HAS NO FAILURES AHAT SUB I IS ZERO***

      SUMNAI = 0.
      DO 165 I=1, K
           AHATI(I) = QHATI(I) / QHTMAX
           SUMNAI = SUMNAI + N(I) * AHATI(I)
 165  CONTINUE

***1 COMPONENT FAILURE SERIES SYSTEM***

      IF (FCT .EQ. 1) THEN
         LOOPS0(LOOP)=' *ONECF*  '
         DO 305 ALF=1,MAXALF
            SUC=REAL(NTEST-BIGF)
            FDEG1=2.*(REAL(BIGF)+1.)
            FDEG2=2.*SUC
            STUD=FIN(1.-ALFA(ALF),FDEG1,FDEG2)
            RSHAT(ALF,LOOP)=SUC/(SUC+(REAL(BIGF)+1.)*STUD)
*           PRINT *,'SUC=',SUC,'FAIL=',BIGF,'NTEST=',NTEST
*           PRINT *,'FIN=',STUD
*           PRINT *,'ALFA=',ALFA(ALF),'RSHAT=',RSHAT(ALF,LOOP)
            IF (FLAG .EQ.1) THEN
                 RHTSTR(ALF,LOOP)=RSHAT(ALF,LOOP)
            ELSE
            ENDIF
 305     CONTINUE
      ENDIF

***CALCULATE 1 REPLICATION OF UPPR ALFA C.L. ON SYSTEM RELIABILITY***

      DEGFR(LOOP) = 2 * (1 + BIGF)

      DO 170 ALF=1, MAXALF
           CALL MDCHI(1 - ALFA(ALF),DEGFR(LOOP),CHISQ(ALF,LOOP), ERROR)
           QHTUPR(ALF,LOOP) = CHISQ(ALF,LOOP) / (2 * SUMNAI)
```

```
            IF(FLAG.EQ.1) THEN
                 RHTSTR(ALF,LOOP) = 1 -(CHISQ(ALF,LOOP) / REAL(2*N(1)))
            ELSE
            END IF

***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR COMPNTS. IN SERIES***

            IF (FCT .NE. 1) THEN
            CALL RHTSRS(QHTUPR(ALF,LOOP), AHATI,K, RSHAT(ALF,LOOP))
            ENDIF

***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR BRIDGE STRUCTURE***

            IF (IONECT .NE. 1) THEN
               CALL RHTBRG(QHTUPR(ALF,LOOP),AHATI,K,RSHTBR(ALF,LOOP))
            ENDIF
 170  CONTINUE

***EXACTLY 1 COMPONENT FAILS AND REDUNDANT COMPONENT***

      IF ((IONECT .EQ. 1) .AND. (K .EQ.5)) THEN
           DO 207 I=1, K
                NIREAL(I) = REAL(N(I))
 207       CONTINUE
         CALL USMNMX(NIREAL,K,INC,NIMIN,NIMAX)
         DO 206 ALF=1,MAXALF
            RSHTBR(ALF,LOOP)=ALFA(ALF)**(1./NIMIN)
 206     CONTINUE
      ENDIF

***THIS ELSE AND ENDIF ARE FOR THE TEST AGAINST MAXRUN***

      ELSE
           WRITE(1,'('' '',/''PROGRAM EXCEEDED THE MAX NO. OF RUNS'',
     +'' ALLOWED OF:'',I6)') TOTREP
      GOTO 9999

      END IF
      GOTO 10
      END IF

C     WRITE(2,'(''UNSORTED RSHAT 1  IS:'',/10(F8.5))')
C    +(RSHAT(1,LOOP), LOOP=1, MAXREP)
C     WRITE(2,'(''UNSORTED RSHAT 2  IS:'',/10(F8.5))')
C    +(RSHAT(2,LOOP), LOOP=1, MAXREP)
C     IF(FLAG.EQ.1) THEN
C          WRITE(2,'(''UNSORTED RHTSTR 1  IS:'',/10(F8.5))')
C    +(RHTSTR(1,LOOP), LOOP=1, MAXREP)
C          WRITE(2,'(''UNSORTED RHTSTR 2  IS:'',/10(F8.5))')
C    +(RHTSTR(2,LOOP), LOOP=1, MAXREP)
C     ELSE
C     END IF
C     IF(K.EQ.5) THEN
C          WRITE(2,'(''UNSORTED RSHTBR 1  IS:'',/10(F8.5))')
C    +(RSHTBR(1,LOOP), LOOP=1, MAXREP)
C          WRITE(2,'(''UNSORTED RSHTBR 2  IS:'',/10(F8.5))')
```

```
C     +(RSHTBR(2,LOOP), LOOP=1, MAXREP)
C      ELSE
C      END IF
C      WRITE (2,'(''ZERO AND ONE FAILURE REPS:'',/10(A8))')
C     +  (LOOPS0(LOOP),LOOP=1,MAXREP)

***SORT THE ARRAYS OF SYSTEM UNRELIABILITIES(1 FOR EACH CONF. LEVEL)***

      DO 700 ALF=1, MAXALF
           DO 800 REPS=1, MAXREP
                TRANSQ(REPS) = QHTUPR(ALF,REPS)
                TRANSR(REPS) = RSHAT(ALF,REPS)
                TRNSTR(REPS) = RHTSTR(ALF,REPS)
                TRANBR(REPS) = RSHTBR(ALF,REPS)
 800        CONTINUE
           CALL SHSORT(TRANSQ,KEY1,MAXREP)
           CALL SHSORT(TRANSR,KEY2,MAXREP)
           CALL SHSORT(TRNSTR,KEY3,MAXREP)
           CALL SHSORT(TRANBR,KEY4,MAXREP)
           DO 900 REPS=1, MAXREP
                QHTUPR(ALF,REPS) = TRANSQ(REPS)
                RSHAT(ALF,REPS) = TRANSR(REPS)
                RHTSTR(ALF,REPS) = TRNSTR(REPS)
                RSHTBR(ALF,REPS) = TRANBR(REPS)
 900        CONTINUE
 700  CONTINUE

***PRINT OUTPUT REPORT HEADINGS***

      WRITE(1,6666)
      WRITE(1,6667) MAXREP
      WRITE(1,6668) K
      WRITE(1,6669)
      IF(K.EQ.5) THEN
           WRITE(1,6699)
      ELSE
      END IF
      WRITE(1,6670) MSTRQ
      WRITE(1,6671)
      WRITE(1,C1C15)
      WRITE(1,3334) AI
      WRITE(1,0007)
      WRITE(1,C1C15)
      WRITE(1,3334) QI
      WRITE(1,0005)
      WRITE(1,C1C15)
      WRITE(1,3335) N
      WRITE(1,6674)

***COMPUTE THE VALUE RS OF THE TRUE SYSTEM REL. FNCTN.(SERIES SYSTEM)***
***  AND FOR THE 5-COMPONENT BRIDGE STRUCTURE***


      CALL RSRS(QI,K,RS)
      WRITE(1,'('' '',////''THE TRUE SERIES SYSTEM '',
```

```
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RS
      CALL RBRIDG(QI,K,RSBRDG)
      IF(K.EQ.5) THEN
      WRITE(1,'('' '',////''THE TRUE BRIDGE STRUCTURE '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RSBRDG
      ELSE
      END IF
      WRITE(1,6675)

***COMPUTE THE DIFFERENCE 'DELTAR' BTWN. RS AND RSHAT OF THE THEO***
***RETICAL QUANTILE GIVEN BY ALFA(MUST USE SORTED RSHAT ARRAY)***

      IF(FLAG.EQ.1) THEN
      WRITE(1,5755)
      ELSE
      END IF
      DO 450 ALF=1, MAXALF
           QUANTL(ALF) = MAXREP * (1 - ALFA(ALF))
           DELTAR(ALF) = RS - RSHAT(ALF,QUANTL(ALF))
           DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
           IF(FLAG.EQ.1) THEN
                DELSTR(ALF) = RS - RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5656) RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5657) DELSTR(ALF)
           ELSE
           END IF
           IF(K.EQ.5) THEN
                DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5666) RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5667) DELBRG(ALF)
           ELSE
           END IF
           WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
           WRITE(1,5556) RSHAT(ALF,QUANTL(ALF))
           WRITE(1,5557) DELTAR(ALF)
 450  CONTINUE
      PRINT *, 'QUANTL(1) IS:', QUANTL(1)
      PRINT *, 'QUANTL(2) IS:', QUANTL(2)

***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***              ******** RSHAT ********                      ***

      WRITE(1,6676)
      DO 400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 500 REPS=1, MAXREP
                DIFF(REPS) = RS - RSHAT(ALF,REPS)
 500       CONTINUE
           DO 600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
```

```
                    GO TO 620
               ELSEIF(DIFF(REPS).LT.0.) THEN
                    TRUQNT(ALF) = REPS
                    GO TO 610
               ELSE
               END IF
600        CONTINUE
610        IF(TRUQNT(ALF).EQ.0.) THEN
               WRITE(1,4443) ALFA(ALF)
               WRITE(1,'('' '',/''THE SMALLEST'',
     +         '' DIFFERENCE BETWEEN RS AND RSHAT IS:'',F10.5)') DIFF(
     +         MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
               WRITE(1,4442) ALFA(ALF)
               WRITE(1,'('' '',/''ALL RSHAT'',
     +          '' ARE GREATER THAN RS'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
               WRITE(1,4444) ALFA(ALF),
     +         (TRUQNT(ALF) / REAL(MAXREP)) * 100.
               WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF))
               WRITE(1,4446)
           ELSE
               WRITE(1,4444) ALFA(ALF),
     +         ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
               WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF)-1)
               WRITE(1,4447)
620        END IF
400    CONTINUE


***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***        ********* RSHTBR (BRIDGE) ********                  ***

       IF(K.EQ.5) THEN
       DO 401 ALF=1,MAXALF
       TRUQNT(ALF) = 0
           DO 501 REPS=1, MAXREP
               DIFF(REPS) = RSBRDG - RSHTBR(ALF,REPS)
501        CONTINUE
           DO 601 REPS=1, MAXREP
               IF(ABS(DIFF(REPS)).LE.EPS) THEN
                    TRUQNT(ALF) = REPS
                    WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +              F8.4)')
     +              (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                    GO TO 621
               ELSEIF(DIFF(REPS).LT.0.) THEN
                    TRUQNT(ALF) = REPS
                    GO TO 611
               ELSE
               END IF
601        CONTINUE
611        IF(TRUQNT(ALF).EQ.0.) THEN
               WRITE(1,4443) ALFA(ALF)
               WRITE(1,'('' '',/''THE SMALLEST'',
```

```
     +          '' DIFFERENCE BETWEEN RSBRDG AND RSHTBR IS:'',
     +          F10.5)') DIFF(MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RSHTBR'',
     +           '' ARE GREATER THAN RSBRDG'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 621       END IF
 401  CONTINUE
      ELSE
      END IF


***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***                  ********* RHTSTR *********                 ***

      IF(FLAG.EQ.1) THEN
      DO 4400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 5500 REPS=1, MAXREP
                DIFF(REPS) = RS - RHTSTR(ALF,REPS)
 5500      CONTINUE
           DO 6600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                     GO TO 6620
                ELSEIF(DIFF(REPS).LT.0.) THEN
                     TRUQNT(ALF) = REPS
                     GO TO 6610
                ELSE
                END IF
 6600      CONTINUE
 6610      IF(TRUQNT(ALF).EQ.0.) THEN
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST'',
     +          '' DIFFERENCE BETWEEN RS AND RHTSTR IS:'',
     +          F9.5)') DIFF(MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RHTSTR'',
     +          '' ARE GREATER THAN RS'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
```

```
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 6620      END IF
 4400 CONTINUE
      ELSE
      END IF

***PRINT THE ARRAYS PERTINENT TO THE OUPUT OF EACH REPLICATION***

      IF(PRNT.EQ.1) THEN
      I = 1
 185  WRITE(1,REPSHD) ALFA(SELCTA), ALFA(SELCTA),
     +ALFA(SELCTB),ALFA(SELCTB),ALFA(SELCTA),ALFA(SELCTA),ALFA(SELCTB),
     +ALFA(SELCTB)
 175  IF(I.GE.(MAXREP + 1)) THEN
           GOTO 180
      ELSE
           IF( (I.EQ.71).OR.(I.EQ.211).OR.(I.EQ.351).OR.(I.EQ.491).OR.
     +     (I.EQ.631).OR.(I.EQ.771).OR.(I.EQ.911).OR.(I.EQ.1051) ) THEN
                I = I + 70
                WRITE(1,'(''+'')')
                GOTO 185
           ELSE

           WRITE(1,3336) I, INT(DEGFR(I)), CHISQ(1,I), QHTUPR(1,I),
     +     CHISQ(2,I), QHTUPR(2,I)
           END IF
           IF(I + 70.LE.MAXREP) THEN
                WRITE(1,3337) I+70,INT(DEGFR(I+70)),CHISQ(1,I+70),
     +          QHTUPR(1,I+70),CHISQ(2,I+70),QHTUPR(2,I+70)
           ELSE
           END IF
      I = I + 1
      GOTO 175
 180  END IF
      ELSE
      ENDIF
 9999 WRITE(1,'(''THE TOTAL NO OF REPS WAS:'',I8)') TOTREP
      WRITE(1,'(''THE TOTAL NO OF EFFECTIVE REPS WAS:'',I8)') LOOP
      WRITE(1,'(''THE TOTAL NO OF NO FAILURE RUNS WAS:'',I8)') ZFAILS
      WRITE(1,'(''AVERAGE  NO. OF COMPONENTS PER REPLICATION WITH '',
     +''NO FAILURES:'',F5.2)') ZFPREP / MAXREP
      WRITE(1,'(''THE TOTAL NO OF RUNS WITH FAILURES WAS:'',I8)') FAILS
 0008 FORMAT (/ 3X,'C 1',5X,'C 2',
     +5X,'C 3',5X,'C 4',5X,'C 5',5X,'C 6',5X,'C 7',5X,
     +'C 8',5X,'C 9',5X,'C 10',4X,'C 11',4X,
     +'C 12',4X,'C 13',4X,'C 14',4X,'C 15')
 0009 FORMAT(/1X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
     +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')',
```

```
     +2X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
     +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')'/)
0001 FORMAT (///'UNIFORM RANDOM DEVIATES ARE:')
0002 FORMAT (///'BERNOULLI TRIALS ARE:')
0003 FORMAT (///'TOTAL NO. OF FAILURES FOR EACH COMPONENT:')
0004 FORMAT (///'ESTIMATED UNRELIABILITY FOR EACH COMPONENT:')
0005 FORMAT (///'TOTAL NUMBER OF MISSION TESTS:')
0006 FORMAT (///'ESTIMATED WEIGHTS FOR EACH COMPONENT:')
0007 FORMAT (///'Q I FOR EACH COMPONENT:')
1111 FORMAT (15F8.5)

2222 FORMAT (/1X,15(I4,4X))
3333 FORMAT (/1X,15(I4,4X))
3334 FORMAT (/15F8.5)
3335 FORMAT (/1X,15(I4,4X))
3336 FORMAT (T3,I4,T9,I3,T13,F11.5,T27,F8.5,T39,F11.5,T53,F8.5)
3337 FORMAT ('+',T67,I4,T73,I3,T77,F11.5,T91,F8.5,T103,F11.5,T117,F8.5)
4442 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
     +'LIMIT IS:',T50,' 00.000 ')
4443 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
     +'LIMIT IS:',T50,'100.0000')
4444 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
     +'LIMIT IS:',T50,F8.4)
4445 FORMAT (' ',/'THE RSHAT VALUE CLOSEST TO RS IS: ',T51,F8.5)
4446 FORMAT (' ',/'(FIRST NEGATIVE DIFFERENCE)')
4447 FORMAT (' ',/'(ELEMENT PRECEEDING FIRST NEGATIVE DIFFERENCE)')
4448 FORMAT (' ',/'THE RHTSTR VALUE CLOSEST TO RS IS: ',T51,F8.5)
4449 FORMAT (' ',/'THE RSHTBR VALUE CLOSEST TO RSBRDG IS: ',T51,F8.5)
5555 FORMAT (' ',///'THE ',I4,'(1-',F4.3,') QUANTILE IS:',T49,F8.3)
5556 FORMAT (' ',/'THE VALUE OF RSHAT FOR THAT QUANTILE IS:',T51,F8.5)
5557 FORMAT (' ',/'THE DIFFERENCE(RS - RSHAT) IS:',T51,F8.5)
5656 FORMAT (' ',/'THE VALUE OF RHTSTR FOR THAT QUANTILE IS:',T51,F8.5)
5666 FORMAT (' ',/'THE VALUE OF RSHTBR FOR THAT QUANTILE IS:',T51,F8.5)
5657 FORMAT (' ',/'THE DIFFERENCE(RS - RHTSTR) IS:',T51,F8.5)
5667 FORMAT (' ',/'THE DIFFERENCE(RS - RSHTBR) IS:',T51,F8.5)
5755 FORMAT (' ',///'SINCE THE NO. OF MISSION TESTS IS THE SAME FOR',
     +' ALL COMPONENTS THE CLOSED FORM SERIES SYSTEM RELIABILITY ',
     +'''RHTSTR'' IS COMPUTED')
6666 FORMAT ('+','**************************************************',
     +'********** RUN INPUT SETTINGS **********************************',
     +'************************')
6667 FORMAT (' ',//'NUMBER OF REPLICATIONS:',T50,I4)
6668 FORMAT (' ',//'NUMBER OF COMPONENTS:',T50,I4)
6669 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'SERIES')
6699 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'BRIDGE')
6670 FORMAT (' ',//'MASTER UNRELIABILITY USED:',T50,F8.5)
6671 FORMAT (' ',//'INPUT WEIGHTS(A SUB I''S):')
6674 FORMAT ('+',///'**************************************************',
     +'**R U N  R E S U L T S**********************************************',
     +'****************')
6675 FORMAT ('+',///'**************************************************',
     +' ESTIMATE ERRORS ***************************************************',
     +'****************')
6676 FORMAT ('+',///'**************************************************',
     +' TRUE CONFIDENCE LIMITS ********************************************',
     +'****************')
```

```
END
```

APPENDIX F. FORTRAN CODE FOR THE PREFERRED LOWER CONFIDENCE LIMIT FOR SYSTEM RELIABILITY (PARALLEL SYSTEM)

```
      PROGRAM ZFYSCN
*****************************************************************************
*                                                                           *
*      TITLE: BINOMIAL INTERVAL ESTIMATION PROCEDURE                        *
*             ZERO FAILURES ALLOWED; NO SCALING                             *
*     AUTHOR: E. F. BELLINI, LT, USN                                        *
*     MODIFIED BY:  LT VALERIE A. COVINGTON,USN   (MAR 90)
*       DATE: NOV 89                                                        *
*                                                                           *
*     THIS PROGRAM COMPUTES THE TRUE CONFIDENCE LEVEL FOR THE ESTIMATE      *
*     RELIABILITY OF A SERIES AND BRIDGE SYSTEM GIVEN THE RELIABILITY       *
*     OF THEIR COMPONENTS                                                   *
*                                                                           *
*     IN ITS PRESENT CONFIGURATION THIS PROGRAM IS SET UP TO RUN 12          *
*     TIMES EACH TIME PRODUCING 1000 REPLICATIONS USING A DIFFERENT         *
*     SET OF INPUT DATA.  RUN THE PROGRAM FROM CMS BY TYPING 'B1 EXEC'.     *
*     THE REXX EXEC PROGRAM                                                 *
*     'B1' CALLS THE I[illegible] FILES TO BE READ AND NAMES THE 12 OUTPUT  *
*     FILES RESULTING [illegible]HE 12 CONSECUTIVE RUNS.  BY EDITING THE    *
*     INDEX COUNTERS 1, [illegible]K OF THE 'B1' EXEC ONE CAN RUN ANY USER- *
*     SPECIFIC RUN FROM JUST ONE RUN TO ALL 12.                             *
*                                                                           *
*     VARIABLES USED                                                        *
*                                                                           *
*          AHATI  : WEIGHT ESTIMATES FOR EACH COMPONENT                     *
*          AI     : INPUT WEIGHTS FOR EACH COMPONENT                        *
*          ALFA   : LEVELS OF SIGNIFICANCE                                  *
*          BIGF   : TOTAL NO. OF FAILURES FOR EACH REPLICATION              *
*          CHISQ  : CHI-SQUARE RANDOM VARIABLE VALUE                        *
*          C1C15  : FORMAT LABEL                                            *
*          DEGFR  : DEGREES OF FREEDOM                                      *
*          DELBRG : DIFFERENCE FOR BRIDGE SYSTEM                            *
*          DELSTR : DIFFERENCE FOR SERIES SYSTEM- CLOSED FORM               *
*          DELTAR : DIFFERENCE FOR SERIES SYSTEM                            *
*          DIFF   : DIFFERENCE (TRUE REL. - ESTIMATED REL.)                 *
*          EPS    : SMALL QUANTITY(CONSTANT)                                *
*          ERROR  : PARAMETER FOR IMSL ROUTINE                              *
*          FAILS  : COUNTS NO. OF REPLICATIONS WITH AT LST. 1 FAILURE       *
*          FI     : NO. OF FAILURES FOR EACH COMPONENT(ALL MISSION TST)     *
*          FLAG   : 1 IF ALL COMP. HAVE SAME NO. OF MISSION TESTS           *
*          INC    : INCREMENT STEP SIZE FOR ROUTINE USMNMX                  *
*          KEY1   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KEY2   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KEY3   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KEY4   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KK     : ARRAY SIZING PARAMETER FOR THE MAX NO OF COMPONENTS     *
*          LOOP   : COUNTS NO. OF REPLICATION PERFORMED                     *
*          MAXALF : MAX NO. OF SIGNIFICANT LEVELS DESIRED(ARRAY SIZING)     *
```

```
*          MAXREP : MAX NO. OF REPLICATIONS                                  *
*          MAXRUN : MAX NO. OF PROGRAM ITERATIONS ALLOWED                    *
*          MSTRQ  : MASTER UNRELIABILITY(USED WITH AI'S TO CALC. QI'S)       *
*          MULT   : MULTIPLIER FOR RANDOM NO. GENERATOR SRND                 *
*          N      : NO. OF MISSION TEST FOR EACH COMPONENT                   *
*          NIMAX  : MAX NO. OF MISSION TESTS                                 *
*          NIMIM  : MIN NO. OF MISSION TESTS                                 *
*          NINDX  : INDEX NO. OF MAX NO. OF MISSION TESTS                    *
*          NIREAL : NO. OF MISSION TESTS TRANSFORMED TO REAL                 *
*          NMAX   : MAX NO. OF MISSION TESTS FOR OUTPUT CONTROL              *
*          NPRNT  : FLAG FOR DETAILED REPORT OUTPUT                          *
*          PRNT   : SAME AS ABOVE(PARAMETER)                                 *
*          QHATI  : UNRELIABILITY ESTIMATES FOR EACH COMPONENT               *
*          QHTMAX : LARGEST QHATI                                            *
*          QHTUPR : UPPER LIMIT ON SYSTEM UNRELIABILITY                      *
*          QI     : INPUT UNRELIABILIY FOR EACH COMPONENT                    *
*          QINDX  : INDEX                                                    *
*          QUANTL : QUANTILE                                                 *
*          REPSHD : REPLICATIONS HEADING FORMAT NUMBER                       *
*          RHTSTR : SERIES SYSTEM RELIABILITY ESTIMATE(CLOSED FORM)          *
*          RS     : TRUE SERIES SYSTEM RELIABILITY                           *
*          RSBRDG : TRUE BRIDGE SYSTEM RELIABILITY                           *
*          RSHAT  : SERIES SYSTEM RELIABILITY ESTIMATE                       *
*          RSHTBR : BRIDGE SYSTEM RELIABILITY ESTIMATE                       *
*          SEED   : PARAMETER                                                *
*          SELCTA : SIGNIFICANCE LEVEL SELECTION                             *
*          SELCTB : SIGNIFICANCE LEVEL SELECTION                             *
*          SORT   : PARAMETER FOR ROUTINE SRND                               *
*          SUMNAI : SUM OF THE PRODUCT OF NI'S AND AI'S                      *
*          TEMP   : TEMPORARY ARRAY                                          *
*          TOTREP : TOTAL NUMBER OF PROGRAM ITERATIONS                       *
*          TRANBR : TEMPORARY ARRAY                                          *
*          TRANSQ : TEMPORARY ARRAY                                          *
*          TRANSR : TEMPORARY ARRAY                                          *
*          TRIALS : BERNOULLI TRIALS ARRAY (2-DIM)                           *
*          TRNSTR : TEMPORARY ARRAY                                          *
*          TRUQNT : TRUE QUANTILE                                            *
*          UNIRV  : UNIFORM RANDOM DEVIATES (2-DIM)                          *
*          ZFAILS : TOTAL NUMBER OF REPLICATIONS WITH ZERO FAILURES          *
*          ZFPREP : NO. OF COMPNTS. WITH ZERO FAILURES PER REPLICATION       *
*                                                                            *
******************************************************************************

      PARAMETER (KK=10,MAXALF=2,NPRNT=0)
      PARAMETER (MAXREP=1000, MAXRUN=2000, EPS=.000001)
      REAL*4 UNIRV(15,1000),TEMP(1000),QI(KK),AI(KK),AHATI(KK)
      REAL*4 QHATI(KK), NMAX, NNMAX, QHTMAX, CHISQR(5,5), ALFA(MAXALF)
      REAL*4 DF(5), AALFA(5),SUMNAI,RSHAT(MAXALF,MAXREP),RS
      REAL*4 KEY1(MAXREP),KEY2(MAXREP),KEY3(MAXREP),TRNSTR(MAXREP)
      REAL*4 DEGFR(MAXREP), QHTUPR(MAXALF,MAXREP),CHISQ(MAXALF,MAXREP)
      REAL*4 QUPA1(MAXREP), QUPA2(MAXREP),RHTSTR(MAXALF,MAXREP)
      REAL*4 DELTAR(MAXALF), TRANSQ(MAXREP),TRANSR(MAXREP),DIFF(MAXREP)
      REAL*4 DELSTR(MAXALF),NIMIN,NIMAX,NIREAL(KK).
      REAL*4 RSHTBR(MAXALF,MAXREP),DELBRG(MAXALF),KEY4(MAXREP)
      REAL*4 TRANBR(MAXREP), RSBRDG ,MSTRQ
      REAL*4 ZFPREP
```

```
      REAL*4 AVGN,SUC,STUD,PTEMP(10),FDEG1,FDEG2,P3,S3,S4

      INTEGER SEED, MULT, SORT, TRIALS(15,1000), BIGF, FI(KK), N(KK)
      INTEGER NINDX, QINDX, ERROR, REPS, SELCTA, SELCTK, TOTREP
      INTEGER C1C15, REPSHD, SELCTB, ALF, FLAG, LOOP,PRNT
      INTEGER QUANTL(MAXALF), TRUQNT(MAXALF),ZFAILS,FAILS,INC
      INTEGER NTEST,FCT,HFI

      CHARACTER*8 LOOPS0(MAXREP)

      DATA SEED/123457/, MULT/1/, INC/1/
      DATA AALFA/.01,.05,.9,.95,.99/, DF/1,5,10,30,40/
      DATA ALFA/.20,.050/
      DATA SORT/0/

      ASSIGN 8 TO C1C15
      ASSIGN 9 TO REPSHD

*     CALL COMPRS
      PRNT = NPRNT

      DO 12 I=1,KK
           AI(I) = 9999.
           N(I) = 99999999
   12 CONTINUE

      READ(03,*)K,MSTRQ

      DO 11 I=1,K
      READ(03,*) AI(I),N(I)
   11 CONTINUE


      IF(K.NE.5) THEN
           WRITE(1,'(''WARNING: BRIDGE STRUCTURE '',
     +''ONLY USES THE FIRST 5 COMPONENTS'')')
      ELSE
      END IF

***INITIALIZE THE QHTUPR ARRAY OF UNRELIABILITY REPLICATIONS,    ***
*  RSHAT ARRAY OF ESTIMATE SYSTEM RELIABILITY REPLICATIONS        *
*  AND RHTSTR ARRAY OF EST. SYST. REL. FOR A SERIES SYST WHEN     *
***ALL THE COMPONENT MISSION TESTS ARE EQUAL IN NUMBER           ***

      DO 172 ALF=1,MAXALF
           DO 173 REPS=1,MAXREP
                QHTUPR(ALF,REPS) = 0.
                RSHAT(ALF,REPS) = 0.
                RHTSTR(ALF,REPS) = 0.
                RSHTBR(ALF,REPS) = 0.
                LOOPS0(REPS)=' ******* '
  173       CONTINUE
  172  CONTINUE

***SET FLAG TO 1 IF ALL COMPONENTS HAVE SAME NO. OF MISSION TESTS****
```

```
      FLAG=1
      DO 50 I=1,K -1
           IF((N(I) - N(I+1)).NE.0) THEN
                FLAG=0
           ELSE
           END IF
  50  CONTINUE
      PRINT *, 'FLAG IS:', FLAG

***MAIN PROGRAM OUTER LOOP START(EVERY LOOP IS ONE REPLICATION)***

      ZFPREP = 0.
      ZFAILS = 0
      FAILS = 0
      TOTREP = 0
      LOOP = 0
  10  IF(LOOP.LT.MAXREP) THEN
           LOOP = LOOP + 1
           IF(TOTREP.LT.MAXRUN) THEN
                TOTREP = TOTREP + 1
      SELCTA = 1
      SELCTB = 2

***FILL ARRAY KEY(REPS) WITH INTEGERS 1 TO K TO BE USED AS OUTPUT***
***OF THE SUBROUTINE SHSORT                                      ***

      DO 95 REPS=1, MAXREP
           KEY1(REPS) = REPS
           KEY2(REPS) = REPS
           KEY3(REPS) = REPS
           KEY4(REPS) = REPS
  95  CONTINUE

***CALCULATE NMAX NOT TO PRINT LONGER THAN THE MAX SAMPLE SIZE***

***CALCULATE THE MAXIMUM NO. OF TRIALS AND ITS INDEX NO.***

      CALL IMAX(N,K,NMAX,NINDX)


***CALCULATE THE QI'S FROM THE GIVEN MASTER Q AND THE AI'S***

      DO 115 I=1, K
           QI(I) = MSTRQ * AI(I)
 115  CONTINUE
C          S3=QI(3)
           S4=QI(1)**.20
      DO 120 I=1,15
           DO 125 J=1,500
                UNIRV(I,J) = 999.
                TRIALS(I,J) = 99999
 125       CONTINUE
 120  CONTINUE

*** DRAW UNIFORM (0,1) RV'S AND CONVERT TO BERNOULLI TRIALS***
      DO 130 I=1, K
```

```
            CALL SRND(SEED, TEMP, N(I), MULT, SORT)
            DO 135 J=1, N(I)
                 UNIRV(I,J) = TEMP(J)
                 IF (UNIRV(I,J).LE. 1 - QI(I)) THEN
                      TRIALS(I,J) = 0
                 ELSE
                      TRIALS(I,J) = 1
                 END IF
 135  CONTINUE
 130  CONTINUE


***CALCULATE THE NO. OF FAILURES FOR EACH COMPONENT***

      DO 150 I=1, K
           FI(I) = 0
 150  CONTINUE
      IONECT = 0

***CALCULATE THE F SUB I'S AND THE GRAND TOTAL NO. OF FAILURES***
      BIGF = 0
      DO 155 I=1, K
           DO 160 J=1, N(I)
                FI(I) = FI(I) + TRIALS(I,J)
 160       CONTINUE
      IF (FI(I)..EQ. 0) THEN
         ZFPREP=ZFPREP+1
      ELSE
      ENDIF
      BIGF = BIGF + FI(I)

      QHATI(I) = REAL(FI(I)) / N(I)
 155  CONTINUE

***Changes for parallel system***


      IF (FI(1) .EQ. 0) THEN
         ZFPREP=ZFPREP - 1
      ENDIF
      BIGF = BIGF - FI(1)
      FI(1) = 0
      DO 161 I=1,N(1)
        HFI=0
        DO 162 J=1,5
           CALL SRND(SEED, PTEMP(J), N(1), MULT, SORT)
           IF (PTEMP(J) .GT. 1-S4) THEN
               HFI = HFI + 1
           ENDIF
 162     CONTINUE
         IF (HFI .EQ. 5) THEN
            FI(1) = FI(1) + 1
         ENDIF
 161  CONTINUE
      BIGF = BIGF + FI(1)
      IF (FI(1) .EQ. 0) THEN
```

```
          ZFPREP = ZFPREP + 1
        ELSE
        ENDIF
C       IF (FI(3) .EQ. 0) THEN
C          ZFPREP=ZFPREP - 1
C       ENDIF
C       BIGF = BIGF - FI(3)
C       FI(3) = 0
C       DO 163 I=1,N(3)
C         HFI=0
C         DO 164 J=1,3
C            CALL SRND(SEED, PTEMP(J), N(3), MULT, SORT)
C            IF (PTEMP(J) .GT. 1-S3) THEN
C                HFI = HFI + 1
C            ENDIF
C164      CONTINUE
C         IF (HFI .GE. 2) THEN
C            FI(3) = FI(3) + 1
C         ENDIF
C163    CONTINUE
C       BIGF = BIGF + FI(3)
C       IF (FI(3) .EQ. 0) THEN
C          ZFPREP = ZFPREP + 1
C       ELSE
C       ENDIF
        DO 19 I=1,K
         QI(I) = MSTRQ * AI(I)
        QHATI(I) = REAL(FI(I)) / N(I)

   19   CONTINUE
C       QI(4) = QI(4)**2
C       P3 = 1.-QI(3)
C       QI(3) = 1.-((3.*P3**2*QI(3))+(P3**3))
***COUNTS NUMBER OF COMPONENTS THAT HAVE FAILED***

        DO 156 I=1,K
           IF (FI(I) .NE. 0) IONECT=IONECT+1
  156   CONTINUE

***CASE WHERE NO COMPONENTS HAVE ANY FAILURES***

        IF(BIGF.EQ.0) THEN
             LOOPS0(LOOP)=' *ZERO* '
             ZFAILS = ZFAILS + 1
             AVGN=0.0
             DO 200 I=1,K
                  AVGN=AVGN+REAL(N(I))
  200        CONTINUE
             AVGN=AVGN/REAL(K)
             DO 205 ALF=1, MAXALF
                  RSHAT(ALF,LOOP)= ALFA(ALF)**(1./AVGN)
             IF(FLAG.EQ.1) THEN
                  RHTSTR(ALF,LOOP)=ALFA(ALF)**(1./N(1))
             ELSE
             END IF
*            PRINT *,LOOP',LOOP,'RSHAT',RSHAT(ALF,LOOP)
```

```
 205        CONTINUE
                 DEGFR(LOOP) = 2.
                 GO TO 10
           ELSE
                FAILS = FAILS + 1
           END IF

***COUNTS NUMBER OF COMPONENTS THAT FAIL RECORDS NO. COMPT TESTS***
           FCT=0
           DO 202 I=1,K
                IF (FI(I) .NE. 0) THEN
                   FCT=FCT+1
                   NTEST=N(I)
            ENDIF
 202  CONTINUE

***FIND THE MAX OF THE INDIVIDUAL COMPONENT UNRELIABILITIES***

           CALL RMAX(QHATI, K, QHTMAX, QINDX)
           IF (LOOP .EQ. 1) THEN
           ENDIF

***CALCULATE THE AHAT SUB I'S (WEIGHT ESTIMATES)***
***IF COMPONENT HAS NO FAILURES AHAT SUB I IS ZERO***

           SUMNAI = 0.
           DO 165 I=1, K
                AHATI(I) = QHATI(I) / QHTMAX
                SUMNAI = SUMNAI + N(I) * AHATI(I)
 165  CONTINUE

***1 COMPONENT FAILURE SERIES SYSTEM***

           IF (FCT .EQ. 1) THEN
              LOOPS0(LOOP)=' *ONECF*  '
              DO 305 ALF=1,MAXALF
                 SUC=REAL(NTEST-BIGF)
                 FDEG1=2.*(REAL(BIGF)+1.)
                 FDEG2=2.*SUC
                 STUD=FIN(1.-ALFA(ALF),FDEG1,FDEG2)
                 RSHAT(ALF,LOOP)=SUC/(SUC+(REAL(BIGF)+1.)*STUD)
*                PRINT *,'SUC=',SUC,'FAIL=',BIGF,'NTEST=',NTEST
*                PRINT *,'FIN=',STUD
*                PRINT *,'ALFA=',ALFA(ALF),'RSHAT=',RSHAT(ALF,LOOP)
                 IF (FLAG .EQ.1) THEN
                      RHTSTR(ALF,LOOP)=RSHAT(ALF,LOOP)
                 ELSE
                 ENDIF
 305     CONTINUE
           ENDIF

***CALCULATE 1 REPLICATION OF UPPR ALFA C.L. ON SYSTEM RELIABILITY***

           DEGFR(LOOP) = 2 * (1 + BIGF)

           DO 170 ALF=1, MAXALF
```

```
            CALL MDCHI(1 - ALFA(ALF),DEGFR(LOOP),CHISQ(ALF,LOOP), ERROR)
            QHTUPR(ALF,LOOP) = CHISQ(ALF,LOOP) / (2 * SUMNAI)
            IF(FLAG.EQ.1) THEN
                 RHTSTR(ALF,LOOP) = 1 -(CHISQ(ALF,LOOP) / REAL(2*N(1)))
            ELSE
            END IF

***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR COMPNTS. IN SERIES***

            IF (FCT .NE. 1) THEN
            CALL RHTSRS(QHTUPR(ALF,LOOP), AHATI,K, RSHAT(ALF,LOOP))
            ENDIF

***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR BRIDGE STRUCTURE***

            IF (IONECT .NE. 1) THEN
               CALL RHTBRG(QHTUPR(ALF,LOOP),AHATI,K,RSHTBR(ALF,LOOP))
            ENDIF
 170  CONTINUE

***EXACTLY 1 COMPONENT FAILS AND REDUNDANT COMPONENT***

      IF ((IONECT .EQ. 1) .AND. (K .EQ.5)) THEN
           DO 207 I=1, K
                NIREAL(I) = REAL(N(I))
 207       CONTINUE
         CALL USMNMX(NIREAL,K,INC,NIMIN,NIMAX)
         DO 206 ALF=1,MAXALF
            RSHTBR(ALF,LOOP)=ALFA(ALF)**(1./NIMIN)
 206     CONTINUE
      ENDIF

***THIS ELSE AND ENDIF ARE FOR THE TEST AGAINST MAXRUN****

      ELSE
           WRITE(1,'('' '',/''PROGRAM EXCEEDED THE MAX NO. OF RUNS'',
     +'' ALLOWED OF:'',I6)') TOTREP
      GOTO 9999

      END IF
      GOTO 10
      END IF

C     WRITE(2,'(''UNSORTED RSHAT 1  IS:'',/10(F8.5))')
C    +(RSHAT(1,LOOP), LOOP=1, MAXREP)
C     WRITE(2,'(''UNSORTED RSHAT 2  IS:'',/10(F8.5))')
C    +(RSHAT(2,LOOP), LOOP=1, MAXREP)
C     IF(FLAG.EQ.1) THEN
C          WRITE(2,'(''UNSORTED RHTSTR 1  IS:'',/10(F8.5))')
C    +(RHTSTR(1,LOOP), LOOP=1, MAXREP)
C          WRITE(2,'(''UNSORTED RHTSTR 2  IS:'',/10(F8.5))')
C    +(RHTSTR(2,LOOP), LOOP=1, MAXREP)
C     ELSE
C     END IF
C     IF(K.EQ.5) THEN
C          WRITE(2,'(''UNSORTED RSHTBR 1  IS:'',/10(F8.5))')
```

```
C     +(RSHTBR(1,LOOP), LOOP=1, MAXREP)
C           WRITE(2,'(''UNSORTED RSHTBR 2  IS:'',/10(F8.5))')
C     +(RSHTBR(2,LOOP), LOOP=1, MAXREP)
C      ELSE
C      END IF
C      WRITE (2,'(''ZERO AND ONE FAILURE REPS:'',/10(A8))')
C     +  (LOOPS0(LOOP),LOOP=1,MAXREP)

***SORT THE ARRAYS OF SYSTEM UNRELIABILITIES(1 FOR EACH CONF. LEVEL)***

      DO 700 ALF=1, MAXALF
           DO 800 REPS=1, MAXREP
                TRANSQ(REPS) = QHTUPR(ALF,REPS)
                TRANSR(REPS) = RSHAT(ALF,REPS)
                TRNSTR(REPS) = RHTSTR(ALF,REPS)
                TRANBR(REPS) = RSHTBR(ALF,REPS)
 800        CONTINUE
           CALL SHSORT(TRANSQ,KEY1,MAXREP)
           CALL SHSORT(TRANSR,KEY2,MAXREP)
           CALL SHSORT(TRNSTR,KEY3,MAXREP)
           CALL SHSORT(TRANBR,KEY4,MAXREP)
           DO 900 REPS=1, MAXREP
                QHTUPR(ALF,REPS) = TRANSQ(REPS)
                RSHAT(ALF,REPS) = TRANSR(REPS)
                RHTSTR(ALF,REPS) = TRNSTR(REPS)
                RSHTBR(ALF,REPS) = TRANBR(REPS)
 900        CONTINUE
 700  CONTINUE

***PRINT OUTPUT REPORT HEADINGS***

      WRITE(1,6666)
      WRITE(1,6667) MAXREP
      WRITE(1,6668) K
      WRITE(1,6669)
      IF(K.EQ.5) THEN
           WRITE(1,6699)
      ELSE
      END IF
      WRITE(1,6670) MSTRQ
      WRITE(1,6671)
      WRITE(1,C1C15)
      WRITE(1,3334) AI
      WRITE(1,0007)
      WRITE(1,C1C15)
      WRITE(1,3334) QI
      WRITE(1,0005)
      WRITE(1,C1C15)
      WRITE(1,3335) N
      WRITE(1,6674)

***COMPUTE THE VALUE RS OF THE TRUE SYSTEM REL. FNCTN.(SERIES SYSTEM)***
***  AND FOR THE 5-COMPONENT BRIDGE STRUCTURE***
```

```
      CALL RSRS(QI,K,RS)
      WRITE(1,'('' '',////''THE TRUE SERIES SYSTEM '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RS
      CALL RBRIDG(QI,K,RSBRDG)
      IF(K.EQ.5) THEN
      WRITE(1,'('' '',////''THE TRUE BRIDGE STRUCTURE '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RSBRDG
      ELSE
      END IF
      WRITE(1,6675)

***COMPUTE THE DIFFERENCE 'DELTAR' BTWN. RS AND RSHAT OF THE THEO***
***RETICAL QUANTILE GIVEN BY ALFA(MUST USE SORTED RSHAT ARRAY)***

      IF(FLAG.EQ.1) THEN
      WRITE(1,5755)
      ELSE
      END IF
      DO 450 ALF=1, MAXALF
           QUANTL(ALF) = MAXREP * (1 - ALFA(ALF))
           DELTAR(ALF) = RS - RSHAT(ALF,QUANTL(ALF))
           DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
           IF(FLAG.EQ.1) THEN
                DELSTR(ALF) = RS - RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5656) RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5657) DELSTR(ALF)
           ELSE
           END IF
           IF(K.EQ.5) THEN
                DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5666) RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5667) DELBRG(ALF)
           ELSE
           END IF
           WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
           WRITE(1,5556) RSHAT(ALF,QUANTL(ALF))
           WRITE(1,5557) DELTAR(ALF)
 450  CONTINUE
      PRINT *, 'QUANTL(1) IS:', QUANTL(1)
      PRINT *, 'QUANTL(2) IS:', QUANTL(2)

***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***                ********* RSHAT ********                    ***

      WRITE(1,6676)
      DO 400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 500 REPS=1, MAXREP
                DIFF(REPS) = RS - RSHAT(ALF,REPS)
 500       CONTINUE
           DO 600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
```

```
     +              F8.4)')
     +              (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                    GO TO 620
               ELSEIF(DIFF(REPS).LT.0.) THEN
                    TRUQNT(ALF) = REPS
                    GO TO 610
               ELSE
               END IF
600            CONTINUE
610            IF(TRUQNT(ALF).EQ.0.) THEN
                    WRITE(1,4443) ALFA(ALF)
                    WRITE(1,'('' '',/''THE SMALLEST'',
     +              '' DIFFERENCE BETWEEN RS AND RSHAT IS:'',F10.5)') DIFF(
     +              MAXREP)
               ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                    WRITE(1,4442) ALFA(ALF)
                    WRITE(1,'('' '',/''ALL RSHAT'',
     +                '' ARE GREATER THAN RS'')')
               ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +         THEN
                    WRITE(1,4444) ALFA(ALF),
     +              (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                    WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF))
                    WRITE(1,4446)
               ELSE
                    WRITE(1,4444) ALFA(ALF),
     +              ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                    WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF)-1)
                    WRITE(1,4447)
620            END IF
400       CONTINUE


***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***          ******** RSHTBR (BRIDGE) ********                  ***

          IF(K.EQ.5) THEN
          DO 401 ALF=1,MAXALF
          TRUQNT(ALF) = 0
               DO 501 REPS=1, MAXREP
                    DIFF(REPS) = RSBRDG - RSHTBR(ALF,REPS)
501            CONTINUE
               DO 601 REPS=1, MAXREP
                    IF(ABS(DIFF(REPS)).LE.EPS) THEN
                         TRUQNT(ALF) = REPS
                         WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +                   F8.4)')
     +                   (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                         GO TO 621
                    ELSEIF(DIFF(REPS).LT.0.) THEN
                         TRUQNT(ALF) = REPS
                         GO TO 611
                    ELSE
                    END IF
601            CONTINUE
611            IF(TRUQNT(ALF).EQ.0.) THEN
```

```
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST''
     +          '' DIFFERENCE BETWEEN RSBRDG AND RSHTBR IS:'',
     +          F10.5)') DIFF(MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RSHTBR''
     +           '' ARE GREATER THAN RSBRDG'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 621       END IF
 401  CONTINUE
      ELSE
      END IF

                :
***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***                 ******** RHTSTR ********                   ***

      IF(FLAG.EQ.1) THEN
      DO 4400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 5500 REPS=1, MAXREP
                DIFF(REPS) = RS - RHTSTR(ALF,REPS)
 5500       CONTINUE
           DO 6600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                     GO TO 6620
                ELSEIF(DIFF(REPS).LT.0.) THEN
                     TRUQNT(ALF) = REPS
                     GO TO 6610
                ELSE
                END IF
 6600       CONTINUE
 6610       IF(TRUQNT(ALF).EQ.0.) THEN
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST''
     +          '' DIFFERENCE BETWEEN RS AND RHTSTR IS:'',
     +          F9.5)') DIFF(MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RHTSTR''
     +          '' ARE GREATER THAN RS'')')
```

```
            ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +      THEN
                 WRITE(1,4444) ALFA(ALF),
     +           (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                 WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF))
                 WRITE(1,4446)
            ELSE
                 WRITE(1,4444) ALFA(ALF),
     +           ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                 WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF)-1)
                 WRITE(1,4447)
 6620       END IF
 4400  CONTINUE
       ELSE
       END IF

***PRINT THE ARRAYS PERTINENT TO THE OUPUT OF EACH REPLICATION***

       IF(PRNT.EQ.1) THEN
       I = 1
  185  WRITE(1,REPSHD) ALFA(SELCTA), ALFA(SELCTA),
      +ALFA(SELCTB),ALFA(SELCTB),ALFA(SELCTA),ALFA(SELCTA),ALFA(SELCTB),
      +ALFA(SELCTB)
  175  IF(I.GE.(MAXREP + 1)) THEN
            GOTO 180
       ELSE
            IF( (I.EQ.71).OR.(I.EQ.211).OR.(I.EQ.351).OR.(I.EQ.491).OR.
     +      (I.EQ.631).OR.(I.EQ.771).OR.(I.EQ.911).OR.(I.EQ.1051) ) THEN
                 I = I + 70
                 WRITE(1,'(''+'')')
                 GOTO 185
            ELSE

            WRITE(1,3336) I, INT(DEGFR(I)), CHISQ(1,I), QHTUPR(1,I),
     +      CHISQ(2,I), QHTUPR(2,I)
            END IF
            IF(I + 70.LE.MAXREP) THEN
                 WRITE(1,3337) I+70,INT(DEGFR(I+70)),CHISQ(1,I+70),
     +           QHTUPR(1,I+70),CHISQ(2,I+70),QHTUPR(2,I+70)
            ELSE
            END IF
       I = I + 1
       GOTO 175
  180  END IF
       ELSE
       ENDIF
 9999  WRITE(1,'(''THE TOTAL NO OF REPS WAS:'',I8)') TOTREP
       WRITE(1,'(''THE TOTAL NO OF EFFECTIVE REPS WAS:'',I8)') LOOP
       WRITE(1,'(''THE TOTAL NO OF NO FAILURE RUNS WAS:'',I8)') ZFAILS
       WRITE(1,'(''AVERAGE  NO. OF COMPONENTS PER REPLICATION WITH '',
      +''NO FAILURES:'',F5.2)') ZFPREP / MAXREP
       WRITE(1,'(''THE TOTAL NO OF RUNS WITH FAILURES WAS:'',I8)') FAILS
 0008  FORMAT (/ 3X,'C 1',5X,'C 2',
      +5X,'C 3',5X,'C 4',5X,'C 5',5X,'C 6',5X,'C 7',5X,
      +'C 8',5X,'C 9',5X,'C 10',4X,'C 11',4X,
      +'C 12',4X,'C 13',4X,'C 14',4X,'C 15')
```

```
0009 FORMAT(/1X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
    +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')',
    +2X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
    +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')'/)
0001 FORMAT (///'UNIFORM RANDOM DEVIATES ARE:')
0002 FORMAT (///'BERNOULLI TRIALS ARE:')
0003 FORMAT (///'TOTAL NO. OF FAILURES FOR EACH COMPONENT:')
0004 FORMAT (///'ESTIMATED UNRELIABILITY FOR EACH COMPONENT:')
0005 FORMAT (///'TOTAL NUMBER OF MISSION TESTS:')
0006 FORMAT (///'ESTIMATED WEIGHTS FOR EACH COMPONENT:')
0007 FORMAT (///'Q I FOR EACH COMPONENT:')
1111 FORMAT (15F8.5)

2222 FORMAT (/1X,15(I4,4X))
3333 FORMAT (/1X,15(I4,4X))
3334 FORMAT (/15F8.5)
3335 FORMAT (/1X,15(I4,4X))
3336 FORMAT (T3,I4,T9,I3,T13,F11.5,T27,F8.5,T39,F11.5,T53,F8.5)
3337 FORMAT ('+',T67,I4,T73,I3,T77,F11.5,T91,F8.5,T103,F11.5,T117,F8.5)
4442 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
    +'LIMIT IS:',T50,' 00.000 ')
4443 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
    +'LIMIT IS:',T50,'100.0000')
4444 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
    +'LIMIT IS:',T50,F8.4)
4445 FORMAT (' ',/'THE RSHAT VALUE CLOSEST TO RS IS: ',T51,F8.5)
4446 FORMAT (' ',/'(FIRST NEGATIVE DIFFERENCE)')
4447 FORMAT (' ',/'(ELEMENT PRECEEDING FIRST NEGATIVE DIFFERENCE)')
4448 FORMAT (' ',/'THE RHTSTR VALUE CLOSEST TO RS IS: ',T51,F8.5)
4449 FORMAT (' ',/'THE RSHTBR VALUE CLOSEST TO RSBRDG IS: ',T51,F8.5)
5555 FORMAT (' ',///'THE ',I4,'(1-',F4.3,') QUANTILE IS:',T49,F8.3)
5556 FORMAT (' ',/'THE VALUE OF RSHAT FOR THAT QUANTILE IS:',T51,F8.5)
5557 FORMAT (' ',/'THE DIFFERENCE(RS - RSHAT) IS:',T51,F8.5)
5656 FORMAT (' ',/'THE VALUE OF RHTSTR FOR THAT QUANTILE IS:',T51,F8.5)
5666 FORMAT (' ',/'THE VALUE OF RSHTBR FOR THAT QUANTILE IS:',T51,F8.5)
5657 FORMAT (' ',/'THE DIFFERENCE(RS - RHTSTR) IS:',T51,F8.5)
5667 FORMAT (' ',/'THE DIFFERENCE(RS - RSHTBR) IS:',T51,F8.5)
5755 FORMAT (' ',///'SINCE THE NO. OF MISSION TESTS IS THE SAME FOR',
    +' ALL COMPONENTS THE CLOSED FORM SERIES SYSTEM RELIABILITY ',
    +'''RHTSTR'' IS COMPUTED')
6666 FORMAT ('+','**************************************************',
    +'********** RUN INPUT SETTINGS **********************************',
    +'**********')
6667 FORMAT (' ',//'NUMBER OF REPLICATIONS:',T50,I4)
6668 FORMAT (' ',//'NUMBER OF COMPONENTS:',T50,I4)
6669 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'SERIES')
6699 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'BRIDGE')
6670 FORMAT (' ',//'MASTER UNRELIABILITY USED:',T50,F8.5)
6671 FORMAT (' ',//'INPUT WEIGHTS(A SUB I''S):')
6674 FORMAT ('+',///'**************************************************',
    +'**R U N  R E S U L T S**********************************************',
    +'**********')
6675 FORMAT ('+',///'**************************************************',
    +' ESTIMATE ERRORS ***********************************************',
    +'**********')
6676 FORMAT ('+',///'**************************************************',
```

```
     +' TRUE CONFIDENCE LIMITS **********************************************',
     +'***************')
      END
```

APPENDIX G. FORTRAN CODE FOR ALTERNATE PROCEDURE A FOR ESTIMATING THE LOWER CONFIDENCE LIMIT FOR SYSTEM RELIABILITY

```
      PROGRAM ZFYSCN
*****************************************************************************
*                                                                           *
*      TITLE: BINOMIAL INTERVAL ESTIMATION PROCEDURE                        *
*             ZERO FAILURES ALLOWED; NO SCALING                             *
*     AUTHOR: E. F. BELLINI, LT, USN                                        *
*       DATE: NOV 89                                                        *
*                                                                           *
*     THIS PROGRAM COMPUTES THE TRUE CONFIDENCE LEVEL FOR THE ESTIMATE      *
*     RELIABILITY OF A SERIES AND BRIDGE SYSTEM GIVEN THE RELIABILITY       *
*     OF THEIR COMPONENTS                                                   *
*                                                                           *
*     IN ITS PRESENT CONFIGURATION THIS PROGRAM IS SET UP TO RUN 12          *
*     TIMES EACH TIME PRODUCING 1000 REPLICATIONS USING A DIFFERENT         *
*     SET OF INPUT DATA.  RUN THE PROGRAM FROM CMS BY TYPING 'B1 EXEC'.     *
*     THE REXX EXEC PROGRAM                                                 *
*     'B1' CALLS THE INPUT FILES TO BE READ AND NAMES THE 12 OUTPUT         *
*     FILES RESULTING FROM THE 12 CONSECUTIVE RUNS.  BY EDITING THE         *
*     INDEX COUNTERS I, J, K OF THE 'B1' EXEC ONE CAN RUN ANY USER-         *
*     SPECIFIC RUN FROM JUST ONE RUN TO ALL 12.                             *
*                                                                           *
*     VARIABLES USED                                                        *
*                                                                           *
*          AHATI  : WEIGHT ESTIMATES FOR EACH COMPONENT                     *
*          AI     : INPUT WEIGHTS FOR EACH COMPONENT                        *
*          ALFA   : LEVELS OF SIGNIFICANCE                                  *
*          BIGF   : TOTAL NO. OF FAILURES FOR EACH REPLICATION              *
*          CHISQ  : CHI-SQUARE RANDOM VARIABLE VALUE                        *
*          C1C15  : FORMAT LABEL                                            *
*          DEGFR  : DEGREES OF FREEDOM                                      *
*          DELBRG : DIFFERENCE FOR BRIDGE SYSTEM                            *
*          DELSTR : DIFFERENCE FOR SERIES SYSTEM- CLOSED FORM               *
*          DELTAR : DIFFERENCE FOR SERIES SYSTEM                            *
*          DIFF   : DIFFERENCE (TRUE REL. - ESTIMATED REL.)                 *
*          EPS    : SMALL QUANTITY(CONSTANT)                                *
*          ERROR  : PARAMETER FOR IMSL ROUTINE                              *
*          FAILS  : COUNTS NO. OF REPLICATIONS WITH AT LST. 1 FAILURE       *
*          FI     : NO. OF FAILURES FOR EACH COMPONENT(ALL MISSION TST)     *
*          FLAG   : 1 IF ALL COMP. HAVE SAME NO. OF MISSION TESTS           *
*          INC    : INCREMENT STEP SIZE FOR ROUTINE USMNMX                  *
*          KEY1   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KEY2   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KEY3   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KEY4   : ARRAY OF INDECES FOR ROUTINE SHSORT                     *
*          KK     : ARRAY SIZING PARAMETER FOR THE MAX NO OF COMPONENTS     *
*          LOOP   : COUNTS NO. OF REPLICATION PERFORMED                     *
*          MAXALF : MAX NO. OF SIGNIFICANT LEVELS DESIRED(ARRAY SIZING)     *
*          MAXREP : MAX NO. OF REPLICATIONS                                 *
```

```
*          MAXRUN : MAX NO. OF PROGRAM ITERATIONS ALLOWED                    *
*          MSTRQ  : MASTER UNRELIABILITY(USED WITH AI'S TO CALC. QI'S)       *
*          MULT   : MULTIPLIER FOR RANDOM NO. GENERATOR SRND                 *
*          N      : NO. OF MISSION TEST FOR EACH COMPONENT                   *
*          NIMAX  : MAX NO. OF MISSION TESTS                                 *
*          NIMIM  : MIN NO. OF MISSION TESTS                                 *
*          NINDX  : INDEX NO. OF MAX NO. OF MISSION TESTS                    *
*          NIREAL : NO. OF MISSION TESTS TRANSFORMED TO REAL                 *
*          NMAX   : MAX NO. OF MISSION TESTS FOR OUTPUT CONTROL              *
*          NPRNT  : FLAG FOR DETAILED REPORT OUTPUT                          *
*          PRNT   : SAME AS ABOVE(PARAMETER)                                 *
*          QHATI  : UNRELIABILITY ESTIMATES FOR EACH COMPONENT               *
*          QHTMAX : LARGEST QHATI                                            *
*          QHTUPR : UPPER LIMIT ON SYSTEM UNRELIABILITY                      *
*          QI     : INPUT UNRELIABILIY FOR EACH COMPONENT                    *
*          QINDX  : INDEX                                                    *
*          QUANTL : QUANTILE                                                 *
*          REPSHD : REPLICATIONS HEADING FORMAT NUMBER                       *
*          RHTSTR : SERIES SYSTEM RELIABILITY ESTIMATE(CLOSED FORM)          *
*          RS     : TRUE SERIES SYSTEM RELIABILITY                           *
*          RSBRDG : TRUE BRIDGE SYSTEM RELIABILITY                           *
*          RSHAT  : SERIES SYSTEM RELIABILITY ESTIMATE                       *
*          RSHTBR : BRIDGE SYSTEM RELIABILITY ESTIMATE                       *
*          SEED   : PARAMETER                                                *
*          SELCTA : SIGNIFICANCE LEVEL SELECTION                             *
*          SELCTB : SIGNIFICANCE LEVEL SELECTION                             *
*          SORT   : PARAMETER FOR ROUTINE SRND                               *
*          SUMNAI : SUM OF THE PRODUCT OF NI'S AND AI'S                      *
*          TEMP   : TEMPORARY ARRAY                                          *
*          TOTREP : TOTAL NUMBER OF PROGRAM ITERATIONS                       *
*          TRANBR : TEMPORARY ARRAY                                          *
*          TRANSQ : TEMPORARY ARRAY                                          *
*          TRANSR : TEMPORARY ARRAY                                          *
*          TRIALS : BERNOULLI TRIALS ARRAY (2-DIM)                           *
*          TRNSTR : TEMPORARY ARRAY                                          *
*          TRUQNT : TRUE QUANTILE                                            *
*          UNIRV  : UNIFORM RANDOM DEVIATES (2-DIM)                          *
*          ZFAILS : TOTAL NUMBER OF REPLICATIONS WITH ZERO FAILURES          *
*          ZFPREP : NO. OF COMPNTS. WITH ZERO FAILURES PER REPLICATION       *
*                                                                            *
******************************************************************************

      PARAMETER (KK=10,MAXALF=2,NPRNT=0)
      PARAMETER (MAXREP=1000, MAXRUN=2000, EPS=.000001)
      REAL*4 UNIRV(15,1000),TEMP(1000),QI(KK),AI(KK),AHATI(KK)
      REAL*4 QHATI(KK), NMAX, NNMAX, QHTMAX, CHISQR(5,5), ALFA(MAXALF)
      REAL*4 DF(5),AALFA(5),SUMNAI,RSHAT(MAXALF,MAXREP),RS
      REAL*4 KEY1(MAXREP),KEY2(MAXREP),KEY3(MAXREP),TRNSTR(MAXREP)
      REAL*4 DEGFR(MAXREP), QHTUPR(MAXALF,MAXREP),CHISQ(MAXALF,MAXREP)
      REAL*4 QUPA1(MAXREP), QUPA2(MAXREP),RHTSTR(MAXALF,MAXREP)
      REAL*4 DELTAR(MAXALF), TRANSQ(MAXREP),TRANSR(MAXREP),DIFF(MAXREP)
      REAL*4 DELSTR(MAXALF),NIMIN,NIMAX,NIREAL(KK)
      REAL*4 RSHTBR(MAXALF,MAXREP),DELBRG(MAXALF),KEY4(MAXREP)
      REAL*4 TRANBR(MAXREP), RSBRDG ,MSTRQ
      REAL*4 ZFPREP
```

```
      INTEGER SEED, MULT, SORT, TRIALS(15,1000), BIGF, FI(KK), N(KK)
      INTEGER NINDX, QINDX, ERROR, REPS, SELCTA, SELCTK, TOTREP
      INTEGER C1C15, REPSHD, SELCTB, ALF, FLAG, LOOP,PRNT
      INTEGER QUANTL(MAXALF), TRUQNT(MAXALF),ZFAILS,FAILS,INC

      DATA SEED/123457/, MULT/1/, INC/1/
      DATA AALFA/.01,.05,.9,.95,.99/, DF/1,5,10,30,40/
      DATA ALFA/.20,.050/
      DATA SORT/0/

      ASSIGN 8 TO C1C15
      ASSIGN 9 TO REPSHD

*     CALL COMPRS
      PRNT = NPRNT

      DO 12 I=1,KK
           AI(I) = 9999.
           N(I) = 99999999
   12 CONTINUE

      READ(03,*)K,MSTRQ

      DO 11 I=1,K
      READ(03,*) AI(I),N(I)
   11 CONTINUE


      IF(K.NE.5) THEN
           WRITE(1,'(''WARNING: BRIDGE STRUCTURE '',
     +''ONLY USES THE FIRST 5 COMPONENTS'')')
      ELSE
      END IF

***// INITIALIZE THE QHTUPR ARRAY OF UNRELIABILITY REPLICATIONS,   //***
*     RSHAT ARRAY OF ESTIMATE SYSTEM RELIABILITY REPLICATIONS         *
*     AND RHTSTR ARRAY OF EST. SYST. REL. FOR A SERIES SYST WHEN      *
***// ALL THE COMPONENT MISSION TESTS ARE EQUAL IN NUMBER           //***

      DO 172 ALF=1,MAXALF
           DO 173 REPS=1,MAXREP
                QHTUPR(ALF,REPS) = 0.
                RSHAT(ALF,REPS) = 0.
                RHTSTR(ALF,REPS) = 0.
                RSHTBR(ALF,REPS) = 0.
  173       CONTINUE
  172 CONTINUE

***// SET FLAG TO 1 IF ALL COMPONENTS HAVE SAME NO. OF MISSION TESTS****

      FLAG=1
      DO 50 I=1,K -1
           IF((N(I) - N(I+1)).NE.0) THEN
                FLAG=0
           ELSE
           END IF
```

```
 50   CONTINUE
      PRINT *, 'FLAG IS:', FLAG
***// MAIN PROGRAM OUTER LOOP START(EVERY LOOP IS ONE REPLICATION)//***

      ZFPREP = 0.
      ZFAILS = 0
      FAILS = 0
      TOTREP = 0
      LOOP = 0
 10   IF(LOOP.LT.MAXREP) THEN
           LOOP = LOOP + 1
           IF(TOTREP.LT.MAXRUN) THEN
                TOTREP = TOTREP + 1
      SELCTA = 1
      SELCTB = 2
***// FILL ARRAY KEY(REPS) WITH INTEGERS 1 TO K TO BE USED AS OUTPUT
***// OF THE SUBROUTINE SHSORT
      DO 95 REPS=1, MAXREP
           KEY1(REPS) = REPS
           KEY2(REPS) = REPS
           KEY3(REPS) = REPS
           KEY4(REPS) = REPS
 95   CONTINUE

***// CALCULATE NMAX NOT TO PRINT LONGER THAN THE MAX SAMPLE SIZE

***// CALCULATE THE MAXIMUM NO. OF TRIALS AND ITS INDEX NO. //***

      CALL IMAX(N,K,NMAX,NINDX)


***// CALCULATE THE QI'S FROM THE GIVEN MASTER Q AND THE AI'S

      DO 115 I=1, K
           QI(I) = MSTRQ * AI(I)
 115  CONTINUE

      DO 120 I=1,15
           DO 125 J=1,500
                UNIRV(I,J) = 999.
                TRIALS(I,J) = 99999
 125       CONTINUE
 120  CONTINUE

***// DRAW UNIFORM (0,1) RV'S AND CONVERT TO BERNOULLI TRIALS //***

      DO 130 I=1, K
           CALL SRND(SEED, TEMP, N(I), MULT, SORT)
           DO 135 J=1, N(I)
                UNIRV(I,J) = TEMP(J)
                IF (UNIRV(I,J).LE. 1 - QI(I)) THEN
                     TRIALS(I,J) = 0
                ELSE
                     TRIALS(I,J) = 1
                END IF
 135  CONTINUE
```

```
130  CONTINUE


***// CALCULATE THE NO. OF FAILURES FOR EACH COMPONENT  //***

     DO 150 I=1, K
          FI(I) = 0
150  CONTINUE

***// CALCULATE THE F SUB I'S AND THE GRAND TOTAL NO. OF FAILURES
     BIGF = 0
     DO 155 I=1, K
          DO 160 J=1, N(I)
               FI(I) = FI(I) + TRIALS(I,J)
160       CONTINUE
          IF(FI(I).EQ.0) THEN
               ZFPREP = ZFPREP + 1
          ELSE
          END IF
***// CALCULATE THE QHAT SUB I'S: F SUB I'S DIVIDED BY N SUB I'S
               QHATI(I) = REAL(FI(I)) / N(I)
          BIGF = BIGF + FI(I)
155  CONTINUE

***// CASE WHERE NO COMPONENTS HAVE ANY FAILURES                    //***

     IF(BIGF.EQ.0) THEN
          ZFAILS = ZFAILS + 1
          DO 200 I=1, K
               NIREAL(I) = REAL(N(I))
200       CONTINUE
          CALL USMNMX(NIREAL,K,INC,NIMIN,NIMAX)
          DO 205 ALF=1, MAXALF
               CALL MDCHI(1 - ALFA(ALF),2.,CHISQ(ALF,LOOP),ERROR)
               RSHAT(ALF,LOOP)= 1 - (CHISQ(ALF,LOOP) / REAL(2 * NIMIN))
          IF(FLAG.EQ.1) THEN
               RHTSTR(ALF,LOOP)=1-(CHISQ(ALF,LOOP) / REAL(2 * N(1)))
          ELSE
          END IF
205       CONTINUE
     IF(PRNT.EQ.1) THEN
          WRITE(1,0007)
          WRITE(1,C1C15)
          WRITE(1,3334) QI
          WRITE(1,0001)
          WRITE(1,C1C15)
          DO 141 J=1,NMAX
               WRITE(1,1111) (UNIRV(I,J), I=1, K)
141       CONTINUE
          WRITE(1,0002)
          WRITE(1,C1C15)
          DO 146 J=1,NMAX
               WRITE(1,2222) (TRIALS(I,J), I=1, K)
146       CONTINUE
          WRITE(1,0003)
          WRITE(1,C1C15)
```

```
            WRITE(1,3333) FI
            WRITE(1,0005)
            WRITE(1,C1C15)
            WRITE(1,3335) N
            WRITE(1,0004)
            WRITE(1,C1C15)
            WRITE(1,3334) QHATI
      WRITE(1,'(/''THE MAXIMUM Q HAT SUB I IS:'', T40, F8.5)') QHTMAX
      WRITE(1,'(/''THE MAXI Q HAT SUB I IS ELMNT NO.:'',T40,I5)') QINDX
      WRITE(1,'(/''THE GRAND TOTAL NO. OF FAILURES IS:'',T40, I5)') BIGF
      ELSE
      ENDIF
                  DEGFR(LOOP) = 2.
                  GO TO 10
      ELSE
           FAILS = FAILS + 1
      END IF

***// FIND THE MAX OF THE INDIVIDUAL COMPONENT UNRELIABILITIES
      CALL RMAX(QHATI, K, QHTMAX, QINDX)

***// PRINT THE RESULT OF THE MAIN OPERATING ELEMENTS OF THE PROGRAM

      IF(PRNT.EQ.1) THEN
            WRITE(1,0007)
            WRITE(1,C1C15)
            WRITE(1,3334) QI
            WRITE(1,0001)
            WRITE(1,C1C15)
            DO 140 J=1,NMAX
                 WRITE(1,1111) (UNIRV(I,J), I=1, K)
 140        CONTINUE
            WRITE(1,0002)
            WRITE(1,C1C15)
            DO 145 J=1,NMAX
                 WRITE(1,2222) (TRIALS(I,J), I=1, K)
 145        CONTINUE
            WRITE(1,0003)
            WRITE(1,C1C15)
            WRITE(1,3333) FI
            WRITE(1,0005)
            WRITE(1,C1C15)
            WRITE(1,3335) N
            WRITE(1,0004)
            WRITE(1,C1C15)
            WRITE(1,3334) QHATI
      WRITE(1,'(/''THE MAXIMUM Q HAT SUB I IS:'', T40, F8.5)') QHTMAX
      WRITE(1,'(/''THE MAXI Q HAT SUB I IS ELMNT NO.:'',T40,I5)') QINDX
      WRITE(1,'(/''THE GRAND TOTAL NO. OF FAILURES IS:'',T40, I5)') BIGF
      ELSE
      ENDIF

***// CALCULATE THE AHAT SUB I'S (WEIGHT ESTIMATES)

      SUMNAI = 0.
      DO 165 I=1, K
```

```
           AHATI(I) = QHATI(I) / QHTMAX
           SUMNAI = SUMNAI + N(I) * AHATI(I)
 165  CONTINUE
      IF(PRNT.EQ.1) THEN
           WRITE(1,0006)
           WRITE(1,C1C15)
           WRITE(1,3334) AHATI
      ELSE
      END IF

***// CALCULATE 1 REPLICATION OF UPPR ALFA C.L. ON SYSTEM RELIABILITY

      DEGFR(LOOP) = 2 * (1 + BIGF)

      DO 170 ALF=1, MAXALF
           CALL MDCHI(1 - ALFA(ALF),DEGFR(LOOP),CHISQ(ALF,LOOP), ERROR)
           QHTUPR(ALF,LOOP) = CHISQ(ALF,LOOP) / (2 * SUMNAI)
           IF(FLAG.EQ.1) THEN
                RHTSTR(ALF,LOOP) = 1 -(CHISQ(ALF,LOOP) / REAL(2*N(1)))
           ELSE
           END IF
*    +     (ALF,LOOP), ALFA(ALF)
***// CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR COMPNTS. IN SERIES

           CALL RHTSRS(QHTUPR(ALF,LOOP), AHATI,K, RSHAT(ALF,LOOP))
*    +T40,F8.5)') RSHAT(ALF,LOOP)

***// CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR BRIDGE STRUCTURE ***

           CALL RHTBRG(QHTUPR(ALF,LOOP),AHATI,K,RSHTBR(ALF,LOOP))
 170  CONTINUE

***// THIS ELSE AND ENDIF ARE FOR THE TEST AGAINST MAXRUN  ***********
      ELSE
           WRITE(1,'('' '',/''PROGRAM EXCEEDED THE MAX NO. OF RUNS'',
     +'' ALLOWED OF:'',I6)') TOTREP
      GOTO 9999

      END IF
      GOTO 10
      END IF
      WRITE(2,'(''UNSORTED RSHAT 1  IS:'',/10(F8.5))')
     +(RSHAT(1,LOOP), LOOP=1, MAXREP)
      WRITE(2,'(''UNSORTED RSHAT 2  IS:'',/10(F8.5))')
     +(RSHAT(2,LOOP), LOOP=1, MAXREP)
      IF(FLAG.EQ.1) THEN
           WRITE(2,'(''UNSORTED RHTSTR 1  IS:'',/10(F8.5))')
     +(RHTSTR(1,LOOP), LOOP=1, MAXREP)
           WRITE(2,'(''UNSORTED RHTSTR 2  IS:'',/10(F8.5))')
     +(RHTSTR(2,LOOP), LOOP=1, MAXREP)
      ELSE
      END IF
      IF(K.EQ.5) THEN
           WRITE(2,'(''UNSORTED RSHTBR 1  IS:'',/10(F8.5))')
     +(RSHTBR(1,LOOP), LOOP=1, MAXREP)
           WRITE(2,'(''UNSORTED RSHTBR 2  IS:'',/10(F8.5))')
```

```
     +(RSHTBR(2,LOOP), LOOP=1, MAXREP)
      ELSE
      END IF

***// SORT THE ARRAYS OF SYSTEM UNRELIABILITIES(1 FOR EACH CONF. LEVEL)

      DO 700 ALF=1, MAXALF
           DO 800 REPS=1, MAXREP
                TRANSQ(REPS) = QHTUPR(ALF,REPS)
                TRANSR(REPS) = RSHAT(ALF,REPS)
                TRNSTR(REPS) = RHTSTR(ALF,REPS)
                TRANBR(REPS) = RSHTBR(ALF,REPS)
 800        CONTINUE
           CALL SHSORT(TRANSQ,KEY1,MAXREP)
           CALL SHSORT(TRANSR,KEY2,MAXREP)
           CALL SHSORT(TRNSTR,KEY3,MAXREP)
           CALL SHSORT(TRANBR,KEY4,MAXREP)
           DO 900 REPS=1, MAXREP
                QHTUPR(ALF,REPS) = TRANSQ(REPS)
                RSHAT(ALF,REPS) = TRANSR(REPS)
                RHTSTR(ALF,REPS) = TRNSTR(REPS)
                RSHTBR(ALF,REPS) = TRANBR(REPS)
 900        CONTINUE
 700  CONTINUE


***// PRINT OUTPUT REPORT HEADINGS **************

      WRITE(1,6666)
      WRITE(1,6667) MAXREP
      WRITE(1,6668) K
      WRITE(1,6669)
      IF(K.EQ.5) THEN
           WRITE(1,6699)
      ELSE
      END IF
      WRITE(1,6670) MSTRQ
      WRITE(1,6671)
      WRITE(1,C1C15)
      WRITE(1,3334) AI
      WRITE(1,0007)
      WRITE(1,C1C15)
      WRITE(1,3334) QI
      WRITE(1,0005)
      WRITE(1,C1C15)
      WRITE(1,3335) N
      WRITE(1,6674)
C     WRITE(2,6666)
C     WRITE(2,6667) MAXREP
C     WRITE(2,6668) K
C     WRITE(2,6669)
C     IF(K.EQ.5) THEN
C          WRITE(1,6699)
C     ELSE
C     END IF
C     WRITE(2,6670) MSTRQ
```

```
C     WRITE(2,6671)
C     WRITE(2,C1C15)
C     WRITE(2,3334) AI
C     WRITE(2,0007)
C     WRITE(2,C1C15)
C     WRITE(2,3334) QI
C     WRITE(2,0005)
C     WRITE(2,C1C15)
C     WRITE(2,3335) N
C     WRITE(2,6674)
C
C     WRITE(2,'(''SORTED RSHAT 1  IS:'',/10(F8.5))')
C    +(RSHAT(1,REPS), REPS=1, MAXREP)
C     WRITE(2,'(''SORTED RSHAT 2  IS:'',/10(F8.5))')
C    +(RSHAT(2,REPS), REPS=1, MAXREP)
C     IF(FLAG.EQ.1) THEN
C          WRITE(2,'(''SORTED RHTSTR 1  IS:'',/10(F8.5))')
C    +(RHTSTR(1,REPS), REPS=1, MAXREP)
C          WRITE(2,'(''SORTED RHTSTR 2  IS:'',/10(F8.5))')
C    +(RHTSTR(2,REPS), REPS=1, MAXREP)
C     ELSE
C     END IF
C     IF(K.EQ.5) THEN
C          WRITE(2,'(''SORTED RSHTBR 1  IS:'',/10(F8.5))')
C    +(RSHTBR(1,REPS), REPS=1, MAXREP)
C          WRITE(2,'(''SORTED RSHTBR 2  IS:'',/10(F8.5))')
C    +(RSHTBR(2,REPS), REPS=1, MAXREP)
C     ELSE
C     END IF

***// COMPUTE THE VALUE RS OF THE TRUE SYSTEM REL. FNCTN.(SERIES SYSTEM)
***// AND FOR THE 5-COMPONENT BRIDGE STRUCTURE
      CALL RSRS(QI,K,RS)
      WRITE(1,'('' '',////''THE TRUE SERIES SYSTEM '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RS
      CALL RBRIDG(QI,K,RSBRDG)
      IF(K.EQ.5) THEN
      WRITE(1,'('' '',////''THE TRUE BRIDGE STRUCTURE '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RSBRDG
      ELSE
      END IF
      WRITE(1,6675)

***// COMPUTE THE DIFFERENCE 'DELTAR' BTWN. RS AND RSHAT OF THE THEO
***// RETICAL QUANTILE GIVEN BY ALFA(MUST USE SORTED RSHAT ARRAY)

      IF(FLAG.EQ.1) THEN
      WRITE(1,5755)
      ELSE
      END IF
      DO 450 ALF=1, MAXALF
           QUANTL(ALF) = MAXREP * (1 - ALFA(ALF))
           DELTAR(ALF) = RS - RSHAT(ALF,QUANTL(ALF))
           DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
           IF(FLAG.EQ.1) THEN
                DELSTR(ALF) = RS - RHTSTR(ALF,QUANTL(ALF))
```

```
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5656) RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5657) DELSTR(ALF)
           ELSE
           END IF
           IF(K.EQ.5) THEN
                DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5666) RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5667) DELBRG(ALF)
           ELSE
           END IF
           WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
           WRITE(1,5556) RSHAT(ALF,QUANTL(ALF))
           WRITE(1,5557) DELTAR(ALF)
 450  CONTINUE
      PRINT *, 'QUANTL(1) IS:', QUANTL(1)
      PRINT *, 'QUANTL(2) IS:', QUANTL(2)

***// FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE //***
***//                ******** RSHAT ********                      //***
      WRITE(1,6676)
      DO 400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 500 REPS=1, MAXREP
                DIFF(REPS) = RS - RSHAT(ALF,REPS)
 500       CONTINUE
           DO 600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                     GO TO 620
                ELSEIF(DIFF(REPS).LT.0.) THEN
                     TRUQNT(ALF) = REPS
                     GO TO 610
                ELSE
                END IF
 600       CONTINUE
 610       IF(TRUQNT(ALF).EQ.0.) THEN
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST'',
     +          '' DIFFERENCE BETWEEN RS AND RSHAT IS:'',F10.5)') DIFF(
     +          MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RSHAT'',
     +           '' AR_ GREATER THAN RS'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
```

```
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 620       END IF
 400  CONTINUE


***// FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE //***
***//       ******** RSHTBR (BRIDGE) *******                      //***

      IF(K.EQ.5) THEN
      DO 401 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 501 REPS=1, MAXREP
                DIFF(REPS) = RSBRDG - RSHTBR(ALF,REPS)
 501       CONTINUE
           DO 601 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                     GO TO 621
               :ELSEIF(DIFF(REPS).LT.0.) THEN
                     TRUQNT(ALF) = REPS
                     GO TO 611
                ELSE
                END IF
 601       CONTINUE
 611       IF(TRUQNT(ALF).EQ.0.) THEN
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST'',
     +          '' DIFFERENCE BETWEEN RSBRDG AND RSHTBR IS:'',
     +          F10.5)') DIFF(MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RSHTBR'',
     +           '' ARE GREATER THAN RSBRDG'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 621       END IF
 401  CONTINUE
      ELSE
      END IF
```

```
***// FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE //***
***//                  ********* RHTSTR *********                  //***

      IF(FLAG.EQ.1) THEN
      DO 4400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 5500 REPS=1, MAXREP
                DIFF(REPS) = RS - RHTSTR(ALF,REPS)
 5500      CONTINUE
           DO 6600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                     GO TO 6620
                ELSEIF(DIFF(REPS).LT.0.) THEN
                     TRUQNT(ALF) = REPS
                     GO TO 6610
                ELSE
                END IF
 6600      CONTINUE
 6610      IF(TRUQNT(ALF).EQ.0.) THEN
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST'',
     +          '' DIFFERENCE BETWEEN RS AND RHTSTR IS:'',
     +          F9.5)') DIFF(MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RHTSTR'',
     +          '' ARE GREATER THAN RS'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 6620      END IF
 4400 CONTINUE
      ELSE
      END IF

***// PRINT THE ARRAYS PERTINENT TO THE OUPUT OF EACH REPLICATION *****

      IF(PRNT.EQ.1) THEN
      I = 1
 185  WRITE(1,REPSHD) ALFA(SELCTA), ALFA(SELCTA),
     +ALFA(SELCTB),ALFA(SELCTB),ALFA(SELCTA),ALFA(SELCTA),ALFA(SELCTB),
     +ALFA(SELCTB)
 175  IF(I.GE.(MAXREP + 1)) THEN
           GOTO 180
```

```
      ELSE
           IF( (I.EQ.71).OR.(I.EQ.211).OR.(I.EQ.351).OR.(I.EQ.491).OR.
     +     (I.EQ.631).OR.(I.EQ.771).OR.(I.EQ.911).OR.(I.EQ.1051) ) THEN
                I = I + 70
                WRITE(1,'(''+'')')
                GOTO 185
           ELSE

           WRITE(1,3336) I, INT(DEGFR(I)), CHISQ(1,I), QHTUPR(1,I),
     +     CHISQ(2,I), QHTUPR(2,I)
           END IF
           IF(I + 70.LE.MAXREP) THEN
                WRITE(1,3337) I+70,INT(DEGFR(I+70)),CHISQ(1,I+70),
     +          QHTUPR(1,I+70),CHISQ(2,I+70),QHTUPR(2,I+70)
           ELSE
           END IF
      I = I + 1
      GOTO 175
180   END IF
      ELSE
      ENDIF
9999  WRITE(1,'(''THE TOTAL NO OF REPS WAS:'',I8)') TOTREP
      WRITE(1,'(''THE TOTAL NO OF EFFECTIVE REPS WAS:'',I8)') LOOP
      WRITE(1,'(''THE TOTAL NO OF NO FAILURE RUNS WAS:'',I8)') ZFAILS
      WRITE(1,'(''AVERAGE  NO. OF COMPONENTS PER REPLICATION WITH '',
     +''NO FAILURES:'',F5.2)') ZFPREP / MAXREP
      WRITE(1,'(''THE TOTAL NO OF RUNS WITH FAILURES WAS:'',I8)') FAILS
0008  FORMAT (/ 3X,'C 1',5X,'C 2',
     +5X,'C 3',5X,'C 4',5X,'C 5',5X,'C 6',5X,'C 7',5X,
     +'C 8',5X,'C 9',5X,'C 10',4X,'C 11',4X,
     +'C 12',4X,'C 13',4X,'C 14',4X,'C 15')
0009  FORMAT(/1X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
     +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')',
     +2X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
     +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')'/)
0001  FORMAT (///'UNIFORM RANDOM DEVIATES ARE:')
0002  FORMAT (///'BERNOULLI TRIALS ARE:')
0003  FORMAT (///'TOTAL NO. OF FAILURES FOR EACH COMPONENT:')
0004  FORMAT (///'ESTIMATED UNRELIABILITY FOR EACH COMPONENT:')
0005  FORMAT (///'TOTAL NUMBER OF MISSION TESTS:')
0006  FORMAT (///'ESTIMATED WEIGHTS FOR EACH COMPONENT:')
0007  FORMAT (///'Q I FOR EACH COMPONENT:')
1111  FORMAT (15F8.5)

2222  FORMAT (/1X,15(I4,4X))
3333  FORMAT (/1X,15(I4,4X))
3334  FORMAT (/15F8.5)
3335  FORMAT (/1X,15(I4,4X))
3336  FORMAT (T3,I4,T9,I3,T13,F11.5,T27,F8.5,T39,F11.5,T53,F8.5)
3337  FORMAT ('+',T67,I4,T73,I3,T77,F11.5,T91,F8.5,T103,F11.5,T117,F8.5)
4442  FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
     +'LIMIT IS:',T50,' 00.000 ')
4443  FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
     +'LIMIT IS:',T50,'100.0000')
4444  FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
     +'LIMIT IS:',T50,F8.4)
```

```
4445 FORMAT (' ',/'THE RSHAT VALUE CLOSEST TO RS IS: ',T51,F8.5)
4446 FORMAT (' ',/'(FIRST NEGATIVE DIFFERENCE)')
4447 FORMAT (' ',/'(ELEMENT PRECEEDING FIRST NEGATIVE DIFFERENCE)')
4448 FORMAT (' ',/'THE RHTSTR VALUE CLOSEST TO RS IS: ',T51,F8.5)
4449 FORMAT (' ',/'THE RSHTBR VALUE CLOSEST TO RSBRDG IS: ',T51,F8.5)
5555 FORMAT (' ',///'THE ',I4,'(1-',F4.3,') QUANTILE IS:',T49,F8.3)
5556 FORMAT (' ',/'THE VALUE OF RSHAT FOR THAT QUANTILE IS:',T51,F8.5)
5557 FORMAT (' ',/'THE DIFFERENCE(RS - RSHAT) IS:',T51,F8.5)
5656 FORMAT (' ',/'THE VALUE OF RHTSTR FOR THAT QUANTILE IS:',T51,F8.5)
5666 FORMAT (' ',/'THE VALUE OF RSHTBR FOR THAT QUANTILE IS:',T51,F8.5)
5657 FORMAT (' ',/'THE DIFFERENCE(RS - RHTSTR) IS:',T51,F8.5)
5667 FORMAT (' ',/'THE DIFFERENCE(RS - RSHTBR) IS:',T51,F8.5)
5755 FORMAT (' ',///'SINCE THE NO. OF MISSION TESTS IS THE SAME FOR',
    +' ALL COMPONENTS THE CLOSED FORM SERIES SYSTEM RELIABILITY ',
    +'''RHTSTR'' IS COMPUTED')
6666 FORMAT ('+','**************************************************',
    +'********** RUN INPUT SETTINGS **********************************',
    +'**********')
6667 FORMAT (' ',//'NUMBER OF REPLICATIONS:',T50,I4)
6668 FORMAT (' ',//'NUMBER OF COMPONENTS:',T50,I4)
6669 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'SERIES')
6699 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'BRIDGE')
6670 FORMAT (' ',//'MASTER UNRELIABILITY USED:',T50,F8.5)
6671 FORMAT (' ',//'INPUT WEIGHTS(A SUB I''S):')
6674 FORMAT ('+',///'**************************************************',
    +'**R U N  R E S U L T S*****************************************',
    +'**********')
6675 FORMAT ('+',///'**************************************************',
    +' ESTIMATE ERRORS ***********************************************',
    +'**********')
6676 FORMAT ('+',///'**************************************************',
    +' TRUE CONFIDENCE LIMITS ****************************************',
    +'**********')
     END
```

APPENDIX H. FORTRAN CODE FOR ALTERNATE PROCEDURE B FOR ESTIMATING THE LOWER CONFIDENCE LIMIT FOR SELECTED SYSTEMS

```
      PROGRAM ZFYSCN
*************************************************************************
*                                                                       *
*      TITLE: BINOMIAL INTERVAL ESTIMATION PROCEDURE                    *
*             ZERO FAILURES ALLOWED; NO SCALING                         *
*     AUTHOR: E. F. BELLINI, LT, USN                                    *
*     MODIFIED BY:  LT VALERIE A. COVINGTON,USN   (MAR 90)
*       DATE: NOV 89                                                    *
*                                                                       *
*     THIS PROGRAM COMPUTES THE TRUE CONFIDENCE LEVEL FOR THE ESTIMATE  *
*     RELIABILITY OF A SERIES AND BRIDGE SYSTEM GIVEN THE RELIABILITY   *
*     OF THEIR COMPONENTS                                               *
*                                                                       *
*     IN ITS PRESENT CONFIGURATION THIS PROGRAM IS SET UP TO RUN 12      *
*     TIMES EACH TIME PRODUCING 1000 REPLICATIONS USING A DIFFERENT     *
*     SET OF INPUT DATA.  RUN THE PROGRAM FROM CMS BY TYPING 'B1 EXEC'. *
*     THE REXX EXEC PROGRAM                                             *
*     'B1' CALLS THE INPUT FILES TO BE READ AND NAMES THE 12 OUTPUT     *
*     FILES RESULTING FROM THE 12 CONSECUTIVE RUNS.  BY EDITING THE     *
*     INDEX COUNTERS I, J, K OF THE 'B1' EXEC ONE CAN RUN ANY USER-     *
*     SPECIFIC RUN FROM JUST ONE RUN TO ALL 12.                         *
*                                                                       *
*     VARIABLES USED                                                    *
*                                                                       *
*          AHATI  : WEIGHT ESTIMATES FOR EACH COMPONENT                 *
*          AI     : INPUT WEIGHTS FOR EACH COMPONENT                    *
*          ALFA   : LEVELS OF SIGNIFICANCE                              *
*          BIGF   : TOTAL NO. OF FAILURES FOR EACH REPLICATION          *
*          CHISQ  : CHI-SQUARE RANDOM VARIABLE VALUE                    *
*          C1C15  : FORMAT LABEL                                        *
*          DEGFR  : DEGREES OF FREEDOM                                  *
*          DELBRG : DIFFERENCE FOR BRIDGE SYSTEM                        *
*          DELSTR : DIFFERENCE FOR SERIES SYSTEM- CLOSED FORM           *
*          DELTAR : DIFFERENCE FOR SERIES SYSTEM                        *
*          DIFF   : DIFFERENCE (TRUE REL. - ESTIMATED REL.)             *
*          EPS    : SMALL QUANTITY(CONSTANT)                            *
*          ERROR  : PARAMETER FOR IMSL ROUTINE                          *
*          FAILS  : COUNTS NO. OF REPLICATIONS WITH AT LST. 1 FAILURE   *
*          FI     : NO. OF FAILURES FOR EACH COMPONENT(ALL MISSION TST) *
*          FLAG   : 1 IF ALL COMP. HAVE SAME NO. OF MISSION TESTS       *
*          INC    : INCREMENT STEP SIZE FOR ROUTINE USMNMX              *
*          KEY1   : ARRAY OF INDECES FOR ROUTINE SHSORT                 *
*          KEY2   : ARRAY OF INDECES FOR ROUTINE SHSORT                 *
*          KEY3   : ARRAY OF INDECES FOR ROUTINE SHSORT                 *
*          KEY4   : ARRAY OF INDECES FOR ROUTINE SHSORT                 *
*          KK     : ARRAY SIZING PARAMETER FOR THE MAX NO OF COMPONENTS *
*          LOOP   : COUNTS NO. OF REPLICATION PERFORMED                 *
*          MAXALF : MAX NO. OF SIGNIFICANT LEVELS DESIRED(ARRAY SIZING) *
```

```
*          MAXREP : MAX NO. OF REPLICATIONS                                  *
*          MAXRUN : MAX NO. OF PROGRAM ITERATIONS ALLOWED                    *
*          MSTRQ  : MASTER UNRELIABILITY(USED WITH AI'S TO CALC. QI'S)       *
*          MULT   : MULTIPLIER FOR RANDOM NO. GENERATOR SRND                 *
*          N      : NO. OF MISSION TEST FOR EACH COMPONENT                   *
*          NIMAX  : MAX NO. OF MISSION TESTS                                 *
*          NIMIM  : MIN NO. OF MISSION TESTS                                 *
*          NINDX  : INDEX NO. OF MAX NO. OF MISSION TESTS                    *
*          NIREAL : NO. OF MISSION TESTS TRANSFORMED TO REAL                 *
*          NMAX   : MAX NO. OF MISSION TESTS FOR OUTPUT CONTROL              *
*          NPRNT  : FLAG FOR DETAILED REPORT OUTPUT                          *
*          PRNT   : SAME AS ABOVE(PARAMETER)                                 *
*          QHATI  : UNRELIABILITY ESTIMATES FOR EACH COMPONENT               *
*          QHTMAX : LARGEST QHATI                                            *
*          QHTUPR : UPPER LIMIT ON SYSTEM UNRELIABILITY                      *
*          QI     : INPUT UNRELIABILIY FOR EACH COMPONENT                    *
*          QINDX  : INDEX                                                    *
*          QUANTL : QUANTILE                                                 *
*          REPSHD : REPLICATIONS HEADING FORMAT NUMBER                       *
*          RHTSTR : SERIES SYSTEM RELIABILITY ESTIMATE(CLOSED FORM)          *
*          RS     : TRUE SERIES SYSTEM RELIABILITY                           *
*          RSBRDG : TRUE BRIDGE SYSTEM RELIABILITY                           *
*          RSHAT  : SERIES SYSTEM RELIABILITY ESTIMATE                       *
*          RSHTBR : BRIDGE SYSTEM RELIABILITY ESTIMATE                       *
*          SEED   : PARAMETER                                                *
*          SELCTA : SIGNIFICANCE LEVEL SELECTION                             *
*          SELCTB : SIGNIFICANCE LEVEL SELECTION                             *
*          SORT   : PARAMETER FOR ROUTINE SRND                               *
*          SUMNAI : SUM OF THE PRODUCT OF NI'S AND AI'S                      *
*          TEMP   : TEMPORARY ARRAY                                          *
*          TOTREP : TOTAL NUMBER OF PROGRAM ITERATIONS                       *
*          TRANBR : TEMPORARY ARRAY                                          *
*          TRANSQ : TEMPORARY ARRAY                                          *
*          TRANSR : TEMPORARY ARRAY                                          *
*          TRIALS : BERNOULLI TRIALS ARRAY (2-DIM)                           *
*          TRNSTR : TEMPORARY ARRAY                                          *
*          TRUQNT : TRUE QUANTILE                                            *
*          UNIRV  : UNIFORM RANDOM DEVIATES (2-DIM)                          *
*          ZFAILS : TOTAL NUMBER OF REPLICATIONS WITH ZERO FAILURES          *
*          ZFPREP : NO. OF COMPNTS. WITH ZERO FAILURES PER REPLICATION       *
*                                                                            *
******************************************************************************

      PARAMETER (KK=10,MAXALF=2,NPRNT=0)
      PARAMETER (MAXREP=1000, MAXRUN=2000, EPS=.000001)
      REAL*4 UNIRV(15,1000),TEMP(1000),QI(KK),AI(KK),AHATI(KK)
      REAL*4 QHATI(KK), NMAX, NNMAX, QHTMAX, CHISQR(5,5), ALFA(MAXALF)
      REAL*4 DF(5),AALFA(5),SUMNAI,RSHAT(MAXALF,MAXREP),RS
      REAL*4 KEY1(MAXREP),KEY2(MAXREP),KEY3(MAXREP),TRNSTR(MAXREP)
      REAL*4 DEGFR(MAXREP), QHTUPR(MAXALF,MAXREP),CHISQ(MAXALF,MAXREP)
      REAL*4 QUPA1(MAXREP), QUPA2(MAXREP),RHTSTR(MAXALF,MAXREP)
      REAL*4 DELTAR(MAXALF), TRANSQ(MAXREP),TRANSR(MAXREP),DIFF(MAXREP)
      REAL*4 DELSTR(MAXALF),NIMIN,NIMAX,NIREAL(KK)
      REAL*4 RSHTBR(MAXALF,MAXREP),DELBRG(MAXALF),KEY4(MAXREP)
      REAL*4 TRANBR(MAXREP), RSBRDG ,MSTRQ
      REAL*4 ZFPREP
```

```
      REAL*4 RSHATI(KK),SI(KK),QHATIU(KK)
      REAL*4 MXQHAT,RI(KK),SUMRN
      REAL*4 QHATMU(MAXALF),CHIVAL(MAXALF),P(KK),PTEMP(10)

      INTEGER SEED, MULT, SORT, TRIALS(15,1000), BIGF, FI(KK), N(KK)
      INTEGER NINDX, QINDX, ERROR, REPS, SELCTA, SELCTK, TOTREP
      INTEGER C1C15, REPSHD, SELCTB, ALF, FLAG, LOOP,PRNT,HFI
      INTEGER QUANTL(MAXALF), TRUQNT(MAXALF),ZFAILS,FAILS,INC

      CHARACTER*8 LOOPS0(MAXREP)

      DATA SEED/123457/, MULT/1/, INC/1/
      DATA AALFA/.01,.05,.9,.95,.99/, DF/1,5,10,30,40/
      DATA ALFA/.20,.050/
      DATA SORT/0/

      ASSIGN 8 TO C1C15
      ASSIGN 9 TO REPSHD

*     CALL COMPRS
      PRNT = NPRNT

      DO 12 I=1,KK
           AI(I) = 9999.
           N(I) = 99999999
   12 CONTINUE

      READ(03,*)K,MSTRQ

      DO 11 I=1,K
      READ(03,*) AI(I),N(I)
   11 CONTINUE


      IF(K.NE.5) THEN
           WRITE(1,'(''WARNING: BRIDGE STRUCTURE '',
     +''ONLY USES THE FIRST 5 COMPONENTS'')')
      ELSE
      END IF

***INITIALIZE THE QHTUPR ARRAY OF UNRELIABILITY REPLICATIONS,   ***
*  RSHAT ARRAY OF ESTIMATE SYSTEM RELIABILITY REPLICATIONS       *
*  AND RHTSTR ARRAY OF EST. SYST. REL. FOR A SERIES SYST WHEN    *
***ALL THE COMPONENT MISSION TESTS ARE EQUAL IN NUMBER          ***

      DO 172 ALF=1,MAXALF
           DO 173 REPS=1,MAXREP
                QHTUPR(ALF,REPS) = 0.
                RSHAT(ALF,REPS) = 0.
                RHTSTR(ALF,REPS) = 0.
                RSHTBR(ALF,REPS) = 0.
                LOOPS0(REPS)=' ****** '
  173       CONTINUE
  172 CONTINUE

***SET FLAG TO 1 IF ALL COMPONENTS HAVE SAME NO. OF MISSION TESTS****
```

```
      FLAG=1
      DO 50 I=1,K -1
           IF((N(I) - N(I+1)).NE.0) THEN
                FLAG=0
           ELSE
           END IF
   50 CONTINUE
      PRINT *, 'FLAG IS:', FLAG

***MAIN PROGRAM OUTER LOOP START(EVERY LOOP IS ONE REPLICATION)***

      ZFPREP = 0.
      ZFAILS = 0
      FAILS = 0
      TOTREP = 0
      LOOP = 0
   10 IF(LOOP.LT.MAXREP) THEN
           LOOP = LOOP + 1
           IF(TOTREP.LT.MAXRUN) THEN
                TOTREP = TOTREP + 1
      SELCTA = 1
      SELCTB = 2

***FILL ARRAY KEY(REPS) WITH INTEGERS 1 TO K TO BE USED AS OUTPUT***
***OF THE SUBROUTINE SHSORT                                      ***

      DO 95 REPS=1, MAXREP
           KEY1(REPS) = REPS
           KEY2(REPS) = REPS
           KEY3(REPS) = REPS
           KEY4(REPS) = REPS
   95 CONTINUE

***CALCULATE NMAX NOT TO PRINT LONGER THAN THE MAX SAMPLE SIZE***

***CALCULATE THE MAXIMUM NO. OF TRIALS AND ITS INDEX NO.***

      CALL IMAX(N,K,NMAX,NINDX)


***CALCULATE THE QI'S FROM THE GIVEN MASTER Q AND THE AI'S***

      DO 115 I=1, K
           QI(I) = MSTRQ * AI(I)
  115 CONTINUE

      DO 120 I=1,15
           DO 125 J=1,500
                UNIRV(I,J) = 999.
                TRIALS(I,J) = 99999
  125      CONTINUE
  120 CONTINUE

*** DRAW UNIFORM (0,1) RV'S AND CONVERT TO BERNOULLI TRIALS***
```

```
      DO 130 I=1, K
           CALL SRND(SEED, TEMP, N(I), MULT, SORT)
           DO 135 J=1, N(I)
                UNIRV(I,J) = TEMP(J)
                IF (UNIRV(I,J).LE. 1 - QI(I)) THEN
                     TRIALS(I,J) = 0
                ELSE
                     TRIALS(I,J) = 1
                END IF
 135  CONTINUE
 130  CONTINUE


***CALCULATE THE NO. OF FAILURES FOR EACH COMPONENT***

      DO 150 I=1, K
           FI(I) = 0
 150  CONTINUE
      IONECT = 0

***CALCULATE THE F SUB I'S AND THE GRAND TOTAL NO. OF FAILURES***
      BIGF = 0
      DO 155 I=1, K
           DO 160 J=1, N(I)
                FI(I) = FI(I) + TRIALS(I,J)
 160          CONTINUE
           IF(FI(I).EQ.0) THEN
                ZFPREP = ZFPREP + 1
           ELSE
           END IF

***CALCULATE THE QHAT SUB I'S: F SUB I'S DIVIDED BY N SUB I'S***
                QHATI(I) = REAL(FI(I)) / N(I)
           BIGF = BIGF + FI(I)
 155  CONTINUE
      IF (FI(2) .EQ. 0) THEN
          ZFPREP=ZFPREP - 1
      ELSE
      ENDIF
      BIGF=BIGF-FI(2)
      FI(2) = 0
      DO 161 I=2,N(2)
         HFI=0
         DO 163 J=1,2
            CALL SRND(SEED, PTEMP(J), N(2), MULT, SORT)
            IF (PTEMP(J) .GT. 1-QI(2)**.5) THEN
                HFI= HFI+1
            ENDIF
 163  CONTINUE
      IF (HFI .EQ. 2) THEN
         FI(2) = FI(2) +1
      ENDIF
 161  CONTINUE
      QHATI(2) = REAL(FI(2)) / N(2)
      BIGF= BIGF + FI(2)
      IF (FI(2) .EQ. 0) THEN
```

```
         ZFPREP = ZFPREP + 1
       ENDIF


***COUNTS NUMBER OF COMPONENTS THAT HAVE FAILED***

       DO 136 I=1,K
          IF (FI(I) .NE. 0) IONECT=IONECT+1
 136   CONTINUE

***CASE WHERE NO COMPONENTS HAVE ANY FAILURES***

       IF(BIGF.EQ.0) THEN
            LOOPS0(LOOP)=' *ZERO* '

***     SERIES ESTIMATE MODIFICATION (NO. OF FAILURES IRRELEVANT)***

          DO 152 I=1,K
             SI(I) = REAL(N(I))-REAL(FI(I))
             RSHATI(I)=SI(I)/(SI(I)+(REAL(FI(I))+1.)
     +        * FIN(.50,2.*(REAL(FI(I))+1.),2*SI(I)))
             QHATIU(I)=1.-RSHATI(I)
 152       CONTINUE

          MXQHAT=0.
          DO 154 I=1,K
             IF (QHATIU(I) .GT. MXQHAT) THEN
                MXQHAT= QHATIU(I)
             ENDIF
 154       CONTINUE

        DO 156 ALF=1,MAXALF
          CALL MDCHI(ALFA(ALF),2*(1.+REAL(BIGF)),CHIVAL(ALF),ERROR)
          SUMRN=0.
          DO 157 I=1,K
             RI(I)=QHATIU(I)/MXQHAT
             SUMRN=SUMRN+RI(I)*REAL(N(I))
 157       CONTINUE
          QHATMU(ALF)=CHIVAL(ALF)/(2*SUMRN)
 156    CONTINUE

        DO 158 ALF=1,MAXALF
          RSHAT(ALF,LOOP)=1.
          DO 159 I=1,K
            RSHAT(ALF,LOOP)=RSHAT(ALF,LOOP)*(1.-(RI(I)*QHATMU(ALF)))
             IF(FLAG.EQ.1) THEN
                 RHTSTR(ALF,LOOP) = RSHAT(ALF,LOOP)
          ELSE
          END IF
 159      CONTINUE
 158    CONTINUE
***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR BRIDGE STRUCTURE***

          DO 141 ALF=1, MAXALF
             DO 142 I=1,K
```

```
                P(I)=1-RI(I)*QHATMU(ALF)
 142          CONTINUE
              RSHTBR(ALF,LOOP)=P(1)*P(4)+P(2)*P(5)+P(1)*P(3)*
     C         P(5)+P(2)*P(3)*P(4)-P(1)*P(2)*P(3)*P(4)-P(1)*
     C         P(2)*P(3)*P(5)-P(1)*P(2)*P(4)*P(5)-P(1)*P(3)*
     C         P(4)*P(5)-P(2)*P(3)*P(4)*P(5)+2*P(1)*P(2)*
     C         P(3)*P(4)*P(5)
 141  CONTINUE

           ZFAILS = ZFAILS + 1
                DEGFR(LOOP) = 2.
                GO TO 10
      ELSE
           FAILS = FAILS + 1
      END IF


***FIND THE MAX OF THE INDIVIDUAL COMPONENT UNRELIABILITIES***

      CALL RMAX(QHATI, K, QHTMAX, QINDX)


***CALCULATE THE AHAT SUB I'S (WEIGHT ESTIMATES)***

      SUMNAI = 0.
      DO 165 I=1, K
           AHATI(I) = QHATI(I) / QHTMAX
           SUMNAI = SUMNAI + N(I) * AHATI(I)
 165  CONTINUE

***1 FAILURE ONLY  SERIES SYST.  ***

      IF (IONFCT .EQ. 1) THEN
         LOOPS0(LOOP)=' *ONE*  '
      ENDIF

***CALCULATE 1 REPLICATION OF UPPR ALFA C.L. ON SYSTEM RELIABILITY***

      DEGFR(LOOP) = 2 * (1 + BIGF)

***SERIES ESTIMATE MODIFICATION (NO. OF FAILURES IRRELEVANT)***

          DO 162 I=1,K
             SI(I) = REAL(N(I))-REAL(FI(I))
             RSHATI(I)=SI(I)/(SI(I)+(REAL(FI(I))+1.)
     +        * FIN(.50,2.*(REAL(FI(I))+1.),2*SI(I)))
             QHATIU(I)=1.-RSHATI(I)
 162      CONTINUE

          MXQHAT=0.
          DO 164 I=1,K
             IF (QHATIU(I) .GT. MXQHAT) THEN
                MXQHAT = QHATIU(I)
             ENDIF
 164      CONTINUE
```

```
      DO 166 ALF=1,MAXALF
         CALL MDCHI(ALFA(ALF),2*(1.+REAL(BIGF)),CHIVAL(ALF),ERROR)
         SUMRN=0.
         DO 167 I=1,K
            RI(I)=QHATIU(I)/MXQHAT
            SUMRN=SUMRN+RI(I)*REAL(N(I))
 167     CONTINUE
         QHATMU(ALF)=CHIVAL(ALF)/(2*SUMRN)
 166  CONTINUE

      DO 168 ALF=1,MAXALF
         RSHAT(ALF,LOOP)=1.
         DO 169 I=1,K
           RSHAT(ALF,LOOP)=RSHAT(ALF,LOOP)*(1.-(RI(I)*QHATMU(ALF)))
            IF(FLAG.EQ.1) THEN
                RHTSTR(ALF,LOOP) = RSHAT(ALF,LOOP)
           ELSE
           END IF
 169     CONTINUE
 168  CONTINUE


***CALCULATE VALUE OF THE SYSTEM RELIABILITY FOR BRIDGE STRUCTURE***

           DO 170 ALF=1, MAXALF
              DO 206 I=1,K
                  P(I)=1-RI(I)*QHATMU(ALF)
 206          CONTINUE
              RSHTBR(ALF,LOOP)=P(1)*P(4)+P(2)*P(5)+P(1)*P(3)*
     C         P(5)+P(2)*P(3)*P(4)-P(1)*P(2)*P(3)*P(4)-P(1)*
     C         P(2)*P(3)*P(5)-P(1)*P(2)*P(4)*P(5)-P(1)*P(3)*
     C         P(4)*P(5)-P(2)*P(3)*P(4)*P(5)+2*P(1)*P(2)*
     C         P(3)*P(4)*P(5)
 170  CONTINUE


***THIS ELSE AND ENDIF ARE FOR THE TEST AGAINST MAXRUN***

      ELSE
           WRITE(1,'('' '',/''PROGRAM EXCEEDED THE MAX NO. OF RUNS'',
     +'' ALLOWED OF:'',I6)') TOTREP
      GOTO 9999

      END IF
      GOTO 10
      END IF

      WRITE(2,'(''UNSORTED RSHAT 1  IS:'',/10(F8.5))')
     +(RSHAT(1,LOOP), LOOP=1, MAXREP)
      WRITE(2,'(''UNSORTED RSHAT 2  IS:'',/10(F8.5))')
     +(RSHAT(2,LOOP), LOOP=1, MAXREP)
      IF(FLAG.EQ.1) THEN
           WRITE(2,'(''UNSORTED RHTSTR 1  IS:'',/10(F8.5))')
     +(RHTSTR(1,LOOP), LOOP=1, MAXREP)
           WRITE(2,'(''UNSORTED RHTSTR 2  IS:'',/10(F8.5))')
     +(RHTSTR(2,LOOP), LOOP=1, MAXREP)
```

```
      ELSE
      END IF
      IF(K.EQ.5) THEN
           WRITE(2,'(''UNSORTED RSHTBR 1  IS:'',/10(F8.5))')
     +(RSHTBR(1,LOOP), LOOP=1, MAXREP)
           WRITE(2,'(''UNSORTED RSHTBR 2  IS:'',/10(F8.5))')
     +(RSHTBR(2,LOOP), LOOP=1, MAXREP)
      ELSE
      END IF
      WRITE (2,'(''ZERO AND ONE FAILURE REPS:'',/10(A8))')
     +  (LOOPS0(LOOP),LOOP=1,MAXREP)

***SORT THE ARRAYS OF SYSTEM UNRELIABILITIES(1 FOR EACH CONF. LEVEL)***

      DO 700 ALF=1, MAXALF
           DO 800 REPS=1, MAXREP
                TRANSQ(REPS) = QHTUPR(ALF,REPS)
                TRANSR(REPS) = RSHAT(ALF,REPS)
                TRNSTR(REPS) = RHTSTR(ALF,REPS)
                TRANBR(REPS) = RSHTBR(ALF,REPS)
 800        CONTINUE
           CALL SHSORT(TRANSQ,KEY1,MAXREP)
           CALL SHSORT(TRANSR,KEY2,MAXREP)
           CALL SHSORT(TRNSTR,KEY3,MAXREP)
           CALL SHSORT(TRANBR,KEY4,MAXREP)
           DO 900 REPS=1, MAXREP
                QHTUPR(ALF,REPS) = TRANSQ(REPS)
                RSHAT(ALF,REPS) = TRANSR(REPS)
                RHTSTR(ALF,REPS) = TRNSTR(REPS)
                RSHTBR(ALF,REPS) = TRANBR(REPS)
 900        CONTINUE
 700  CONTINUE

***PRINT OUTPUT REPORT HEADINGS***

      WRITE(1,6666)
      WRITE(1,6667) MAXREP
      WRITE(1,6668) K
      WRITE(1,6669)
      IF(K.EQ.5) THEN
           WRITE(1,6699)
      ELSE
      END IF
      WRITE(1,6670) MSTRQ
      WRITE(1,6671)
      WRITE(1,C1C15)
      WRITE(1,3334) AI
      WRITE(1,0007)
      WRITE(1,C1C15)
      WRITE(1,3334) QI
      WRITE(1,0005)
      WRITE(1,C1C15)
      WRITE(1,3335) N
      WRITE(1,6674)
```

```
***COMPUTE THE VALUE RS OF THE TRUE SYSTEM REL. FNCTN.(SERIES SYSTEM)***
***  AND FOR THE 5-COMPONENT BRIDGE STRUCTURE***

      CALL RSRS(QI,K,RS)
      WRITE(1,'('' '',////''THE TRUE SERIES SYSTEM '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RS
      CALL RBRIDG(QI,K,RSBRDG)
      IF(K.EQ.5) THEN
      WRITE(1,'('' '',////''THE TRUE BRIDGE STRUCTURE '',
     +''RELIABILITY VALUE IS:'',T51,F8.5)') RSBRDG
      ELSE
      END IF
      WRITE(1,6675)

***COMPUTE THE DIFFERENCE 'DELTAR' BTWN. RS AND RSHAT OF THE THEO***
***RETICAL QUANTILE GIVEN BY ALFA(MUST USE SORTED RSHAT ARRAY)***

      IF(FLAG.EQ.1) THEN
      WRITE(1,5755)
      ELSE
      END IF
      DO 450 ALF=1, MAXALF
           QUANTL(ALF) = MAXREP * (1 - ALFA(ALF))
           DELTAR(ALF) = RS - RSHAT(ALF,QUANTL(ALF))
           DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
           IF(FLAG.EQ.1) THEN
                DELSTR(ALF) = RS - RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5656) RHTSTR(ALF,QUANTL(ALF))
                WRITE(1,5657) DELSTR(ALF)
           ELSE
           END IF
           IF(K.EQ.5) THEN
                DELBRG(ALF) = RSBRDG - RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
                WRITE(1,5666) RSHTBR(ALF,QUANTL(ALF))
                WRITE(1,5667) DELBRG(ALF)
           ELSE
           END IF
           WRITE(1,5555) MAXREP, ALFA(ALF), REAL(QUANTL(ALF))
           WRITE(1,5556) RSHAT(ALF,QUANTL(ALF))
           WRITE(1,5557) DELTAR(ALF)
 450  CONTINUE
      PRINT *, 'QUANTL(1) IS:', QUANTL(1)
      PRINT *, 'QUANTL(2) IS:', QUANTL(2)

***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***              ******** RSHAT *******                        ***

      WRITE(1,6676)
      DO 400 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 500 REPS=1, MAXREP
                DIFF(REPS) = RS - RSHAT(ALF,REPS)
 500       CONTINUE
           DO 600 REPS=1, MAXREP
```

```
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                     GO TO 620
                ELSEIF(DIFF(REPS).LT.0.) THEN
                     TRUQNT(ALF) = REPS
                     GO TO 610
                ELSE
                END IF
 600       CONTINUE
 610       IF(TRUQNT(ALF).EQ.0.) THEN
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST'',
     +          '' DIFFERENCE BETWEEN RS AND RSHAT IS:'',F10.5)') DIFF(
     +          MAXREP)
           ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RSHAT'',
     +           '' ARE GREATER THAN RS'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4445) RSHAT(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 620       END IF
 400  CONTINUE


***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***        ******** RSHTBR (BRIDGE) *******                    ***

      IF(K.EQ.5) THEN
      DO 401 ALF=1,MAXALF
      TRUQNT(ALF) = 0
           DO 501 REPS=1, MAXREP
                DIFF(REPS) = RSBRDG - RSHTBR(ALF,REPS)
 501       CONTINUE
           DO 601 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                     TRUQNT(ALF) = REPS
                     WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +               F8.4)')
     +               (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                     GO TO 621
                ELSEIF(DIFF(REPS).LT.0.) THEN
                     TRUQNT(ALF) = REPS
                     GO TO 611
                ELSE
```

```
                END IF
 601        CONTINUE
 611        IF(TRUQNT(ALF).EQ.0.) THEN
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST'',
     +          '' DIFFERENCE BETWEEN RSBRDG AND RSHTBR IS:'',
     +          F10.5)') DIFF(MAXREP)
            ELSEIF(TRUQNT(ALF).EQ.1.) THEN
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'('' '',/''ALL RSHTBR'',
     +           '' ARE GREATER THAN RSBRDG'')')
            ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +      THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
            ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4449) RSHTBR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 621        END IF
 401    CONTINUE
        ELSE
        END IF


***FIND THE TRUE CONFIDENCE LEVEL OF THE SYSTEM REL. ESTIMATE***
***                ******** RHTSTR ********                   ***

        IF(FLAG.EQ.1) THEN
        DO 4400 ALF=1,MAXALF
        TRUQNT(ALF) = 0
            DO 5500 REPS=1, MAXREP
                DIFF(REPS) = RS - RHTSTR(ALF,REPS)
 5500       CONTINUE
            DO 6600 REPS=1, MAXREP
                IF(ABS(DIFF(REPS)).LE.EPS) THEN
                    TRUQNT(ALF) = REPS
                    WRITE(1,'('' '',/''TRUE CONFIDENCE LIMIT IS:'',
     +              F8.4)')
     +              (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                    GO TO 6620
                ELSEIF(DIFF(REPS).LT.0.) THEN
                    TRUQNT(ALF) = REPS
                    GO TO 6610
                ELSE
                END IF
 6600       CONTINUE
 6610       IF(TRUQNT(ALF).EQ.0.) THEN
                WRITE(1,4443) ALFA(ALF)
                WRITE(1,'('' '',/''THE SMALLEST'',
     +          '' DIFFERENCE BETWEEN RS AND RHTSTR IS:'',
     +          F9.5)') DIFF(MAXREP)
            ELSEIF(TRUQNT(ALF).EQ.1.) THEN
```

```
                WRITE(1,4442) ALFA(ALF)
                WRITE(1,'(''  '',/''ALL RHTSTR'',
     +          '' ARE GREATER THAN RS'')')
           ELSEIF(ABS(DIFF(TRUQNT(ALF))).LE.ABS(DIFF(TRUQNT(ALF) - 1)))
     +     THEN
                WRITE(1,4444) ALFA(ALF),
     +          (TRUQNT(ALF) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF))
                WRITE(1,4446)
           ELSE
                WRITE(1,4444) ALFA(ALF),
     +          ((TRUQNT(ALF)-1) / REAL(MAXREP)) * 100.
                WRITE(1,4448) RHTSTR(ALF,TRUQNT(ALF)-1)
                WRITE(1,4447)
 6620      END IF
 4400 CONTINUE
      ELSE
      END IF

***PRINT THE ARRAYS PERTINENT TO THE OUPUT OF EACH REPLICATION***

      IF(PRNT.EQ.1) THEN
      I = 1
 185  WRITE(1,REPSHD) ALFA(SELCTA), ALFA(SELCTA),
     +ALFA(SELCTB),ALFA(SELCTB),ALFA(SELCTA),ALFA(SELCTA),ALFA(SELCTB),
     +ALFA(SELCTB)
 175  IF(I.GE.(MAXREP + 1)) THEN
           GOTO 180
      ELSE
           IF( (I.EQ.71).OR.(I.EQ.211).OR.(I.EQ.351).OR.(I.EQ.491).OR.
     +     (I.EQ.631).OR.(I.EQ.771).OR.(I.EQ.911).OR.(I.EQ.1051) ) THEN
                I = I + 70
                WRITE(1,'(''+'')')
                GOTO 185
           ELSE

           WRITE(1,3336) I, INT(DEGFR(I)), CHISQ(1,I), QHTUPR(1,I),
     +     CHISQ(2,I), QHTUPR(2,I)
           END IF
           IF(I + 70.LE.MAXREP) THEN
                WRITE(1,3337) I+70,INT(DEGFR(I+70)),CHISQ(1,I+70),
     +          QHTUPR(1,I+70),CHISQ(2,I+70),QHTUPR(2,I+70)
           ELSE
           END IF
      I = I + 1
      GOTO 175
 180  END IF
      ELSE
      ENDIF
 9999 WRITE(1,'(''THE TOTAL NO OF REPS WAS:'',I8)') TOTREP
      WRITE(1,'(''THE TOTAL NO OF EFFECTIVE REPS WAS:'',I8)') LOOP
      WRITE(1,'(''THE TOTAL NO OF NO FAILURE RUNS WAS:'',I8)') ZFAILS
      WRITE(1,'(''AVERAGE  NO. OF COMPONENTS PER REPLICATION WITH '',
     +''NO FAILURES:'',F5.2)') ZFPREP / MAXREP
      WRITE(1,'(''THE TOTAL NO OF RUNS WITH FAILURES WAS:'',I8)') FAILS
 0008 FORMAT (/ 3X,'C 1',5X,'C 2',
```

```
     +5X,'C 3',5X,'C 4',5X,'C 5',5X,'C 6',5X,'C 7',5X,
     +'C 8',5X,'C 9',5X,'C 10',4X,'C 11',4X,
     +'C 12',4X,'C 13',4X,'C 14',4X,'C 15')
0009 FORMAT(/1X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
     +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')',
     +2X,'REP NO',2X,'DF',1X,'CHISQR(',F4.3,')',1X,
     +'QHTUPR(',F4.3,')',1X,'CHISQR(',F4.3,')',1X,'QHTUPR(',F4.3,')'/)
0001 FORMAT (///'UNIFORM RANDOM DEVIATES ARE:')
0002 FORMAT (///'BERNOULLI TRIALS ARE:')
0003 FORMAT (///'TOTAL NO. OF FAILURES FOR EACH COMPONENT:')
0004 FORMAT (///'ESTIMATED UNRELIABILITY FOR EACH COMPONENT:')
0005 FORMAT (///'TOTAL NUMBER OF MISSION TESTS:')
0006 FORMAT (///'ESTIMATED WEIGHTS FOR EACH COMPONENT:')
0007 FORMAT (///'Q I FOR EACH COMPONENT:')
1111 FORMAT (15F8.5)

2222 FORMAT (/1X,15(I4,4X))
3333 FORMAT (/1X,15(I4,4X))
3334 FORMAT (/15F8.5)
3335 FORMAT (/1X,15(I4,4X))
3336 FORMAT (T3,I4,T9,I3,T13,F11.5,T27,F8.5,T39,F11.5,T53,F8.5)
3337 FORMAT ('+',T67,I4,T73,I3,T77,F11.5,T91,F8.5,T103,F11.5,T117,F8.5)
4442 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
    +'LIMIT IS:',T50,' 00.000 ')
4443 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
    +'LIMIT IS:',T50,'100.0000')
4444 FORMAT (' ',///'THE RESULTING (1 - ',F4.3,') CONFIDENCE ',
    +'LIMIT IS:',T50,F8.4)
4445 FORMAT (' ',/'THE RSHAT VALUE CLOSEST TO RS IS: ',T51,F8.5)
4446 FORMAT (' ',/'(FIRST NEGATIVE DIFFERENCE)')
4447 FORMAT (' ',/'(ELEMENT PRECEEDING FIRST NEGATIVE DIFFERENCE)')
4448 FORMAT (' ',/'THE RHTSTR VALUE CLOSEST TO RS IS: ',T51,F8.5)
4449 FORMAT (' ',/'THE RSHTBR VALUE CLOSEST TO RSBRDG IS: ',T51,F8.5)
5555 FORMAT (' ',///'THE ',I4,'(1-',F4.3,') QUANTILE IS:',T49,F8.3)
5556 FORMAT (' ',/'THE VALUE OF RSHAT FOR THAT QUANTILE IS:',T51,F8.5)
5557 FORMAT (' ',/'THE DIFFERENCE(RS - RSHAT) IS:',T51,F8.5)
5656 FORMAT (' ',/'THE VALUE OF RHTSTR FOR THAT QUANTILE IS:',T51,F8.5)
5666 FORMAT (' ',/'THE VALUE OF RSHTBR FOR THAT QUANTILE IS:',T51,F8.5)
5657 FORMAT (' ',/'THE DIFFERENCE(RS - RHTSTR) IS:',T51,F8.5)
5667 FORMAT (' ',/'THE DIFFERENCE(RS - RSHTBR) IS:',T51,F8.5)
5755 FORMAT (' ',///'SINCE THE NO. OF MISSION TESTS IS THE SAME FOR',
    +' ALL COMPONENTS THE CLOSED FORM SERIES SYSTEM RELIABILITY ',
    +'''RHTSTR'' IS COMPUTED')
6666 FORMAT ('+','**********',
    +'********** RUN INPUT SETTINGS **********',
    +'**********')
6667 FORMAT (' ',//'NUMBER OF REPLICATIONS:',T50,I4)
6668 FORMAT (' ',//'NUMBER OF COMPONENTS:',T50,I4)
6669 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'SERIES')
6699 FORMAT (' ',//'SYSTEM RELIABILITY FUNCTION:',T50,'BRIDGE')
6670 FORMAT (' ',//'MASTER UNRELIABILITY USED:',T50,F8.5)
6671 FORMAT (' ',//'INPUT WEIGHTS(A SUB I''S):')
6674 FORMAT ('+',///'**********',
    +'**R U N  R E S U L T S**********',
    +'**********')
6675 FORMAT ('+',///'**********',
```

```
     +' ESTIMATE ERRORS ***************************************************',
     +'****************')
6676 FORMAT ('+',///'***************************************************',
     +' TRUE CONFIDENCE LIMITS ***************************************',
     +'****************')
      END
```

```
C   IMSL ROUTINE NAME   - USMNMX                                          USMN0010
C                                                                         USMN0020
C-------------------------------------------------------------------------USMN0030
C                                                                         USMN0040
C   COMPUTER            - IBM/SINGLE                                      USMN0050
C                                                                         USMN0060
C   LATEST REVISION     - JANUARY 1, 1978                                 USMN0070
C                                                                         USMN0080
C   PURPOSE             - DETERMINATION OF THE MINIMUM AND MAXIMUM        USMN0090
C                           VALUES OF A VECTOR                            USMN0100
C                                                                         USMN0110
C   USAGE               - CALL USMNMX (X,N,INC,XMIN,XMAX)                 USMN0120
C                                                                         USMN0130
C   ARGUMENTS    X      - INPUT VECTOR OF LENGTH N FROM WHICH MINIMUM,    USMN0140
C                           MAXIMUM VALUES ARE TO BE TAKEN.               USMN0150
C                N      - LENGTH OF THE INPUT VECTOR X. (INPUT)           USMN0160
C                INC    - DISPLACEMENT BETWEEN CONSECUTIVE VALUES OF X    USMN0170
C                           TO BE CONSIDERED.                             USMN0180
C                XMIN   - OUTPUT SCALAR CONTAINING MINIMUM VALUE OF X.    USMN0190
C                XMAX   - OUTPUT SCALAR CONTAINING MAXIMUM VALUE OF X.    USMN0200
C                                                                         USMN0210
C   PRECISION/HARDWARE  - SINGLE AND DOUBLE/H32                           USMN0220
C                       - SINGLE/H36,H48,H60                              USMN0230
C                                                                         USMN0240
C   REQD. IMSL ROUTINES - NONE REQUIRED                                   USMN0250
C                                                                         USMN0260
C   NOTATION            - INFORMATION ON SPECIAL NOTATION AND             USMN0270
C                           CONVENTIONS IS AVAILABLE IN THE MANUAL        USMN0280
C                           INTRODUCTION OR THROUGH IMSL ROUTINE UHELP    USMN0290
C                                                                         USMN0300
C   COPYRIGHT           - 1978 BY IMSL, INC. ALL RIGHTS RESERVED.         USMN0310
C                                                                         USMN0320
C   WARRANTY            - IMSL WARRANTS ONLY THAT IMSL TESTING HAS BEEN   USMN0330
C                           APPLIED TO THIS CODE. NO OTHER WARRANTY,      USMN0340
C                           EXPRESSED OR IMPLIED, IS APPLICABLE.          USMN0350
C                                                                         USMN0360
C-------------------------------------------------------------------------USMN0370
C                                                                         USMN0380
      SUBROUTINE USMNMX (X,N,INC,XMIN,XMAX)                               USMN0390
C                                                                         USMN0400
      DIMENSION          X(N)                                             USMN0410
C                                  FIRST EXECUTABLE STATEMENT             USMN0420
      XMIN = X(1)                                                         USMN0430
      XMAX = X(1)                                                         USMN0440
      DO 10 I=1,N,INC                                                     USMN0450
         IF (X(I) .GE. XMIN) GO TO 5                                      USMN0460
         XMIN = X(I)                                                      USMN0470
         GO TO 10                                                         USMN0480
    5    IF (X(I) .GT. XMAX) XMAX = X(I)                                  USMN0490
   10 CONTINUE                                                            USMN0500
      RETURN                                                              USMN0510
```

```
      END                                                               USMN0520
C     .....                                                             SORT0010
C                                                                       SORT0020
C  A. IDENTIFICATION:                                                   SORT0030
C     TITLE:       NUMERICAL SORT                                       SORT0040
C     ID:          M1-NPG-SHSORT (F-IV)                                 SORT0050
C     PROGRAMMER:  R. BRUNELL                                           SORT0060
C     DATE:        MARCH 1968                                           SORT0070
C     MODIFIED:    DEC. 1973   BY L. NOLAN                              SORT0080
C                                                                       SORT0090
C  B. PURPOSE:                                                          SORT0100
C     TO SORT, IN ASCENDING ORDER, AN ARRAY OF SINGLE PRECISION REAL    SORT0110
C     NUMBERS BY THE METHOD OF SHELL, AND TO PRODUCE AN ARRAY OF INDEXESSORT0120
C     SO USER CAN RE-ORDER OTHER CORRESPONDING INFORMATION ACCORDING TO SORT0130
C     ASCENDING VALUES OF "A".                                          SORT0140
C                                                                       SORT0150
C  C. USAGE:                                                            SORT0160
C     1. CALLING STATEMENT:                                             SORT0170
C        CALL SHSORT(A,KEY,N)                                           SORT0180
C     2. ARGUMENTS:                                                     SORT0190
C          A - ARRAY OF NUMBERS TO BE SORTED. THIS ARRAY IS SORTED      SORT0200
C              (RE-ORDERED) BY "SHSORT".                                SORT0210
C        KEY - ARRAY, DIMENSIONED AT LEAST N IN CALLING PROGRAM, TO BE  SORT0220
C              FILLED BY USER WITH INTEGERS FROM 1 TO N.  AFTER EXIT    SORT0230
C              FROM SHSORT, KEY(1) WILL CONTAIN THE ORIGINAL INDEX OF   SORT0240
C              THE SMALLEST ELEMENT OF "A"; KEY(2) WILL CONTAIN THE     SORT0250
C              ORIGINAL INDEX OF THE NEXT-TO-SMALLEST ELEMENT OF "A";   SORT0260
C              ETC.  KEY(N) WILL CONTAIN THE ORIGINAL INDEX OF THE      SORT0270
C              LARGEST ELEMENT OF "A".                                  SORT0280
C          N - NUMBER OF MEMBERS IN ARRAYS "A" AND "KEY".               SORT0290
C                                                                       SORT0300
C  D. REFERENCES:                                                       SORT0310
C     1. "ALGORITHM 201, SHELLSORT", BOOTHROYD, J., "COMMUNICATIONS OF  SORT0320
C         ACM", VOL 6, NO 8, AUGUST 1963, P.445.                        SORT0330
C     2. "CERTIFICATION OF ALGORITHM 201", BATTY,M.A., "COMMUNICATIONS  SORT0340
C         OF ACM", VOL 7, NO 6, JUNE 1964, P.349.                       SORT0350
C                                                                       SORT0360


      SUBROUTINE SHSORT(A,KEY,N)                                        SORT0370
      DIMENSION A(N),KEY(N)                                             SORT0380
      M1=1                                                              SORT0390
    6 M1=M1*2                                                           SORT0400
      IF (M1 .LE. N)  GO TO 6                                           SORT0410
      M1=M1/2-1                                                         SORT0420
      MM=MAX0(M1/2,1)                                                   SORT0430
      GO TO 21                                                          SORT0440
   20 MM=MM/2                                                           SORT0450
      IF (MM .LE. 0)  GO TO 100                                         SORT0460
   21 K=N-MM                                                            SORT0470
   22 DO 1 J=1,K                                                        SORT0480
      II=J                                                              SORT0490
   11 IM=II+MM                                                          SORT0500
      IF (A(IM) .GE. A(II))  GO TO 1                                    SORT0510
      TEMP=A(II)                                                        SORT0520
      IT=KEY(II)                                                        SORT0530
```

```
      A(II)=A(IM)                                                       SORT0540
      KEY(II)=KEY(IM)                                                   SORT0550
      A(IM)=TEMP                                                        SORT0560
      KEY(IM)=IT                                                        SORT0570
      II=II-MM                                                          SORT0580
      IF (II .GT. 0)  GO TO 11                                          SORT0590
    1 CONTINUE                                                          SORT0600
      GO TO 20                                                          SORT0610
  100 RETURN                                                            SORT0620
      END                                                               SORT0630



      SUBROUTINE RHTSRS(QHTUP,AAHTI,N,RRSHAT)
***// THIS ROUTINE CALCULATES THE VALUE OF THE SYSTEM RELIABILITY OF A
***// SERIES SYSTEM OF 'N' NO. OF COMPONENTS WHICH HAVE UNRELIABILITY
***// 'QHTUP'.  THE FINAL SYSTEM RELIABILITY VALUE PASSED IS 'RRSHAT'
      REAL*4 QHTUP, RRSHAT, AAHTI(N)
      INTEGER I, N
      RRSHAT = 1.
      DO 100 I=1, N
           RRSHAT = RRSHAT * (1 -(AAHTI(I)* QHTUP))
 100  CONTINUE
      END


      SUBROUTINE RSRS(QIS,N,RRS)
***// THIS ROUTINE CALCULATES THE VALUE OF THE SYSTEM RELIABILITY OF A
***// SERIES SYSTEM OF 'COMP' NO. OF COMPONENTS WHICH HAVE UNRELIABILITY
***// 'QIS'.  THE FINAL SYSTEM RELIABILITY VALUE PASSED IS 'RRS'
      REAL*4 QIS(N), RRS
      INTEGER I, N
      RRS = 1.
      DO 100 I=1, N
           RRS = RRS * (1 - QIS(I))
 100  CONTINUE
      END


***// THIS SUBROUTINE CALCULATES THE ESTIMATED RELIABILITY OF A
***// 5-COMPONENT BRIDGE STRUCTURE.(ONLY CARRIED OUT TO THE Q-CUBED TERM
      SUBROUTINE RHTBRG(QHTUP,AHT,N,RRBRDG)
      REAL*4 QHTUP, RRBRDG, AHT(N)
      INTEGER N
*     PRINT *, 'THE VALUES FOR AHAT PASSED ARE:',AHT
      RRBRDG=1-((QHTUP**2)*(AHT(1)*AHT(2)+AHT(4)*AHT(5)))-
     C((QHTUP**3)*(AHT(1)*AHT(3)*AHT(5)+AHT(2)*AHT(3)*AHT(4)))+
     C((QHTUP**4)*(AHT(1)*AHT(2)*AHT(3)*AHT(4)+AHT(1)*AHT(2)*AHT(3)*
     CAHT(5)+AHT(1)*AHT(2)*AHT(4)*AHT(5)+AHT(1)*AHT(3)*AHT(4)*AHT(5)+
     CAHT(2)*AHT(3)*AHT(4)*AHT(5)))-
     C2*((QHTUP**5)*(AHT(1)*AHT(2)*AHT(3)*AHT(4)*AHT(5)))
*     PRINT *, 'COMPUTED RRBRDG IS:', RRBRDG
      END


      SUBROUTINE CPARE(FI,K,BFLAG)
```

```
      INTEGER BFLAG,FI(K)
      BFLAG=0
      IF ((FI(1) .EQ. 0) .AND. (FI(3) .EQ. 0) .AND.
     +    (FI(5) .EQ. 0)) THEN
            BFLAG=0
      ELSE IF ((FI(1) .EQ. 0) .AND. (FI(4) .EQ. 0)) THEN
            BFLAG = 0
      ELSE IF ((FI(2) .EQ. 0) .AND. (FI(5) .EQ. 0)) THEN
            BFLAG = 0
      ELSE IF ((FI(2) .EQ. 0) .AND. (FI(3) .EQ. 0) .AND.
     +   (FI(4) .EQ. 0)) THEN
            BFLAG = 0
      ELSE IF (((FI(1) .EQ. 1) .AND. (FI(2) .EQ. 1)) .AND.
     +         ((FI(2) .EQ. 0) .AND. (FI(4) .EQ. 0) .AND.
     +         (FI(5) .EQ. 0))) THEN
            BFLAG = 1
      ELSE IF (((FI(4) .EQ. 1) .AND. (FI(5) .EQ. 1)) .AND.
     +         ((FI(1) .EQ. 0) .AND. (FI(2) .EQ. 0) .AND.
     +         (FI(3) .EQ. 0))) THEN
            BFLAG = 1
      ELSE IF (((FI(2) .EQ. 0) .AND. (FI(4) .EQ. 0)) .AND.
     +         ((FI(1) .EQ. 1) .AND. (FI(3) .EQ. 1) .AND.
     +         (FI(5) .EQ. 1))) THEN
            BFLAG = 1
      ELSE IF (((FI(1) .EQ. 0) .AND. (FI(5) .EQ. 0)) .AND.
     +         ((FI(2) .EQ. 1) .AND. (FI(3) .EQ. 1) .AND.
     +         (FI(4) .EQ. 1))) THEN
            BFLAG = 1
      ELSE
            BFLAG = 2
      ENDIF

      RETURN
      END


***// THIS SUBROUTINE CALCULATES THE "TRUE" RELIABILITY OF A 5-COMPONENT
***// BRIDGE STRUCTURE
      SUBROUTINE RBRIDG(QI,N,RRSS)
      REAL*4 QI(N), RRSS
      INTEGER N
      IF(N.NE.5) THEN
           WRITE(1,'(''WARNING: BRIDGE STRUCTURE ONLY USES '',
     +''THE FIRST 5 COMPONENTS'')')
      ELSE
      END IF
      RRSS=(1-QI(1))*(1-QI(4))+(1-QI(2))*(1-QI(5))+(1-QI(1))*(1-QI(3))*
     C(1-QI(5))+(1-QI(2))*(1-QI(3))*(1-QI(4))-(1-QI(1))*(1-QI(2))*
     C(1-QI(3))*(1-QI(4))-(1-QI(1))*(1-QI(2))*(1-QI(3))*(1-QI(5))-
     C(1-QI(1))*(1-QI(2))*(1-QI(4))*(1-QI(5))-(1-QI(1))*(1-QI(3))*
     C(1-QI(4))*(1-QI(5))-(1-QI(2))*(1-QI(3))*(1-QI(4))*(1-QI(5))+
     C2*(1-QI(1))*(1-QI(2))*(1-QI(3))*(1-QI(4))*(1-QI(5))
      END
```

LIST OF REFERENCES

1. Mann, Nancy R. and Grubbs, Frank E., *Approximate Optimum Confidence Bounds for System Reliability Based on Component Test Data*, Technometrics 16, pp. 335-47, 1974.

2. Myhre, J., Rosenfeld, A., and Saunders, S., *Determining Confidence Bounds for Highly Reliable Coherent Systems Based on a Paucity of Component Failures*, Naval Research Logistics Quarterly, 25, June 1978.

3. Easterling, Robert G., *Approximate Confidence Limits for System Reliability*, Journal of the American Statistical Association 67, March 1972.

4. Winterbottom, Alan, *Lower Confidence Limits for Series System Reliability from Binomial Subsystem Data*, Journal of the American Statistical Association 69, September 1974.

5. Lee, Hyeon-Soo, *Approximate Interval Estimation Methods for the Reliability of Systems Using Component Data With Exponential and Weibull Distributions*, M.S. Thesis, Naval Postgraduate School, Monterey, California, September 1989.

6. Lomnicki, Z.A., *Two Terminal Series-Parallel Networks*, Advances in Applied Probability 4, pp.109-150,1973.

7. *Confidence Limits For Attributes Data*, LMSC-803324, Lockheed Missiles and Space Company.

8. Bellini, E.F., *Approximate Interval Estimation Methods for the Reliability of Systems Using Discrete Component Data*, M.S. Thesis, Naval Postgraduate School, Monterey, California, September 1990.

BIBLIOGRAPHY

Bain, L.J. and Engelhardt, M., *Introduction to Probability and Mathematical Statistics*, Duxbury Press, Boston, 1987.

Mann, N.R., Schafer, R.E., and Signpurwalla, N.D., *Methods for Statistical Analysis of Reliability and Life Data*, John Wiley and Sons, Inc., New York, pp. 487-524, 1975.

Lloyd, D. and Lipow, M., *Reliability Management, Methods, and Mathematics*, 2nd Edition, American Society for Quality Control, 1984.

INITIAL DISTRIBUTION LIST

		No. Copies
1.	Defense Technical Information Center Cameron Station Alexandria, VA 22304-6145	2
2.	Library, Code 52 Naval Postgraduate School Monterey, CA 93943-5002	2
3.	Professor W. Max Woods Naval Postgraduate School, Code OR-Wo Monterey, CA 93943-5000	4
4.	Professor Lyn R. Whitaker Naval Postgraduate School, Code OR-Wh Monterey, CA 93943-5000	1
5.	Chief of Naval Operations (OP-81) Department of the Navy Washington, DC 20350	1
6.	Base Library FL 4887 Luke Air Force Base, AZ 85309	2
7.	LT Valerie A. Covington, USN P.O. Box 62 Litchfield Park, AZ 85340	3